

Note: This is a reference cited in *AP 42, Compilation of Air Pollutant Emission Factors, Volume I Stationary Point and Area Sources*. AP42 is located on the EPA web site at www.epa.gov/ttn/chief/ap42/

The file name refers to the reference number, the AP42 chapter and section. The file name "ref02_c01s02.pdf" would mean the reference is from AP42 chapter 1 section 2. The reference may be from a previous version of the section and no longer cited. The primary source should always be checked.

AP-42 Section Number: 9.5.2

Reference Number: 4

Title: KSI-2 & KSI-3 Continuous
Smokehouses Stack Emissions Testing

Hillshire Farms & Kahn's

September 1991

Hillshire Farm

AP-42 Section 9.5.2
Reference 4
Report Sect. 4
Reference 2

New London, WI

Report to

HILLSHIRE FARM & KAHN'S
New London, Wisconsin

KSI-2 Smokehouse

Sept 20, 1991

KSI-2 & KSI-3 CONTINUOUS SMOKEHOUSES
STACK EMISSIONS TESTING

September 19 & 20, 1991

KSI-3 Smokehouse

Sept 19, 1991

Received: 11/20/91



ETC

Reviewed: 1/2/92

Report to
HILLSHIRE FARM & KAHN'S
New London, Wisconsin

for

KSI-2 & KSI-3 CONTINUOUS SMOKEHOUSES
STACK EMISSIONS TESTING

September 19 & 20, 1991

by

ENVIRONMENTAL TECHNOLOGY & ENGINEERING CORPORATION
13020 W. Bluemound Rd., Elm Grove, Wisconsin 53122
(414) 784-2434

SUMMARY

Particulate Emissions

The particulate matter emission limit specified for KSI-2 in the permit is 1.824 lb/hr. The results of the KSI-2 particulate testing were as follows:

<u>Test</u>	Particulate into Scrubber	Particulate Emissions
	<u>Rate</u>	<u>Rate</u>
1	5.38 lb/hr	1.95 lb/hr
2	4.86 lb/hr	1.45 lb/hr
3	5.81 lb/hr	1.55 lb/hr
---	-----	-----
Avg	5.35 lb/hr	1.65 lb/hr

The particulate matter emission limit specified for KSI-3 in the permit is 1.824 lb/hr. The results of the KSI-3 particulate testing were as follows:

<u>Test</u>	Particulate into Scrubber	Particulate Emissions
	<u>Rate</u>	<u>Rate</u>
1	6.34 lb/hr	1.34 lb/hr
2	5.33 lb/hr	1.42 lb/hr
3	4.87 lb/hr	1.29 lb/hr
---	-----	-----
Avg	5.51 lb/hr	1.35 lb/hr

Formaldehyde Emissions

The formaldehyde emission limit specified for KSI-2 and KSI-3 in the permit is 0.007 lb/hr, however, a footnote in the permit indicates that this limit may be subject to change pending the test results. The results of the KSI-2 formaldehyde testing were as follows:

<u>Test</u>	Formaldehyde into Scrubber	Formaldehyde Emissions
	<u>Rate</u>	<u>Rate</u>
1	0.066 lb/hr	0.029 lb/hr
2	0.071 lb/hr	0.039 lb/hr
3	0.064 lb/hr	0.030 lb/hr
---	-----	-----
Avg	0.067 lb/hr	0.033 lb/hr

The results of the KSI-3 formaldehyde testing were as follows:

KSI-3	Formaldehyde into Scrubber	Formaldehyde Emissions
<u>Test</u>	<u>Rate</u>	<u>Rate</u>
1	0.071 lb/hr	0.035 lb/hr
2	0.057 lb/hr	0.026 lb/hr
3	0.067 lb/hr	0.034 lb/hr
---	---	---
Avg	0.065 lb/hr	0.032 lb/hr

Acetic Acid Emissions

The acetic acid emission limit specified for KSI-2 and KSI-3 in the permit is 0.303 lb/hr. The results of the KSI-2 acetic acid testing were as follows:

KSI-2	Acetic Acid into Scrubber	Acetic Acid Emissions
<u>Test</u>	<u>Rate</u>	<u>Rate</u>
1	.267 lb/hr	.193 lb/hr
2	.256 lb/hr	.161 lb/hr
3	.250 lb/hr	.119 lb/hr
---	---	---
Avg	.258 lb/hr	.158 lb/hr

The results of the KSI-3 acetic acid testing were as follows:

KSI-3	Acetic Acid into Scrubber	Acetic Acid Emissions
<u>Test</u>	<u>Rate</u>	<u>Rate</u>
1	.214 lb/hr	.136 lb/hr
2	.222 lb/hr	.139 lb/hr
3	.202 lb/hr	.129 lb/hr
---	---	---
Avg	.213 lb/hr	.135 lb/hr

Organic Compounds

The permit for KSI-2 and KSI-3 specifies that organic compound emissions be controlled by at least 85 %. Organic compounds include acetic acid, formaldehyde, and the other unidentified organic compounds which were quantified as acetaldehyde. The results of the KSI-2 organic compound testing were as follows:

KSI-2	TOTAL ORGANIC COMPOUNDS				
	into Scrubber		Emissions		Control
Test	Rate		Rate		Efficiency
1	3.66	lb/hr	0.72	lb/hr	80 %
2	4.17	lb/hr	0.59	lb/hr	86 %
3	4.42	lb/hr	0.56	lb/hr	87 %
---	-----		-----		-----
Avg	4.08	lb/hr	0.62	lb/hr	84 %

The results of the KSI-3 organic compound testing were as follows:

KSI-3	TOTAL ORGANIC COMPOUNDS				
	into Scrubber		Emissions		Control
Test	Rate		Rate		Efficiency
1	2.34	lb/hr	0.57	lb/hr	76 %
2	3.30	lb/hr	0.66	lb/hr	80 %
3	2.66	lb/hr	0.65	lb/hr	75 %
---	-----		-----		-----
Avg	2.77	lb/hr	0.63	lb/hr	77 %

Visible Emissions

The permit for KSI-2 and KSI-3 specifies that the visible emissions not exceed 20 % opacity. The highest six minute average opacity for each smokehouse stack was as shown below:

<u>STACK</u>	<u>OPACITY</u>
KSI-2	10.0 %
KSI-3	10.2 %

1.0 GENERAL

On September 19 & 20, 1991, Environmental Technology & Engineering Corp personnel performed stack emissions testing on the KSI-2 and KSI-3 continuous smokehouse operations at the Hillshire Farm & Kahn's facility located in New London, Wisconsin. The purpose of the testing was to demonstrate compliance with the emission limits outlined in the DNR permit No. 89-RV-006.

Both smokehouses were in full operation throughout the testing; product was run through the smokehouses continuously during the testing. Five smoke generators were in operation on each house; four running chips at 20.4 lb/hr and one running "wundersmoke" sawdust at 22 lb/hr, thus a total wood rate of 103.6 lb/hr.

The field tests, corresponding laboratory analysis, and report preparation were performed by ETE personnel; Lowell Huenink was the test team leader.

The following sections of this report document the activities and results of the test program. The report presents all of the relevant data collected. Discussions on the interpretation of the data are provided where appropriate. The results, however, have been presented in the SUMMARY section at the beginning of this report for those readers not wishing to be burdened by the details.

2.0 RESULTS

Emission concentrations and exhaust flow rates were measured during the test efforts. Exhaust flow rates were measured in accordance with EPA Methods 1 through 4 using a pitot tube and inclined manometer. Concentrations of compounds in the exhaust gas stream were measured using a combination of standard EPA methods and Wisconsin DNR recommended methods as indicated below. The emission rates were then calculated as a product of the emission concentrations and exhaust flow rates.

2.1 Particulate Emissions

Isokinetic sampling for particulate matter was performed in accordance with the procedures outlined in EPA Method 5 - "Determination of Particulate Emissions from Stationary Sources" found in 40 CFR, Part 60, Appendix A. A brief summary of this method is included in Section 3.1 of this report. The tests were performed in horizontal duct between the smokehouse and the scrubber and also in the final discharge stack, above the mist eliminator. The results of the testing to determine particulate matter emissions are shown in Tables 2-1 through 2-12. These results include both filterable and condensable ("back-half") particulate matter.

The results of the particulate matter tests showed the emissions to be within the permit limit of 1.824 lb/hr and are summarized below:

KSI-2:	Particulate into Scrubber	Particulate Emissions
<u>Test</u>	<u>Rate</u>	<u>Rate</u>
1	5.38 lb/hr	1.95 lb/hr
2	4.86 lb/hr	1.45 lb/hr
3	5.81 lb/hr	1.55 lb/hr
---	-----	-----
Avg	5.35 lb/hr	1.65 lb/hr

KSI-3:	Particulate into Scrubber	Particulate Emissions
<u>Test</u>	<u>Rate</u>	<u>Rate</u>
1	6.34 lb/hr	1.34 lb/hr
2	5.33 lb/hr	1.42 lb/hr
3	4.87 lb/hr	1.29 lb/hr
---	-----	-----
Avg	5.51 lb/hr	1.35 lb/hr

HILLSHIRE KSI 2 IN TEST 1 TABLE 2-1 9-20-91

BAROMETRIC PRESSURE, in Hg = 29.300
TIP DIAMETER, in .2450
STACK AREA, sq ft = 2.918
SAMPLING TIME PER POINT, min = 4.00
NUMBER OF POINTS = 16
GAS METER VOLUME, acf = 40.72
WATER COLLECTED, ml = 99.00
PARTICULATE COLLECTED, grams = 0.2887
CO2 = 0.20 O2 = 20.40 CO = 0.00 N2 = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	130	0.540	0.63	97	45.48
2	132	0.570	0.66	99	46.81
3	132	0.470	0.54	99	42.50
4	130	0.370	0.43	101	37.65
5	130	0.500	0.58	105	43.76
6	130	0.540	0.63	109	45.48
7	130	0.460	0.53	110	41.98
8	130	0.340	0.40	112	36.09
9	130	0.620	0.70	117	48.73
10	130	0.650	0.75	118	49.90
11	132	0.490	0.57	119	43.40
12	132	0.350	0.41	120	36.68
13	130	0.580	0.67	121	47.13
14	132	0.640	0.73	122	49.60
15	132	0.420	0.49	123	40.18
16	130	0.350	0.41	125	36.61
AVG VALUES	131		0.571	112	43.25

TOTAL GAS WITHDRAWN, scf = 46.31
DRY GAS WITHDRAWN, scf = 41.65
WATER VAPOR WITHDRAWN, scf = 4.66
PERCENT WATER VAPOR = 10.06
ACTUAL WET FLOW RATE, acfm = 7,571.83
STANDARD DRY FLOW RATE, scfm = 5,930.57
PARTICULATE CONCENTRATION, grains/dscf = 0.1069
PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.188
PARTICULATE EMISSION RATE, lb/hr = 5.38
PERCENT OF ISOKINETIC SAMPLING = 97.83

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2450
 STACK AREA, sq ft = 2.918
 SAMPLING TIME PER POINT, min = 4.00
 NUMBER OF POINTS = 16
 GAS METER VOLUME, acf = 40.12
 WATER COLLECTED, ml = 97.00
 PARTICULATE COLLECTED, grams = 0.2568
 CO₂ = 0.20 O₂ = 20.40 CO = 0.00 N₂ = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	130	0.550	0.64	126	45.89
2	132	0.550	0.64	125	45.97
3	132	0.510	0.59	127	44.27
4	130	0.360	0.42	128	37.13
5	130	0.630	0.72	129	49.12
6	130	0.600	0.69	129	47.93
7	130	0.520	0.60	130	44.62
8	130	0.380	0.44	130	38.15
9	130	0.640	0.73	132	49.51
10	130	0.660	0.76	132	50.27
11	130	0.550	0.64	133	45.89
12	130	0.400	0.47	133	39.14
13	130	0.480	0.56	135	42.87
14	130	0.540	0.63	137	45.47
15	130	0.460	0.53	136	41.97
16	130	0.320	0.37	139	35.01
AVG VALUES	130		0.589	131	43.95

TOTAL GAS WITHDRAWN, scf = 45.70
 DRY GAS WITHDRAWN, scf = 41.13
 WATER VAPOR WITHDRAWN, scf = 4.57
 PERCENT WATER VAPOR = 9.99
 ACTUAL WET FLOW RATE, acfm = 7,694.88
 STANDARD DRY FLOW RATE, scfm = 6,036.77
 PARTICULATE CONCENTRATION, grains/dscf = 0.0963
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.167
 PARTICULATE EMISSION RATE, lb/hr = 4.86
 PERCENT OF ISOKINETIC SAMPLING = 94.90

HILLSHIRE

KSI 2 IN

TEST 3

TABLE 2-3

9-20-91

BAROMETRIC PRESSURE, in Hg = 29.300

TIP DIAMETER, in .2450

STACK AREA, sq ft = 2.918

SAMPLING TIME PER POINT, min = 4.00

NUMBER OF POINTS = 16

GAS METER VOLUME, acf = 39.88

WATER COLLECTED, ml = 109.00

PARTICULATE COLLECTED, grams = 0.3085

CO₂ = 0.20 O₂ = 20.40 CO = 0.00 N₂ = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	130	0.500	0.58	130	43.86
2	130	0.550	0.63	131	46.00
3	130	0.480	0.56	131	42.97
4	130	0.360	0.42	132	37.21
5	130	0.580	0.67	133	47.24
6	135	0.630	0.72	134	49.44
7	135	0.550	0.63	135	46.19
8	135	0.380	0.44	136	38.40
9	135	0.600	0.69	138	48.25
10	135	0.630	0.72	138	49.44
11	135	0.540	0.62	138	45.77
12	130	0.340	0.40	138	36.17
13	135	0.520	0.60	139	44.91
14	135	0.580	0.67	139	47.43
15	135	0.540	0.62	140	45.77
16	135	0.370	0.43	140	37.89
AVG VALUES	133		0.588	136	44.18

TOTAL GAS WITHDRAWN, scf = 46.04

DRY GAS WITHDRAWN, scf = 40.91

WATER VAPOR WITHDRAWN, scf = 5.13

PERCENT WATER VAPOR = 11.14

ACTUAL WET FLOW RATE, acfm = 7,735.50

STANDARD DRY FLOW RATE, scfm = 5,961.84

PARTICULATE CONCENTRATION, grains/dscf = 0.1164

PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.201

PARTICULATE EMISSION RATE, lb/hr = 5.81

PERCENT OF ISOKINETIC SAMPLING = 95.57

HILLSHIRE KSI 2 OUT TEST 1 TABLE 2-4 9-20-91

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2500
 STACK AREA, sq ft = 3.141
 SAMPLING TIME PER POINT, min = 2.50
 NUMBER OF POINTS = 24
 GAS METER VOLUME, acf = 41.40
 WATER COLLECTED, ml = 106.00
 PARTICULATE COLLECTED, grams = 0.0950
 CO₂ = 0.20 O₂ = 20.40 CO = 0.00 N₂ = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	125	0.480	1.36	41	42.68
2	125	0.540	1.55	42	45.27
3	130	0.600	1.70	42	47.92
4	130	0.600	1.70	42	47.92
5	125	0.600	1.70	43	47.72
6	130	0.580	1.65	43	47.11
7	130	0.580	1.65	44	47.11
8	130	0.600	1.70	45	47.92
9	130	0.540	1.55	46	45.46
10	125	0.380	1.08	47	37.97
11	125	0.300	0.86	48	33.74
12	125	0.280	0.82	48	32.60
13	125	0.280	0.82	52	32.60
14	130	0.340	0.98	54	36.07
15	130	0.540	1.55	55	45.46
16	125	0.640	1.85	56	49.28
17	130	0.640	1.85	57	49.49
18	130	0.640	1.85	58	49.49
19	125	0.580	1.65	59	46.91
20	125	0.580	1.65	60	46.91
21	130	0.540	1.55	60	45.46
22	130	0.440	1.25	62	41.04
23	125	0.300	0.86	62	33.74
24	125	0.280	0.82	63	32.60
AVG VALUES	128		1.417	51	43.02

TOTAL GAS WITHDRAWN, scf = 45.67
 DRY GAS WITHDRAWN, scf = 40.68
 WATER VAPOR WITHDRAWN, scf = 4.99
 PERCENT WATER VAPOR = 10.93
 ACTUAL WET FLOW RATE, acfm = 8,107.45
 STANDARD DRY FLOW RATE, scfm = 6,350.97
 PARTICULATE CONCENTRATION, grains/dscf = 0.0360
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.063
 PARTICULATE EMISSION RATE, lb/hr = 1.95
 PERCENT OF ISOKINETIC SAMPLING = 98.37

HILLSHIRE KSI 2 OUT TEST 2 TABLE 2-5 9-20-91

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2500
 STACK AREA, sq ft = 3.141
 SAMPLING TIME PER POINT, min = 2.50
 NUMBER OF POINTS = 24
 GAS METER VOLUME, acf = 40.48
 WATER COLLECTED, ml = 105.00
 PARTICULATE COLLECTED, grams = 0.0700
 CO₂ = 0.20 O₂ = 20.40 CO = 0.00 N₂ = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	125	0.480	1.36	60	42.69
2	125	0.580	1.65	60	46.92
3	130	0.620	1.78	60	48.72
4	130	0.620	1.78	61	48.72
5	130	0.620	1.78	62	48.72
6	125	0.600	1.70	62	47.72
7	125	0.600	1.70	62	47.72
8	130	0.600	1.70	62	47.93
9	130	0.520	1.50	62	44.62
10	130	0.400	1.15	62	39.13
11	125	0.320	0.92	63	34.85
12	125	0.280	0.82	64	32.60
13	125	0.280	0.82	69	32.60
14	130	0.340	0.98	70	36.08
15	130	0.520	1.50	71	44.62
16	130	0.640	1.85	71	49.50
17	130	0.640	1.85	72	49.50
18	130	0.620	1.78	73	48.72
19	130	0.600	1.70	73	47.93
20	130	0.580	1.65	74	47.12
21	130	0.500	1.45	75	43.75
22	130	0.440	1.25	75	41.04
23	130	0.300	0.86	76	33.89
24	130	0.260	0.74	77	31.55
AVG VALUES	129		1.428	67	43.19

TOTAL GAS WITHDRAWN, scf = 44.79
 DRY GAS WITHDRAWN, scf = 39.85
 WATER VAPOR WITHDRAWN, scf = 4.94
 PERCENT WATER VAPOR = 11.03
 ACTUAL WET FLOW RATE, acfm = 8,140.21
 STANDARD DRY FLOW RATE, scfm = 6,358.28
 PARTICULATE CONCENTRATION, grains/dscf = 0.0271
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.047
 PARTICULATE EMISSION RATE, lb/hr = 1.45
 PERCENT OF ISOKINETIC SAMPLING = 96.26

HILLSHIRE KSI 2 OUT TEST 3 TABLE 2-6 9-20-91

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2500
 STACK AREA, sq ft = 3.141
 SAMPLING TIME PER POINT, min = 2.50
 NUMBER OF POINTS = 24
 GAS METER VOLUME, acf = 40.60
 WATER COLLECTED, ml = 110.00
 PARTICULATE COLLECTED, grams = 0.0755
 CO₂ = 0.20 O₂ = 20.40 CO = 0.00 N₂ = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	125	0.280	0.82	68	32.63
2	125	0.360	0.96	69	37.00
3	130	0.540	1.55	70	45.51
4	130	0.620	1.78	70	48.76
5	130	0.640	1.85	70	49.54
6	130	0.640	1.85	71	49.54
7	130	0.580	1.65	72	47.16
8	130	0.540	1.55	72	45.51
9	125	0.540	1.55	73	45.31
10	130	0.460	1.32	73	42.00
11	125	0.300	0.86	73	33.78
12	125	0.280	0.82	74	32.63
13	130	0.460	1.32	77	42.00
14	130	0.380	1.65	78	38.17
15	130	0.600	1.70	78	47.97
16	125	0.620	1.78	78	48.55
17	130	0.620	1.78	79	48.76
18	130	0.600	1.70	79	47.97
19	130	0.600	1.70	79	47.97
20	130	0.580	1.65	79	47.16
21	130	0.540	1.55	79	45.51
22	130	0.400	1.15	79	39.17
23	125	0.300	0.86	80	33.78
24	130	0.280	0.82	80	32.77
AVG VALUES	129		1.426	75	42.88

TOTAL GAS WITHDRAWN, scf = 45.18
 DRY GAS WITHDRAWN, scf = 40.00
 WATER VAPOR WITHDRAWN, scf = 5.18
 PERCENT WATER VAPOR = 11.46
 ACTUAL WET FLOW RATE, acfm = 8,081.40
 STANDARD DRY FLOW RATE, scfm = 6,281.82
 PARTICULATE CONCENTRATION, grains/dscf = 0.0291
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.051
 PARTICULATE EMISSION RATE, lb/hr = 1.55
 PERCENT OF ISOKINETIC SAMPLING = 97.81

HILLSHIRE KSI 3 IN TEST 1 TABLE 2-7 9-19-91

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2500
 STACK AREA, sq ft = 2.918
 SAMPLING TIME PER POINT, min = 4.00
 NUMBER OF POINTS = 16
 GAS METER VOLUME, acf = 39.92
 WATER COLLECTED, ml = 154.00
 PARTICULATE COLLECTED, grams = 0.3707
 CO₂ = 0.20 O₂ = 20.40 CO = 0.00 N₂ = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	136	0.350	0.45	93	37.18
2	134	0.370	0.47	93	38.16
3	140	0.280	0.36	95	33.37
4	140	0.220	0.28	96	29.58
5	140	0.380	0.48	99	38.87
6	140	0.400	0.51	101	39.88
7	140	0.350	0.45	103	37.30
8	140	0.240	0.31	105	30.89
9	140	0.520	0.63	109	45.47
10	140	0.480	0.60	111	43.69
11	140	0.400	0.51	111	39.88
12	140	0.300	0.38	114	34.54
13	140	0.590	0.73	119	48.43
14	140	0.710	0.88	120	53.13
15	140	0.630	0.79	121	50.05
16	140	0.380	0.48	122	38.87
AVG VALUES	139		0.519	107	39.96

TOTAL GAS WITHDRAWN, scf = 48.05
 DRY GAS WITHDRAWN, scf = 40.80
 WATER VAPOR WITHDRAWN, scf = 7.25
 PERCENT WATER VAPOR = 15.08
 ACTUAL WET FLOW RATE, acfm = 6,995.46
 STANDARD DRY FLOW RATE, scfm = 5,096.11
 PARTICULATE CONCENTRATION, grains/dscf = 0.1402
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.249
 PARTICULATE EMISSION RATE, lb/hr = 6.34
 PERCENT OF ISOKINETIC SAMPLING = 107.11

HILLSHIRE

KSI 3 IN

TEST 2

TABLE 2-8

9-19-91

BAROMETRIC PRESSURE, in Hg = 29.300

TIP DIAMETER, in .2500

STACK AREA, sq ft = 2.918

SAMPLING TIME PER POINT, min = 4.00

NUMBER OF POINTS = 16

GAS METER VOLUME, acf = 38.68

WATER COLLECTED, ml = 151.00

PARTICULATE COLLECTED, grams = 0.3032

CO₂ = 0.20 O₂ = 20.40 CO = 0.00 N₂ = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	140	0.450	0.57	119	42.32
2	140	0.380	0.48	118	38.89
3	140	0.320	0.41	119	35.68
4	140	0.220	0.28	120	29.59
5	140	0.400	0.51	120	39.90
6	140	0.430	0.54	121	41.36
7	140	0.370	0.47	122	38.37
8	140	0.230	0.29	123	30.25
9	140	0.540	0.67	125	46.35
10	134	0.550	0.68	126	46.55
11	132	0.460	0.58	127	42.50
12	132	0.270	0.34	128	32.56
13	134	0.550	0.68	129	46.55
14	132	0.760	0.94	129	54.62
15	132	0.680	0.84	130	51.67
16	132	0.380	0.48	130	38.63
AVG VALUES	137		0.547	124	40.99

TOTAL GAS WITHDRAWN, scf = 46.73

DRY GAS WITHDRAWN, scf = 39.62

WATER VAPOR WITHDRAWN, scf = 7.11

PERCENT WATER VAPOR = 15.21

ACTUAL WET FLOW RATE, acfm = 7,175.83

STANDARD DRY FLOW RATE, scfm = 5,241.36

PARTICULATE CONCENTRATION, grains/dscf = 0.1181

PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.203

PARTICULATE EMISSION RATE, lb/hr = 5.33

PERCENT OF ISOKINETIC SAMPLING = 101.12

HILLSHIRE KSI 3 IN TEST 3 TABLE 2-9 9-19-91

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2500
 STACK AREA, sq ft = 2.918
 SAMPLING TIME PER POINT, min = 4.00
 NUMBER OF POINTS = 16
 GAS METER VOLUME, acf = 38.52
 WATER COLLECTED, ml = 168.00
 PARTICULATE COLLECTED, grams = 0.2789
 CO₂ = 0.20 O₂ = 20.40 CO = 0.00 N₂ = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	137	0.380	0.48	128	38.90
2	138	0.420	0.53	127	40.93
3	140	0.330	0.42	128	36.34
4	140	0.210	0.27	128	28.99
5	140	0.450	0.57	128	42.44
6	140	0.420	0.53	129	41.00
7	140	0.320	0.41	129	35.79
8	140	0.240	0.31	130	31.00
9	134	0.550	0.69	131	46.69
10	134	0.520	0.65	131	45.39
11	134	0.430	0.54	132	41.28
12	134	0.290	0.37	132	33.90
13	134	0.570	0.71	134	47.53
14	134	0.740	0.91	134	54.15
15	134	0.670	0.83	135	51.53
16	134	0.380	0.48	136	38.81
AVG VALUES	137		0.544	131	40.92

TOTAL GAS WITHDRAWN, scf = 47.39
 DRY GAS WITHDRAWN, scf = 39.48
 WATER VAPOR WITHDRAWN, scf = 7.91
 PERCENT WATER VAPOR = 16.69
 ACTUAL WET FLOW RATE, acfm = 7,163.83
 STANDARD DRY FLOW RATE, scfm = 5,142.12
 PARTICULATE CONCENTRATION, grains/dscf = 0.1090
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.187
 PARTICULATE EMISSION RATE, lb/hr = 4.87
 PERCENT OF ISOKINETIC SAMPLING = 102.72

HILLSHIRE KSI 3 OUT TEST 1 TABLE 2-10 9-19-91

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2500
 STACK AREA, sq ft = 3.141
 SAMPLING TIME PER POINT, min = 2.50
 NUMBER OF POINTS = 24
 GAS METER VOLUME, acf = 35.52
 WATER COLLECTED, ml = 135.00
 PARTICULATE COLLECTED, grams = 0.0657
 CO2 = 0.20 O2 = 20.40 CO = 0.00 N2 = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	130	0.340	0.92	45	36.39
2	135	0.380	1.02	46	38.64
3	135	0.390	1.05	47	39.14
4	135	0.420	1.14	48	40.62
5	140	0.450	1.20	49	42.22
6	135	0.450	1.20	50	42.05
7	135	0.470	1.22	50	42.97
8	135	0.420	1.10	51	40.62
9	135	0.340	0.90	52	36.55
10	140	0.320	0.84	53	35.60
11	135	0.300	0.78	54	34.33
12	135	0.300	0.78	54	34.33
13	135	0.350	0.92	58	37.08
14	135	0.400	1.05	59	39.64
15	135	0.420	1.10	59	40.62
16	135	0.450	1.15	60	42.05
17	135	0.470	1.22	60	42.97
18	135	0.470	1.22	62	42.97
19	140	0.450	1.15	63	42.22
20	135	0.380	1.00	64	38.64
21	135	0.320	0.84	64	35.46
22	135	0.320	0.84	65	35.46
23	135	0.320	0.84	65	35.46
24	135	0.300	0.78	65	34.33
AVG VALUES	135		1.011	56	38.76

TOTAL GAS WITHDRAWN, scf = 41.24
 DRY GAS WITHDRAWN, scf = 34.88
 WATER VAPOR WITHDRAWN, scf = 6.35
 PERCENT WATER VAPOR = 15.41
 ACTUAL WET FLOW RATE, acfm = 7,305.51
 STANDARD DRY FLOW RATE, scfm = 5,363.55
 PARTICULATE CONCENTRATION, grains/dscf = 0.0291
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.050
 PARTICULATE EMISSION RATE, lb/hr = 1.34
 PERCENT OF ISOKINETIC SAMPLING = 99.89

HILLSHIRE KSI 3 OUT TEST 2 TABLE 2-11 9-19-91

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2500
 STACK AREA, sq ft = 3.141
 SAMPLING TIME PER POINT, min = 2.50
 NUMBER OF POINTS = 24
 GAS METER VOLUME, acf = 35.00
 WATER COLLECTED, ml = 141.00
 PARTICULATE COLLECTED, grams = 0.0699
 CO2 = 0.20 O2 = 20.40 CO = 0.00 N2 = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	135	0.360	0.94	50	37.67
2	135	0.360	0.94	51	37.67
3	135	0.410	1.16	51	40.20
4	140	0.460	1.20	52	42.75
5	135	0.470	1.22	52	43.04
6	135	0.470	1.22	53	43.04
7	135	0.450	1.16	53	42.11
8	135	0.400	1.05	54	39.70
9	135	0.350	0.92	55	37.14
10	135	0.300	0.78	55	34.38
11	135	0.300	0.78	55	34.38
12	135	0.280	0.74	55	33.22
13	135	0.320	0.84	58	35.51
14	135	0.340	0.90	59	36.60
15	140	0.360	0.94	60	37.82
16	135	0.400	1.05	60	39.70
17	135	0.440	1.15	60	41.64
18	135	0.460	1.20	60	42.58
19	135	0.440	1.15	60	41.64
20	135	0.400	1.05	61	39.70
21	135	0.360	0.94	62	37.67
22	135	0.340	0.90	62	36.60
23	135	0.300	0.78	62	34.38
24	135	0.300	0.78	62	34.38
AVG VALUES	135		0.991	57	38.48

TOTAL GAS WITHDRAWN, scf = 41.01
 DRY GAS WITHDRAWN, scf = 34.37
 WATER VAPOR WITHDRAWN, scf = 6.64
 PERCENT WATER VAPOR = 16.18
 ACTUAL WET FLOW RATE, acfm = 7,252.03
 STANDARD DRY FLOW RATE, scfm = 5,275.57
 PARTICULATE CONCENTRATION, grains/dscf = 0.0314
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.053
 PARTICULATE EMISSION RATE, lb/hr = 1.42
 PERCENT OF ISOKINETIC SAMPLING = 100.08

HILLSHIRE KSI 3 OUT TEST 3 TABLE 2-12 9-19-91

BAROMETRIC PRESSURE, in Hg = 29.300
 TIP DIAMETER, in .2500
 STACK AREA, sq ft = 3.141
 SAMPLING TIME PER POINT, min = 2.50
 NUMBER OF POINTS = 24
 GAS METER VOLUME, acf = 34.72
 WATER COLLECTED, ml = 148.00
 PARTICULATE COLLECTED, grams = 0.0637
 CO2 = 0.20 O2 = 20.40 CO = 0.00 N2 = 79.40

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE METER inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	135	0.330	0.86	52	36.12
2	135	0.350	0.92	53	37.20
3	135	0.370	0.98	54	38.25
4	140	0.400	1.05	54	39.93
5	135	0.440	1.15	54	41.71
6	135	0.460	1.20	54	42.64
7	135	0.430	1.12	55	41.23
8	140	0.400	1.05	56	39.93
9	135	0.370	0.98	57	38.25
10	135	0.320	0.84	58	35.57
11	135	0.300	0.78	59	34.44
12	135	0.300	0.78	59	34.44
13	135	0.350	0.92	61	37.20
14	135	0.360	0.94	62	37.73
15	135	0.400	1.05	62	39.77
16	140	0.460	1.20	62	42.82
17	135	0.470	1.22	63	43.11
18	135	0.480	1.25	64	43.56
19	135	0.440	1.15	64	41.71
20	135	0.400	1.05	65	39.77
21	135	0.360	0.94	65	37.73
22	135	0.340	0.88	65	36.66
23	135	0.300	0.78	65	34.44
24	135	0.280	0.74	65	33.27
AVG VALUES	136		0.993	60	38.64

TOTAL GAS WITHDRAWN, scf = 41.08
 DRY GAS WITHDRAWN, scf = 34.11
 WATER VAPOR WITHDRAWN, scf = 6.97
 PERCENT WATER VAPOR = 16.96
 ACTUAL WET FLOW RATE, acfm = 7,282.82
 STANDARD DRY FLOW RATE, scfm = 5,246.82
 PARTICULATE CONCENTRATION, grains/dscf = 0.0288
 PARTICULATE EMISSIONS, lb/1000 lb wet gas = 0.049
 PARTICULATE EMISSION RATE, lb/hr = 1.29
 PERCENT OF ISOKINETIC SAMPLING = 99.85

2.2 Formaldehyde Emissions

Testing to determine the formaldehyde emissions was performed using the sampling and analytical procedures of NIOSH Method 3500. A further description of the method is included in Section 3.2.

The formaldehyde emission limit specified for KSI-2 and KSI-3 in the permit is 0.007 lb/hr, however, a footnote in the permit indicates that this limit may be subject to change pending the test results. The results of the formaldehyde testing were as follows:

KSI-2	Formaldehyde	Formaldehyde
	into Scrubber	Emissions
Test	Rate	Rate
1	0.066 lb/hr	0.029 lb/hr
2	0.071 lb/hr	0.039 lb/hr
3	0.064 lb/hr	0.030 lb/hr
---	-----	-----
Avg	0.067 lb/hr	0.033 lb/hr

KSI-3	Formaldehyde	Formaldehyde
	into Scrubber	Emissions
Test	Rate	Rate
1	0.071 lb/hr	0.035 lb/hr
2	0.057 lb/hr	0.026 lb/hr
3	0.067 lb/hr	0.034 lb/hr
---	-----	-----
Avg	0.065 lb/hr	0.032 lb/hr

2.3 Acetic Acid Emissions

Testing to determine the acetic acid emissions was performed using the sampling and analytical procedures outlined in EPA Method 18, direct interface with the gas chromatograph. A further description of the method is included in Section 3.3.

The acetic acid emission limit specified for KSI-2 and KSI-3 in the permit is 0.303 lb/hr. The test results are summarized below:

KSI-2:		Acetic Acid into Scrubber	Acetic Acid Emissions
Test		Rate	Rate
1		.267 lb/hr	.193 lb/hr
2		.256 lb/hr	.161 lb/hr
3		.250 lb/hr	.119 lb/hr
---		-----	-----
Avg		.258 lb/hr	.158 lb/hr

KSI-3:		Acetic Acid into Scrubber	Acetic Acid Emissions
Test		Rate	Rate
1		.214 lb/hr	.136 lb/hr
2		.222 lb/hr	.139 lb/hr
3		.202 lb/hr	.129 lb/hr
---		-----	-----
Avg		.213 lb/hr	.135 lb/hr

2.4 Organic Compound Emissions

The testing was performed using an on-site gas chromatograph as outlined in EPA Method 18 - "Measurement of Gaseous Organic Compound Emissions by Gas Chromatography." A description of the method is given in Section 3.3.

The permit for KSI-2 and KSI-3 specifies that organic compound emissions be controlled by at least 85 %. Organic compounds include acetic acid, formaldehyde, and the other unidentified organic compounds which were quantified as acetaldehyde. The results of the testing were as follows:

KSI-2		TOTAL ORGANIC COMPOUNDS				
Test	into Scrubber		Emissions		Control	
	Rate		Rate		Efficiency	
1	3.66	lb/hr	0.72	lb/hr	80	%
2	4.17	lb/hr	0.59	lb/hr	86	%
3	4.42	lb/hr	0.56	lb/hr	87	%
---	-----		-----		-----	
Avg	4.08	lb/hr	0.62	lb/hr	85	%

KSI-3		TOTAL ORGANIC COMPOUNDS		Control Efficiency
<u>Test</u>	into Scrubber <u>Rate</u>	<u>Rate</u>	Emissions <u>Rate</u>	
1	2.34 lb/hr	0.57	lb/hr	76 %
2	3.30 lb/hr	0.66	lb/hr	80 %
3	2.66 lb/hr	0.65	lb/hr	75 %
---	-----	---	-----	-----
Avg	2.77 lb/hr	0.63	lb/hr	77 %

2.5 Visible Emissions

The visible emissions from each of the smokehouse stacks was observed in accordance with the procedures outlined in EPA Method 9. The permit for KSI-2 and KSI-3 specifies that the visible emissions not exceed 20 % opacity. The highest six minute average opacity for each smokehouse stack was as shown below:

<u>STACK</u>	MAXIMUM 6 MINUTE <u>OPACITY</u>
KSI-2	10.0 %
KSI-3	10.2 %

3.0 METHODS OF TESTING

3.1 Particulate Emissions

The equipment used to sample was the Western Precipitation Division of the Joy Manufacturing Company Emission Parameter Analyzer. Samples were collected and analyzed in accordance with EPA Method 5 (40 CFR, Part 60, Appendix A).

The sampling train consisted of a stainless steel probe tip, a heated probe, a heated glass cyclone and flask, and a heated filter holder with a tared filter. A series of four impingers followed in an ice bath. The first was a modified Greenburg-Smith impinger with 100 ml of distilled water; the second was a Greenburg-Smith impinger with 100 ml of distilled water; the third was a modified Greenburg-Smith impinger dry; the fourth was also a modified Greenburg-Smith impinger containing a tared quantity of Silica Gel. The gas then passed through a vacuum pump, calibrated dry gas meter, and a calibrated orifice. A schematic drawing of the sampling train is included as Figure 3-1.

The temperatures of the stack gas stream, as well as strategic locations within the sampling devices, were monitored by RTDs and read directly from a gauge on the control unit.

The initial gas stream velocity was obtained from a preliminary traverse using an "S" type pitot tube. The initial moisture was estimated from previous tests of similar processes. This data, along with the stack temperature, was used to set a nomograph so that rapid calculations of isokinetic sampling conditions could be made during the test.

The principle of the method was to collect a representative sample of the exhaust gas stream. This was done by adjusting the sample collection velocity to match the exhaust gas stream velocity at the point of collection. The velocity at the point of collection was measured with an "S" type pitot tube attached to the probe and the collection velocity was matched to the stack gas velocity by adjusting the flow as indicated by the calibrated orifice.

To determine the molecular weight of the stack gas, integrated samples were collected from the stack and analyzed on-site with an Orsat analyzer for percentage CO₂, O₂, and N₂.

At the completion of the test, the probe tip and probe were washed with acetone which was placed in a tared beaker and evaporated to dryness at room temperature. The filter and beaker were then desiccated to the tared humidity conditions and weighed. The impinger contents were measured and weighed for determination of the actual moisture content of the exhaust gas stream. The first three impingers, as well as the probe and glassware following the filter, were then rinsed with acetone which was placed in a tared beaker and evaporated to dryness at room temperature. The impinger water was subjected to organic compound extraction using 1,1,2-trichloro-1,2,2-trifluoroethane. The extract was evaporated in tared beakers at room temperature. Following the organic compound extraction, a 100 milliliter aliquot of the remaining water was evaporated to dryness in a tared beaker at 220 F.

The combined weight of the filter catch, the probe and tip washing residue and the three beaker residues from the "back-half" analysis for condensible particulate matter (acetone rinse, organic compound extract, and impinger water residue corrected to account for the aliquot size) were used to determine the emission rates.

A computer was used to calculate the stack velocities, emission concentrations, emission rates and volumetric flow rates using the field and laboratory data.

3.2 Formaldehyde Emissions

Samples for formaldehyde were obtained using NIOSH Method 3500 as recommended by the Wisconsin DNR for toxic air emissions sampling.

The sampling train consisted of a glass probe connected to midget impingers by tygon tubing; a series of three midget impingers were placed in an ice bath. The first two impingers each contained 15 milliliters (ml) of absorbing solution (1% sodium bisulfite), and the third was dry to serve as a trap for carry-over of any liquid. The gas then passed through a silica gel tube to trap all water vapor prior to the sampling pump and dry gas meter. A schematic of the sampling train is included as Figure 3-2.

The principle of the method was to collect a representative sample of the exhaust gas stream by placing the probe at a single point in the duct and sampling for a 60 minute period at a nominal sampling rate of 1 liter per minute. The testing was coordinated with the particulate emissions test runs. At the completion of each test, a leak check was performed.

3.3 Acetic Acid and Total Organic Compound Emissions

Sampling for organic compounds was performed in accordance with EPA Method 18 - "Measurement of Gaseous Organic Compound Emissions by Gas Chromatography."

Samples were drawn from the exhaust gas stream using a glass syringe, with volume of one cubic centimeter (cc). Samples taken from the stack were injected directly into the heated injection port of an Analytical Instruments Corporation (AID) Model 511 portable GC. The GC conditions were as follows:

Column	DC 200
Temperature	106 C
Carrier Gas	Nitrogen at 20 cc/min

Recorded chromatograms were obtained using a Hewlett Packard Model 3309A integrator.


Standard concentrations of acetaldehyde and acetic acid were prepared by injecting a known quantity of each solvent into a 1 liter flask which was gently heated (hot water bath) to assure complete vaporization; after heating, the standard was allowed to return to standard temperature conditions.

A 1 cc sample of the calibration standard was injected into the GC and the concentrations of the exhaust gas stream were then determined by comparing the response of the standards to the response to the exhaust duct samples. Retention time was used to identify the acetic acid and the GC response to the acetic acid standard was used to quantify the acetic acid in the exhaust gas stream. The acetaldehyde standard was then used to quantify the remaining compounds seen on the chromatogram, that is, the area under all of the peaks except acetic acid were totaled and then compared to a standard concentration of acetaldehyde.

The compound concentrations were then used in conjunction with the exhaust gas flow rates to determine both the acetic acid and total organic compound emission rates in units of pounds per hour (lb/hr).

3.4 Visible Emissions

The visible emissions from each of the smokehouse stacks was observed in accordance with the procedures outlined in EPA Method 9.



Method 5

Figure 3-1

Particulate sampling train.

4.0 CALIBRATION DATA

The probe tips, pitot tube, dry gas meter, and orifices were calibrated prior to the particulate and particle sizing testing according to procedures outlined in the Maintenance, Calibration, and Operation of Isokinetic Source-Sampling Equipment as published by the EPA. The values obtained were:

Probe tip diameters	d =	0.250"
Pitot tube coeff.	Cp =	0.85
Orifice coeff.	dH@ =	1.77

The dry gas meter presently installed in the control box is a temperature compensating meter. The correction factor for the dry gas meter is represented by:

$$Gama = 1.002 + ((Td - 70) \times .00012)$$

where: Td = Dry Gas Meter Temperature

The dry gas meter used for the formaldehyde testing was not temperature compensated; therefore, all of the sample volumes were corrected for temperature to 68 F. The coefficient of this meter was 1.020.

The most recent calibrations were performed August 5, 1991.

APPENDIX A

SAMPLE CALCULATIONS

SAMPLE CALCULATION

BAROMETRIC PRESSURE, in Hg (Pb) = 29.200
 STACK PRESSURE, in Hg (Pb + Pg/13.6) = 29.178
 TIP DIAMETER, in (An = PI*D^2/576) = .2450
 STACK AREA, sq ft (A) = 10.560
 SAMPLING TIME PER POINT, min = 2.50
 NUMBER OF POINTS = 24
 GAS METER VOLUME, acf (Vm) = 66.06
 WATER COLLECTED, ml (Vf - Vi) = 86.00
 PARTICULATE COLLECTED, grams (Mn) = 0.0755
 CO2 = 0.60 O2 = 21.00 CO = 0.00 N2 = 78.40
 WET MOLECULAR WEIGHT, lb/mole (Ms) = 28.45

SAMPLING POINT	STACK TEMP deg F	PITOT DEL P inches	ORIFICE DEL H inches	GAS METER OUTLET T deg F	GAS VELOCITY fps
1	110	1.450	4.05	32	72.51
2	110	1.350	3.75	32	69.97
3	110	1.350	3.75	32	69.97
4	110	1.300	3.70	32	68.66
5	110	1.250	3.60	32	67.33
6	110	1.250	3.60	32	67.33
7	110	1.050	2.95	32	61.71
8	110	1.000	2.85	32	60.22
9	110	1.000	2.85	34	60.22
10	110	1.050	2.95	34	61.71
11	110	0.950	2.75	38	58.69
12	115	0.950	2.75	38	58.95
13	115	1.300	3.70	42	68.96
14	115	1.250	3.60	42	67.62
15	115	1.200	3.40	42	66.26
16	115	1.200	3.40	42	66.26
17	115	1.150	3.30	44	64.86
18	115	1.150	3.30	46	64.86
19	115	1.050	2.95	48	61.98
20	115	1.150	3.30	48	64.86
21	115	1.000	2.85	50	60.48
22	115	1.100	3.15	50	63.43
23	115	1.050	2.95	50	61.98
24	115	0.900	2.55	50	57.38
AVG VALUES	113		3.250	40	64.42

TOTAL GAS WITHDRAWN, scf = 69.39
 DRY GAS WITHDRAWN, scf (Vmstd) = 65.35
 WATER VAPOR WITHDRAWN, scf (Vwstd) = 4.05
 PERCENT WATER VAPOR (%H2O) = 5.83
 ACTUAL WET FLOW RATE, acfm = 40,819.39
 STANDARD DRY FLOW RATE, scfm (Qs) = 34,558.69
 PARTICULATE CONCENTRATION, grains/dscf (Cs) = 0.018
 PARTICULATE EMISSION RATE, lb/hr (ER) = 5.325
 PARTICULATE EMISSIONS, lb/1000 lb (EC) = 0.033
 PERCENT OF ISOKINETIC SAMPLING (I) = 101.67

SAMPLE CALCULATIONS

1. DRY MOLECULAR WEIGHT (Md) lb/lb-mole

$$Md = .44\% \text{ CO}_2 + .32\% \text{ O}_2 + .282\% \text{ N}_2 + .28\% \text{ CO}$$

2. WATER VAPOR PERCENT (%H₂O)

$$V_w \text{ std} = 0.04707 \cdot (V_f - V_i)$$

where: $V_w \text{ std}$ = standard cubic feet of water vapor
 V_f = Final volume of impingers, ml
 V_i = Initial volume of impingers, ml

$$\% \text{H}_2\text{O} = V_w \text{ std} \cdot 100 / (V_m \text{ std} + V_w \text{ std})$$

where $V_m \text{ std}$ = standard cubic feet of gas sampled

3. WET MOLECULAR WEIGHT (Ms) lb/lb-mole

$$Ms = Md \cdot (1 - \% \text{H}_2\text{O} / 100) + 18 \cdot \% \text{H}_2\text{O} / 100$$

4. STACK PRESSURE (Ps) in. Hg

$$Ps = Pb + Pg / 13.6$$

where: Pb = barometric pressure (uncorrected), in. Hg
 Pg = stack gauge pressure, in. H₂O
13.6 = specific gravity of mercury (Hg)

5. AVERAGE STACK VELOCITY (Vs) feet per second

$$Vs = K_p \cdot C_p \cdot (\text{DELP}) \cdot T_{\text{avg}} / (Ps \cdot Ms)$$

where: K_p = 85.49 unit conversion
 C_p = 0.85, pitot tube calibration factor
DELP = square root of velocity head, in. H₂O
 T_{avg} = average stack temperature, deg R (460+F)
 Ps = stack pressure
 Ms = wet molecular weight

6. STACK GAS FLOW RATE (Qs) std cubic feet per minute

$$Qs = 60 \cdot (1 - \% \text{H}_2\text{O} / 100) \cdot Vs \cdot A \cdot (528 \cdot Ps / T_{\text{avg}} / 29.92)$$

where: A = stack area, ft²
528 = std temperature, deg R
29.92 = std pressure, in. Hg

7. DRY GAS VOLUME (V_m std) std cubic feet

$$V_m \text{ std} = GAMA * (V_m - (AL - .02)t) * (P_b + DELH / 13.6) / 29.92$$

where: GAMA = dry gas meter calibration factor
V_m = volume of dry gas metered, cubic feet
AL = post test leak rate, cubic feet per minute
t = total time of test, minutes
DELH = average orifice pressure drop, in.H₂O

8. PARTICULATE CONCENTRATION (C_s) grains/dry std cubic foot

$$C_s = M_n * 15.43 / V_m \text{ std}$$

where: M_n = particulate captured, grams
15.43 = grains per gram

9. EMISSION RATE (ER) pounds per hour

$$PMRA = M_n * A * 60 / (t * A_n * 453.6) \quad \text{AREA METHOD lb/hr}$$

$$PMRC = C_s * Q_s * 60 / (15.43 * 453.6) \quad \text{CONC. METHOD lb/hr}$$

$$ER = (PMRA + PMRC) / 2$$

where: A_n = area of sampling nozzle, square feet

10. EMISSION CONCENTRATION (EC) lb/1000 lb exhaust gas

$$EC = ER * 386700 * (1 - \%H_2O / 100) / (Q_s * 60 * M_s)$$

where: 386700 = cubic feet per lb mole * 1000

11. ISOKINETIC SAMPLING PERCENTAGE (I) %

$$I = PMRA / PMRC$$

SAMPLE CALCULATIONS
for
Single Point (non-isokinetic) Sampling

1. DRY GAS SAMPLE VOLUME (V_m m³, std), std cubic meters

$$V_m \text{ m}^3, \text{ std} = GAMA * (V_m) * (P_b) / 29.92 * 528 / T_{\text{avg}} * 0.02832$$

where: GAMA = dry gas meter calibration factor
V_m = volume of dry gas metered, cubic feet
T_{avg} = average meter temperature, deg R (460+F)
528 = std temperature, deg R
0.02832 = cubic meters per cubic foot factor

2. EMISSION CONCENTRATION (EC), milligrams per std cubic meter

$$EC = (mg - mgb) / (V_m \text{ m}^3, \text{ std})$$

where: mg = milligrams of compound found in sample,
determined from comparison to a generated
standard curve.
mgb = milligrams of compound found in "blank"
sampling media


3. EMISSION RATE (ER), pounds per hour

$$ER = EC * (Q_s) * 0.02832 * 60 * (1/453600)$$

where: Q_s = stack gas flow rate, std cubic feet per minute
60 = minutes per hour factor
1/453600 = pound per milligrams factor

APPENDIX B


FIELD & LABORATORY DATA SHEETS

[illegible]

PLANT HILL SAUCE
DATE 9-20-71

AMBIENT TEMPERATURE 85

MEIER AM. _____



BAROMETRIC PRESSURE _____

C FACTOR _____

ASSUMED MOISTURE 3 15%

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841

100

PROCESS WEIGHT RATE _____
 DECAT RESULT TC _____

PROBE LENGTH, in. 5.5 S.S.

KEY RESULTS

1/2"

0201

NOZZLE DIAMETER, in. 1/2

202

STACK DIAMETER, in. (20'2)

$$\frac{1}{2}$$

750

080114
Z

PROBE HEATER SETTING 650

9/10/70
9/10/70

HEATER BOX SETTING 250

Environ Monit Assess

CROSS SECTION

[illegible]




PLANT HILL SHIRE
 DATE 9-20-91
 LOCATION N.W. CONDOY
 OPERATOR MILK
 STACK NO. KST-2 114
 RUN NO. 3
 SAMPLE BOX NO. 6
 METER BOX NO. 2
 AMBIENT TEMPERATURE 90
 BAROMETRIC PRESSURE _____
 ASSUMED MOISTURE, % 15%
 PROBE LENGTH, in. 5' S.S.
 NOZZLE DIAMETER, in. 1/4"
 STACK DIAMETER, in. (20 1/2)"
 PROBE HEATER SETTING 250
 HEATER BOX SETTING 250
 MEIER AM. _____
 C FACTOR _____
 PROCESS WEIGHT RATE _____
 ORSAT RESULTS
 CO₂ _____
 O₂ _____
 CO _____
 N₂ _____
 PRICK OR _____
 PILOT OR _____
 ASTICK _____

[illegible]

PARTICULATE FIELD DATA

SCHEMATIC OF STACK



CROSS SECTION

TRAVERSE POINT NUMBER	SAMPLING TIME (H), min.	STATIC PRESSURE (in. H ₂ O)	STACK TEMPERATURE (T _s), °F	VELOCITY HEAD (V _p), (1/V _p ²)	PRESSURE DIFFERENTIAL ACROSS ORIFICE METER (in. H ₂ O) ACTUAL DESIRED	GAS SAMPLE VOLUME (V _m), (ft)	GAS SAMPLE TEMPERATURE AT DRY GAS METER INLET (T _m), °F OUTLET (T _m), °F	SAMPLE BOX TEMPERATURE °F	TEMPERATURE OF GAS LEAVING CONDENSER OR LAST IMPINGER °F	PUMP VACUUM in. Hg gauge	VELOCITY lps
A 1	08:23:30		125	.48	1.36	7333.00		943.54/44	6150/22		
2	35	-.28	125	.51	1.55	377		943.54/42	6164/36		
3	37		130	.60	1.70	36.6		42			
4	40		130	.60	1.70	38.6		42			
5	43	-.26	125	.60	1.70	40.5		43			
6	50		130	.58	1.65	42.4		43			
7	52		130	.58	1.65	44.4		44			
8	53		130	.60	1.70	46.2		45			
9	55	-.32	130	.58	1.55	48.1		46			
10	57		125	.38	1.08	49.9		47			
11	57	-.26	125	.30	.80	51.5		48			
12	58		125	.38	.82	52.8		48			
B 13	08:21:05		125	.28	.82	51.2		52			
14	07:4	-.24	130	.34	.98	55.5		51			
15	10		130	.51	1.51	57.1		55			
16	12:4		125	.64	1.85	58.7		56			
17	15	-.26	130	.64	1.85	60.7		57			
18	17		130	.64	1.85	62.6		59			
19	20		125	.58	1.61	64.6		59			
20	23	-.28	125	.58	1.61	66.5		60			
21	25		130	.58	1.55	68.3		60			
22	27		130	.44	1.21	70.1	41.60	60			
23	30	-.24	125	.30	.80	71.7		60			
24	32		125	.26	.82	73.1		62			


SP: 0.85 }
 1.002 } 8.5.91
 METER AM: 1.77
 C FACTOR: _____
 PROCESS WEIGHT RATE: _____
 ORSAT RESULTS:
 CO₂: 0.2
 O₂: 20.4
 CO: _____
 N₂: _____
 P₁: 1.070
 P₂: 1.070
 P₃: 1.070
 P₄: 1.070
 P₅: 1.070
 P₆: 1.070
 P₇: 1.070
 P₈: 1.070
 P₉: 1.070
 P₁₀: 1.070
 P₁₁: 1.070
 P₁₂: 1.070
 P₁₃: 1.070
 P₁₄: 1.070
 P₁₅: 1.070
 P₁₆: 1.070
 P₁₇: 1.070
 P₁₈: 1.070
 P₁₉: 1.070
 P₂₀: 1.070
 P₂₁: 1.070
 P₂₂: 1.070
 P₂₃: 1.070
 P₂₄: 1.070

AMBIENT TEMPERATURE: 40
 BAROMETRIC PRESSURE: 30
 ASSUMED MOISTURE, %: 5.5
 PROBE LENGTH, in.: 31
 NOZZLE DIAMETER, in.: 14
 STACK DIAMETER, in.: 24
 PROBE HEATER SETTING: 250
 HEATER BOX SETTING: 250

PLANT: HILLSHIRE
 DATE: 9-20-91
 LOCATION: NEW LONDON
 OPERATOR: WJD
 STACK NO.: K552 ON
 RUN NO.: 1
 SAMPLE BOX NO.: 1
 METER BOX NO.: 1

PARTICULATE FIELD DATA

SCHEMATIC OF STACK



PLANT 1-1-1, S1410
 DATE 9-20-91
 LOCATION NEW LONDON
 OPERATOR WJP
 STACK NO. KST2-005
 RUN NO. 2
 SAMPLE BOX NO. 2
 METER BOX NO. 1

AMBIENT TEMPERATURE _____
 BAROMETRIC PRESSURE _____
 ASSUMED MOISTURE, % 5.5
 PROBE LENGTH, in. 3'
 NOZZLE DIAMETER, in. 1/4
 STACK DIAMETER, in. 24
 PROBE HEATER SETTING 250
 HEATER BOX SETTING 250


MEIER AM. _____
 FACTOR _____
 PROCESS WEIGHT RATE _____
 ORSAT RESULTS
 CO2 20.2
 CO 20.0
 N2 _____

PRELIMINARY
PRINT OUT

TRAVERSE POINT NUMBER	SAMPLING TIME (Hr.)	STATIC PRESSURE (in. H ₂ O)	STACK TEMPERATURE (T _s), °F	VELOCITY HEAD (VP), (1/2 VP) ²	PRESSURE DIFFERENTIAL ACROSS ORIFICE METER (in. H ₂ O) ACTUAL DESIRED	GAS SAMPLE VOLUME (V _m), ft ³	GAS SAMPLE TEMPERATURE AT DRY GAS METER INLET (T _m), °F OUTLET (T _m), °F	SAMPLE BOX TEMPERATURE °F	TEMPERATURE OF GAS LEAVING CONDENSER OR LAST IMPINGER °F	PUMP VACUUM in Hg gauge	VELOCITY fps
1	1020.00		125	.48	1.30	7376.00	60	945.54	676.98		
2	921		123	.58	1.65	777	60	947.58	701.00		
3	25		130	.62	1.70	79.6	60				
4	274		130	.62	1.78	81.5	61	7.00/54			
5	30		130	.62	1.78	83.4	62				
6	324		125	.60	1.70	85.4	62				
7	31		125	.60	1.70	87.3	62				
8	31		130	.60	1.70	89.2	62				
9	40		130	.52	1.50	91.0	62				
10	42		130	.40	1.18	92.7	62				
11	65		125	.30	.92	94.4	63				
12	41		125	.28	.82	95.7	64				
13	54571		125	.98	.50	97.0	69				
14	51		130	.34	.90	98.3	71				
15	574		130	.22	1.50	99.6	71				
16	00		130	.64	1.85	01.2	71				
17	024		130	.64	1.85	03.4	72				
18	05		130	.62	1.78	05.3	73				
19	071		130	.60	1.70	07.1	73				
20	10		130	.58	1.65	09.0	74				
21	24		130	.50	1.45	10.8	75				
22	11		130	.44	1.21	12.4	75				
23	171		130	.30	1.80	13.9	75				
24	20		130	.20	1.4	15.2	75				

PARTICULATE FIELD DATA

SCHEMATIC OF STACK



PLANT Hillsmore METER AM
 DATE 7-20-91 C FACTOR _____
 LOCATION New London BAROMETRIC PRESSURE SS
 OPERATOR WJO ASSUMED MOISTURE, % SAT
 STACK NO. KSE 2 0.5 PROBE LENGTH, in. 3'
 RUN NO. 3 NOZZLE DIAMETER, in. 1/2
 SAMPLE BOX NO. 3 STACK DIAMETER, in. 26
 METER BOX NO. 1 PROBE HEATER SETTING 250
 ORSAT RESULTS
 CO₂ _____
 O₂ _____
 CO _____
 N₂ _____
 H₂ _____
 H₂O _____

TRAVERSE POINT NUMBER	SAMPLING TIME (hr), min.	STATIC PRESSURE (in. H ₂ O)	STACK TEMPERATURE (T _g), °F	VELOCITY HEAD (V _p), (1/16")	PRESSURE DIFFERENTIAL ACROSS ORIFICE METER (in. H ₂ O)	GAS SAMPLE VOLUME (V _m), ft ³	GAS SAMPLE TEMPERATURE AT DRY GAS METER INLET (T _{m,in}), °F	OUTLET (T _{m,out}), °F	SAMPLE BOX TEMPERATURE °F	SYNTHETIC TEMPERATURE OF GAS LEAVING CONDENSER OR LAST IMPINGER °F	PUMP VACUUM in. Hg gauge	VELOCITY f/s
1	120550		125	.25	.82	74.80	60	60	947.50/50	701000		
2	074		125	.34	.96	19.5	69	69	949.50/50	723000		
3	10		130	.54	1.55	20.8	70	70	2.00/55			
4	124	- .20	130	.62	1.70	22.6	70	70				
5	15		130	.64	1.85	24.4	71	71				
6	12		130	.64	1.85	26.4	72	72				
7	20		130	.58	1.65	28.3	72	72				
8	22		130	.54	1.55	30.2	73	73				
9	25		125	.54	1.55	31.9	73	73				
10	27		130	.46	1.32	33.8	73	73				
11	30		125	.30	.86	35.4	73	73				
12	35		125	.28	.82	36.8	74	74				
13	3.374		130	.46	1.32	38.1	77	77				
14	6		130	.58	1.65	39.7	78	78				
15	624		130	.60	1.70	41.5	78	78				
16	55	- .20	125	.62	1.78	43.3	78	78				
17	57		130	.62	1.78	45.3	79	79				
18	50		130	.60	1.70	47.1	79	79				
19	54		130	.60	1.70	49.0	79	79				
20	55		130	.58	1.60	50.9	79	79				
21	524		130	.54	1.55	52.7	79	79				
22	00		130	.40	1.15	54.4	80	80				
23	05		125	.30	.86	56.0	80	80				
24	07		125	.28	.82	57.3	80	80				


PARTICULATE FIELD DATA

PLANT ILLUSIATLE MEIER A.H. _____
DATE 9-19-91 C FACTOR _____
LOCATION NEW CONCORD PROCESS WEIGHT RATE _____
OPERATOR MSH ORSAT RESULTS _____
STACK NO. KSI 3-126T CO2 0.2 (807M)
RUN NO. 1 CO 0220.1 IN _____
SAMPLE BOX NO. 4 CO 560 IN / 550 OUT IN _____
METER BOX NO. 2 N2 BALE _____

4

4

PREL-OK
P/TOT-OK
POST-OK

[illegible]

50

PLANT *HILLSHIRE*

AMBIENT TEMPERATURE

The diagram illustrates a gas flow system for sampling. A horizontal tube carries gas flow from right to left, as indicated by the 'GAS FLOW' label and arrow. A vertical 'SAMPLING LINE' branches off downwards from the center of this tube. The horizontal tube is labeled 'DISTURBANCE' at both ends. A scale bar at the bottom indicates distances of 0, 1, 2, and 3 units.

DATE 9-19-91

LOCATION VIEW, ON DIRT!

ASSUMED MOISTURE %

0/

OPERATOR YES

PROBE LENGTH, in.

5

STACK NO. N1-5757

NOZZLE DIAMETER, in. —

51

RUN NO. 6

STACK DIAMETER, in. —

7210

SAMPLE BOX NO. 5

PROBE HEATER SETTING

250

2

HEATED BOX SETTING


052

CROSS SECTION

[illegible]


PARTICULATE FIELD DATA

PLANT	1-1115 MCI	AMBIENT TEMPERATURE	90	METER ΔH	
DATE	9-15-91	BAROMETRIC PRESSURE		C FACTOR	
LOCATION	New London	ASSUMED MOISTURE, %	10	PROCESS WEIGHT RATE	
OPERATOR	MJH	PROBE LENGTH, in.	5' S.S.	ORSAT RESULTS	
STACK NO.	KSI 3-12	NOZZLE DIAMETER, in.	1/4	CO ₂	
RUN NO.	3	STACK DIAMETER, in.	(20 1/2)" ²	O ₂	
SAMPLE BOX NO.	6	PROBE HEATER SETTING	250	CO	
METER BOX NO.	2	HEATER BOX SETTING	250	N ₂	
				PREC ORC	
				PITOT ORC	

[illegible]

PARTICULATE FIELD DATA

SCHEMATIC OF STACK



CROSS SECTION

PLANT HILLSHIRE FARM DATE 9-19-91 LOCATION NEW LONDON OPERATOR WJO STACK NO. KSI 3 - OUTLET RUN NO. 1 SAMPLE BOX NO. 1 METER BOX NO. 1

AMBIENT TEMPERATURE 45 BAROMETRIC PRESSURE 30.1 ASSUMED MOISTURE, % SAT (18.1) PROBE LENGTH, in. 3' NOZZLE DIAMETER, in. 1/4 STACK DIAMETER, in. 24 PROBE HEATER SETTING 250 HEATER BOX SETTING 250


MEIER AM 1.77 C FACTOR 1.002 PROCESS WEIGHT RATE 8.5 91 ORSAT RESULTS CO2 0.2 CO 20.4 N2 79.4 FUELUM POST LKUM PITOT LKUM

TRAVERSE POINT NUMBER	SAMPLING TIME (H), min.	STATIC PRESSURE (in. H ₂ O)	STACK TEMPERATURE (T _s), °F	VELOCITY HEAD (1/P _s) (1/17.1)	PRESSURE DIFFERENTIAL ACROSS ORIFICE METER (in. H ₂ O) ACTUAL DESIRED	GAS SAMPLE VOLUME (V _m), ft ³	GAS SAMPLE TEMPERATURE AT DRY GAS METER INLET (T _{m, in}), °F OUTLET (T _{m, out}), °F	SKS TEMPERATURE OF GAS LEAVING CONDENSER OR LAST IMPINGER °F	PUMP VACUUM in. Hg gauge	VELOCITY lps
1	10:50:00	-0.20	130	34	0.92	707.00	45	1417.96		
2	5:24	-0.20	135	38	1.02	18.5	46	1727.96		
3	5:5		135	39	1.05	20.0	47	17000		
4	5:14	-0.26	135	42	1.14	21.5	48			
5	5:00		140	45	1.20	23.1	49			
6	5:04	-0.24	135	45	1.20	24.7	50			
7	5:05		135	47	1.22	26.4	50			
8	5:07	-0.22	135	42	1.10	28.1	51			
9	5:10		135	34	0.90	29.7	52			
10	5:11	-0.20	140	32	0.84	31.7	53			
11	5:15		135	30	0.78	32.4	53			
12	5:17	-0.20	135	30	0.78	33.6	54			
13	5:18:21		135	34	0.92	34.5	54			
14	5:25	-0.20	135	40	1.05	36.4	54			
15	5:27		135	42	1.10	37.9	54			
16	5:30	-0.24	135	45	1.15	39.4	60			
17	5:32		135	47	1.22	41.0	60			
18	5:35	-0.24	135	47	1.20	42.6	60			
19	5:37		140	45	1.15	44.3	62			
20	5:40	-0.22	135	38	1.00	45.9	62			
21	5:42		135	33	0.84	47.3	62			
22	5:44	-0.20	135	32	0.80	48.6	65			
23	5:47		135	30	0.78	49.9	65			
24	5:50		135	30	0.78	51.2	65			

1.0
1.0
2.8
4.0
6.0

PARTICULATE FIELD DATA


SCHEMATIC OF STACK



PLANT HILL SITE AMBIENT TEMPERATURE 41 MEIER ΔH
 DATE 9-19-91 BAROMETRIC PRESSURE 18 C FACTOR
 LOCATION NEW LONDON ASSUMED MOISTURE, % 18 PROCESS WEIGHT RATE
 OPERATOR WJD PROBE LENGTH, in. 3' ORSAT RESULTS
 STACK NO. KSI 3 OUT NOZZLE DIAMETER, in. 1/4 CO2 0.2
 RUN NO. 2 STACK DIAMETER, in. 26 CO 20.4
 SAMPLE BOX NO. 2 PROBE HEATER SETTING 250 N2
 METER BOX NO. 1 HEATER BOX SETTING 250 PER LK M
PITOT LK M

TRAVERSE POINT NUMBER	SAMPLING TIME (hr), min	STATIC PRESSURE (in. H ₂ O)	STACK TEMPERATURE (T _s), °F	VELOCITY HEAD (V _p) (ft./min) ²	PRESSURE DIFFERENTIAL ACROSS ORIFICE METER (ΔH) in. H ₂ O	GAS SAMPLE VOLUME (V _m), ft ³	GAS SAMPLE TEMPERATURE AT DRY GAS METER INLET (T _{m,i}), °F	OUTLET (T _{m,o}), °F	SAMPLE BOX TEMPERATURE °F	TEMPERATURE OF GAS LEAVING CONDENSER OR LAST IMPINGER °F	PUMP VACUUM in. Hg gauge	VELOCITY fpm
1	125732		135	36	.96	7255.00	50	51	939.54/46	178800		
2	125733		135	36	.94	56.5	51	51	941.50/46	19500		
3	125734		135	41	1.14	57.9	51	52	2.00/46			
4	125735	-22	140	46	1.20	59.5	52	53				
5	125736		135	47	1.22	61.1	53	53				
6	125737		135	47	1.22	62.7	53	53				
7	125738		135	45	1.14	64.4	54	54				
8	125739		135	40	1.05	66.1	55	55				
9	125740		135	35	.92	67.5	55	55				
10	125741		131	30	.73	68.5	55	55				
11	125742		135	30	.78	70.3	55	55				
12	125743		135	28	.74	71.5	55	55				
13	125744		135	32	.84	72.1	58	58				
14	125745		135	34	.90	74.1	59	59				
15	125746		140	36	.94	75.6	60	60				
16	125747	-22	135	40	1.05	76.9	60	60				
17	125748		135	44	1.15	78.4	60	60				
18	125749		135	46	1.20	80.0	60	60				
19	125750		135	40	1.15	81.6	61	61				
20	125751		135	34	1.05	83.2	62	62				
21	125752		135	34	.96	84.6	62	62				
22	125753		135	34	.90	86.1	62	62				
23	125754		135	30	.78	87.4	62	62				
24	125755		135	30	.78	88.7	62	62				

SCHEMATIC OF STACK



CROSS SECTION

PARTICULATE FIELD DATA

PLANT ALLSHEAR AMBIENT TEMPERATURE _____ WEIER AM _____
 DATE 9-19-91 BAROMETRIC PRESSURE _____ C FACTOR _____
 LOCATION New London ASSUMED MOISTURE, % 18 PROCESS WEIGHT RATE _____
 OPERATOR WJD PROBE LENGTH, in. _____ ORSAT RESULTS
 STACK NO. KSE 3005 NOZZLE DIAMETER, in. 1/4 CO₂ _____
 RUN NO. 3 STACK DIAMETER, in. 24 CO _____
 SAMPLE BOX NO. 3 PROBE HEATER SETTING 250 N₂ _____
 METER BOX NO. 1 HEATER BOX SETTING 250 1 k ohm
P. T. OF UConn

TRAVERSE POINT NUMBER	SAMPLING TIME (H), min.	STATIC PRESSURE (in. H ₂ O)	STACK TEMPERATURE (T _s), °F	VELOCITY HEAD (V _p) (1/TP)	PRESSURE DIFFERENTIAL ACROSS ORIFICE METER (in. H ₂ O) ACTUAL DESIRED	GAS SAMPLE VOLUME (V _m), ft ³	GAS SAMPLE TEMPERATURE AT DRY GAS METER INLET (T _{m,i}), °F OUTLET (T _{m,o}), °F	SAMPLE BOX TEMPERATURE °F	TEMPERATURE OF GAS LEAVING CONDENSER OR LAST IMPINGER °F	PUMP VACUUM in. Hg gauge	VELOCITY fpm
A1	140730		135	33	.80	729.00	52	941.50/41	193.300		
2	50		135	35	.92	92.9	53	943.50/48	209.067		
3	52		135	37	.95	93.7	54				
4	55	-24	140	40	1.05	95.2	54				
5	58		135	44	1.15	96.7	54				
6	00		135	46	1.20	98.6	55				
7	02		135	43	1.12	00.0	55				
8	05		140	40	1.05	01.5	56				
9	07		135	37	0.98	03.0	57				
10	10		135	35	.84	04.4	58				
11	13		135	30	.78	05.8	59				
12	15		135	30	.78	07.1	59				
13	17		135	35	.92	08.4	61				
14	20		135	36	.94	09.7	62				
15	25		135	40	1.05	11.1	62				
16	27		140	46	1.20	12.6	62				
17	30	-24	135	47	1.22	14.2	63				
18	32		135	48	1.25	15.8	64				
19	35		135	48	1.15	17.4	64				
20	37		135	40	1.05	19.0	65				
21	40		135	36	.96	20.5	65				
22	42		135	34	.88	21.9	65				
23	45		135	30	.78	23.3	65				
24	47		135	28	.71	24.5	65				

24.72

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME Hillshire

DATE OF TEST 9-20-91

JOB NO. _____

TEST ENGINEER MJH

RUN NO. 1 STACK ESI 2 iv

SAMPLE BOX 4 FILTER 1471 WASH BOTTLE _____

BEAKERS: FH Ace 13 BH Trichl 7 BH Ace 14 BH H₂O F

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>152</u>	<u>100</u>	<u>52</u>
<u>2</u>	<u>138</u>	<u>100</u>	<u>38</u>
<u>3</u>	<u>3</u>	<u>0</u>	<u>3</u>
<u>SIL GEL</u>	<u>686</u>	<u>680</u>	<u>6</u>
		<u>WATER TOTAL</u>	<u>99</u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.9332</u>	<u>0.7891</u>	<u>0.1441</u>
FH Wash	<u>0.0009</u>	<u>105.8740</u>	<u>105.8478</u>	<u>0.0253</u>
			<u>FILTERABLE TOTAL</u>	<u>0.1694</u>
Extract	<u>0.0005</u>	<u>67.5580</u>	<u>67.5237</u>	<u>0.0338</u>
Acetone	<u>0.0003</u>	<u>103.2673</u>	<u>103.2234</u>	<u>0.0436</u>
Water	<u>0.0002</u>	<u>115.3098</u>	<u>115.2953 (2.93)</u>	<u>0.0419</u>
			<u>CONDENSIBLE TOTAL</u>	<u>0.1193</u>
			<u>PARTICULATE TOTAL</u>	<u>0.2887</u>

$$\frac{(tot)}{(cal)} = \frac{293}{100} = 2.93$$

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME H.115/12

DATE OF TEST 9-20-91

JOB NO. _____

TEST ENGINEER MJH

RUN NO. 2 STACK K51 2 in

SAMPLE BOX 5 FILTER 1472 WASH BOTTLE —

BEAKERS: FH Ace 15 BH Trichl 8 BH Ace 16 BH H₂O 6

WATER COLLECTED

Impinger No.	Final Wt. - g	Initial Wt. - g	Collected - g
<u>1</u>	<u>169</u>	<u>100</u>	<u>69</u>
<u>2</u>	<u>120</u>	<u>100</u>	<u>20</u>
<u>3</u>	<u>2</u>	<u>0</u>	<u>2</u>
<u>SIL GFC</u>	<u>676</u>	<u>670</u>	<u>6</u>
WATER TOTAL			<u><u>97</u></u>

PARTICULATE COLLECTED

	Blank	Final Wt.	Tare Wt.	Collected - g
Filter		<u>0.9173</u>	<u>0.7878</u>	<u>0.1295</u>
FH Wash	<u>0.0009</u>	<u>95.5520</u>	<u>95.5292</u>	<u>0.0219</u>
FILTERABLE TOTAL				<u><u>0.1514</u></u>

Extract	<u>0.0005</u>	<u>68.8462</u>	<u>68.8007</u>	<u>0.0450</u>
Acetone	<u>0.0003</u>	<u>96.1042</u>	<u>96.0761</u>	<u>0.0278</u>
Water	<u>0.0002</u>	<u>111.6614</u>	<u>111.6500 (2.91)</u>	<u>0.0326</u>
CONDENSIBLE TOTAL				<u><u>0.1054</u></u>

$$\frac{(\text{wt})}{(\text{al. p})} \frac{291}{100} = 2.91$$

PARTICULATE TOTAL

0.2568

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME Hillshire

DATE OF TEST 9-20-91

JOB NO. _____

TEST ENGINEER MJH

RUN NO. 3 STACK KS1 7 12

SAMPLE BOX _____ FILTER 1473 WASH BOTTLE _____

BEAKERS: FH Ace 17 BH Trichl 9 BH Ace 18 BH H₂O H

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>179</u>	<u>100</u>	<u>79</u>
<u>2</u>	<u>118</u>	<u>100</u>	<u>18</u>
<u>3</u>	<u>4</u>	<u>0</u>	<u>4</u>
<u>SIL GEL</u>	<u>690</u>	<u>682</u>	<u>8</u>
<u>WATER TOTAL</u>			<u>109</u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.9289</u>	<u>0.8027</u>	<u>0.1262</u>
FH Wash	<u>0.0009</u>	<u>94.3646</u>	<u>94.3467</u>	<u>0.0170</u>
<u>FILTERABLE TOTAL</u>				<u>0.1432</u>

Extract	<u>0.0005</u>	<u>72.7250</u>	<u>72.1723</u>	<u>0.0522</u>
Acetone	<u>0.0003</u>	<u>93.3389</u>	<u>93.3086</u>	<u>0.0300</u>
Water	<u>0.0002</u>	<u>109.7978</u>	<u>109.7700 (301)</u>	<u>0.0831</u>
<u>CONDENSIBLE TOTAL</u>				<u>0.1653</u>

$\frac{(101)}{(014)} \frac{301}{100} = 3.01$
PARTICULATE TOTAL
0.3085

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME 411/shr

DATE OF TEST 6-20-91

JOB NO. _____

TEST ENGINEER VJD

RUN NO. 1

STACK KSI Zout

SAMPLE BOX 1

FILTER 1468

WASH BOTTLE —

BEAKERS: FH Ace 1

BH Trichl 2

BH Ace 2

BH H₂O A

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>182</u>	<u>100</u>	<u>82</u>
<u>2</u>	<u>116</u>	<u>100</u>	<u>16</u>
<u>3</u>	<u>3</u>	<u>0</u>	<u>3</u>
<u>SL GEC</u>	<u>682</u>	<u>677</u>	<u>5</u>
<u>WATER TOTAL</u>			<u><u>106</u></u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.8230</u>	<u>0.8041</u>	<u>0.0189</u>
FH Wash	<u>0.0009</u>	<u>96.6341</u>	<u>96.6053</u>	<u>0.0279</u>
<u>FILTERABLE TOTAL</u>				<u><u>0.0468</u></u>
Extract	<u>0.0005</u>	<u>70.3158</u>	<u>70.2449</u>	<u>0.0204</u>
Acetone	<u>0.0003</u>	<u>98.2491</u>	<u>98.2388</u>	<u>0.0100</u>
Water	<u>0.0007</u>	<u>110.1399</u>	<u>110.1338 (3.41)</u>	<u>0.0178</u>
<u>CONDENSIBLE TOTAL</u>				<u><u>0.0482</u></u>
<u>PARTICULATE TOTAL</u>				<u><u>0.0950</u></u>

$$\frac{\left(\frac{\text{tot}}{\text{at.g}}\right)}{100} = 3.41$$

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME Hillshire

DATE OF TEST 6-20-91

JOB NO. _____

TEST ENGINEER WJN

RUN NO. 2 STACK ksi 2 out

SAMPLE BOX 7 FILTER 1469 WASH BOTTLE _____

BEAKERS: FH Ace 3 BH Trichl 5 BH Ace 4 BH H₂O B

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>175</u>	<u>100</u>	<u>75</u>
<u>2</u>	<u>118</u>	<u>100</u>	<u>18</u>
<u>3</u>	<u>6</u>	<u>0</u>	<u>6</u>
<u>SIL GEL</u>	<u>639</u>	<u>633</u>	<u>6</u>
		<u>WATER TOTAL</u>	<u>105</u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.8149</u>	<u>0.7939</u>	<u>0.0210</u>
FH Wash	<u>0.0009</u>	<u>102.6067</u>	<u>102.5983</u>	<u>0.0075</u>
			<u>FILTERABLE TOTAL</u>	<u>0.0285</u>
Extract	<u>0.0005</u>	<u>71.7433</u>	<u>71.7281</u>	<u>0.0147</u>
Acetone	<u>0.0003</u>	<u>95.3987</u>	<u>95.3880</u>	<u>0.0104</u>
Water	<u>0.0002</u>	<u>111.2661</u>	<u>111.2504</u> (2.4)	<u>0.0164</u>
			<u>CONDENSIBLE TOTAL</u>	<u>0.0415</u>
			<u>PARTICULATE TOTAL</u>	<u>0.0700</u>

$$\frac{(\text{wt})}{(\text{dl. g})} \frac{299}{100} = 2.99$$

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME Hillshire DATE OF TEST 6-20-71
 JOB NO. _____ TEST ENGINEER WJD
 RUN NO. 3 STACK NSI 2 out
 SAMPLE BOX 3 FILTER 1470 WASH BOTTLE —
 BEAKERS: FH Ace 5 BH Trichl 6 BH Ace 6 BH H₂O 6

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>180</u>	<u>100</u>	<u>80</u>
<u>2</u>	<u>122</u>	<u>100</u>	<u>22</u>
<u>3</u>	<u>3</u>	<u>0</u>	<u>3</u>
<u>SIL GEL</u>	<u>650</u>	<u>645</u>	<u>5</u>
<u>WATER TOTAL</u>			<u><u>110</u></u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.8206</u>	<u>0.7945</u>	<u>0.0261</u>
FH Wash	<u>0.0009</u>	<u>96.4518</u>	<u>96.4360</u>	<u>0.0149</u>
<u>FILTERABLE TOTAL</u>				<u><u>0.0410</u></u>
Extract	<u>0.0005</u>	<u>69.6670</u>	<u>69.6530</u>	<u>0.0135</u>
Acetone	<u>0.0003</u>	<u>97.6942</u>	<u>97.6872</u>	<u>0.0067</u>
Water	<u>0.0002</u>	<u>105.6058</u>	<u>105.6002</u> 3.05	<u>0.0143</u>
<u>CONDENSIBLE TOTAL</u>				<u><u>0.0345</u></u>
<u>PARTICULATE TOTAL</u>				<u><u>0.0755</u></u>

$$\frac{\frac{(4.4)}{(41.8)}}{\frac{305}{100}} = 3.05$$

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME Hillshire

DATE OF TEST 6-19-71

JOB NO. _____

TEST ENGINEER MJH

RUN NO. 1 STACK K51 3 IN

SAMPLE BOX 4 FILTER 1422 WASH BOTTLE _____

BEAKERS: FH Ace 1 BH Trichl 10 BH Ace 2 BH H₂O 4

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>200</u>	<u>100</u>	<u>100</u>
<u>2</u>	<u>142</u>	<u>100</u>	<u>42</u>
<u>3</u>	<u>2</u>	<u>0</u>	<u>2</u>
<u>SIL GEL</u>	<u>640</u>	<u>630</u>	<u>10</u>
<u>WATER TOTAL</u>			<u><u>154</u></u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.9426</u>	<u>0.8072</u>	<u>0.1354</u>
FH Wash	<u>0.0009</u>	<u>96.6387</u>	<u>96.6059</u>	<u>0.0328</u>
<u>FILTERABLE TOTAL</u>				<u><u>0.1682</u></u>
Extract	<u>0.0005</u>	<u>67.5141</u>	<u>67.4693</u>	<u>0.0448</u>
Acetone	<u>0.0003</u>	<u>98.2900</u>	<u>98.2390</u>	<u>0.0510</u>
Water	<u>0.0002</u>	<u>110.1669</u>	<u>110.1352 (344)</u>	<u>0.0317</u>
<u>CONDENSIBLE TOTAL</u>				<u><u>0.2034</u></u>
<u>PARTICULATE TOTAL</u>				<u><u>0.3707</u></u>

$$\frac{344}{100} = 3.44$$
 tot
avg

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME Hillshire

DATE OF TEST 6-19-91

JOB NO. _____

TEST ENGINEER MJH

RUN NO. 2 STACK LSI 3 in

SAMPLE BOX 5 FILTER 1425 WASH BOTTLE -

BEAKERS: FH Ace 3 BH Trichl 11 BH Ace 4 BH H₂O B

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>215</u>	<u>100</u>	<u>115</u>
<u>2</u>	<u>120</u>	<u>100</u>	<u>20</u>
<u>3</u>	<u>4</u>	<u>0</u>	<u>4</u>
<u>SIL GEL</u>	<u>670</u>	<u>658</u>	<u>12</u>
		<u>WATER TOTAL</u>	<u>151</u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.9027</u>	<u>0.8097</u>	<u>0.0930</u>
FH Wash	<u>0.0009</u>	<u>102.6214</u>	<u>102.5986</u>	<u>0.0219</u>
			<u>FILTERABLE TOTAL</u>	<u>0.1149</u>
Extract	<u>0.0005</u>	<u>68.6545</u>	<u>68.6093</u>	<u>0.0447</u>
Acetone	<u>0.0003</u>	<u>95.4262</u>	<u>95.3884</u>	<u>0.0375</u>
Water	<u>0.0002</u>	<u>111.2932</u>	<u>111.2617 (3M)</u>	<u>0.1061</u>
			<u>CONDENSIBLE TOTAL</u>	<u>0.1883</u>
			<u>PARTICULATE TOTAL</u>	<u>0.3032</u>

for
all
100 $\frac{339}{100} = 3.39$

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME Hillsboro DATE OF TEST 6-19-41
 JOB NO. _____ TEST ENGINEER MTJH
 RUN NO. 3 STACK 451 3
 SAMPLE BOX 6 FILTER 1426 WASH BOTTLE —
 BEAKERS: FH Ace 5 BH Trichl 12 BH Ace 6 BH H₂O C

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>219</u>	<u>100</u>	<u>119</u>
<u>2</u>	<u>127</u>	<u>102</u>	<u>27</u>
<u>3</u>	<u>4</u>	<u>0</u>	<u>4</u>
<u>212 GFL</u>	<u>682</u>	<u>664</u>	<u>18</u>
		<u>WATER TOTAL</u>	<u>168</u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.9189</u>	<u>0.8139</u>	<u>0.1050</u>
FH Wash	<u>0.0009</u>	<u>96.4516</u>	<u>96.4352</u>	<u>0.0155</u>
		<u>FILTERABLE TOTAL</u>		<u>0.1205</u>
Extract	<u>0.0005</u>	<u>68.7053</u>	<u>68.6520</u>	<u>0.0528</u>
Acetone	<u>0.0003</u>	<u>97.7282</u>	<u>97.6878</u>	<u>0.0401</u>
Water	<u>0.0002</u>	<u>105.6207</u>	<u>105.6018</u> 3.50	<u>0.0655</u>
		<u>CONDENSIBLE TOTAL</u>		<u>0.1584</u>
		<u>PARTICULATE TOTAL</u>		<u>0.2789</u>

(tot)
(alt)
 $\frac{350}{100} = 3.50$

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME Hillside

DATE OF TEST 6-19-41

JOB NO. _____

TEST ENGINEER WJD

RUN NO. 1 STACK KS1 3 out

SAMPLE BOX 1 FILTER 1464 WASH BOTTLE —

BEAKERS: FH Ace 7 BH Trichl 10 BH Ace 8 BH H₂O 15

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>193</u>	<u>100</u>	<u>93</u>
<u>2</u>	<u>132</u>	<u>100</u>	<u>32</u>
<u>3</u>	<u>2</u>	<u>0</u>	<u>2</u>
<u>SILICATE</u>	<u>641</u>	<u>633</u>	<u>8</u>
<u>WATER TOTAL</u>			<u><u>135</u></u>

PARTICULATE COLLECTED

	<u>Blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.8123</u>	<u>0.7972</u>	<u>0.0151</u>
FH Wash	<u>0.0009</u>	<u>93.8031</u>	<u>93.8905</u>	<u>0.0117</u>
<u>FILTERABLE TOTAL</u>				<u><u>0.0268</u></u>
Extract	<u>0.0005</u>	<u>67.4855</u>	<u>67.4692</u>	<u>0.0158</u>
Acetone	<u>0.0003</u>	<u>103.1820</u>	<u>103.1750</u>	<u>0.0067</u>
Water	<u>0.0002</u>	<u>115.2988</u>	<u>115.2936</u>	<u>0.0164</u>
<u>CONDENSIBLE TOTAL</u>				<u><u>0.0389</u></u>
<u>PARTICULATE TOTAL</u>				<u><u>0.0657</u></u>

$$\frac{\text{(tot)}}{\text{(al. g)}} = \frac{327}{100} = 3.27$$

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME H. 115 hore DATE OF TEST 6-19-71
 JOB NO. _____ TEST ENGINEER WJD
 RUN NO. 2 STACK KSI 3 out
 SAMPLE BOX 2 FILTER 1465 WASH BOTTLE _____
 BEAKERS: FH Ace 9 BH Trichl 11 BH Ace 10 BH H₂O _____

WATER COLLECTED

Impinger No.	Final Wt. - g	Initial Wt. - g	Collected - g
<u>1</u>	<u>198</u>	<u>100</u>	<u>98</u>
<u>2</u>	<u>129</u>	<u>100</u>	<u>29</u>
<u>3</u>	<u>9</u>	<u>0</u>	<u>9</u>
<u>SIL WFL</u>	<u>639</u>	<u>634</u>	<u>5</u>
WATER TOTAL			<u><u>141</u></u>

PARTICULATE COLLECTED

	Blank	Final Wt.	Tare Wt.	Collected - g
Filter		<u>0.8130</u>	<u>0.7964</u>	<u>0.0166</u>
FH Wash	<u>0.0009</u>	<u>95.7735</u>	<u>95.7635</u> <u>104.2438</u>	<u>0.0091</u>
FILTERABLE TOTAL				<u><u>0.0257</u></u>
Extract	<u>0.0005</u>	<u>68.6227</u>	<u>68.6094</u>	<u>0.0128</u>
Acetone	<u>0.0003</u>	<u>104.2537</u>	<u>104.2438</u>	<u>0.0096</u>
Water	<u>0.0002</u>	<u>111.6540</u>	<u>111.6473</u> 3.34	<u>0.0218</u>
CONDENSIBLE TOTAL				<u><u>0.0442</u></u>
PARTICULATE TOTAL				<u><u>0.0699</u></u>

$$\frac{\text{(tot)}}{\text{(wt. g)}} = \frac{336}{100} = 3.36$$

LABORATORY DATA SHEET
PARTICULATE & WATER COLLECTED

JOB NAME F.H. Shore

DATE OF TEST 6-19-91

JOB NO. _____

TEST ENGINEER WJD

RUN NO. 3 STACK 451 3 out

SAMPLE BOX 3 FILTER M6 WASH BOTTLE _____

BEAKERS: FH Ace 11 BH Trichl 12 BH Ace 12 BH H₂O H

WATER COLLECTED

<u>Impinger No.</u>	<u>Final Wt. - g</u>	<u>Initial Wt. - g</u>	<u>Collected - g</u>
<u>1</u>	<u>208</u>	<u>100</u>	<u>108</u>
<u>2</u>	<u>131</u>	<u>100</u>	<u>31</u>
<u>3</u>	<u>4</u>	<u>0</u>	<u>4</u>
<u>SIL 4K</u>	<u>666</u>	<u>661</u>	<u>5</u>
WATER TOTAL			<u><u>148</u></u>

PARTICULATE COLLECTED

	<u>blank</u>	<u>Final Wt.</u>	<u>Tare Wt.</u>	<u>Collected - g</u>
Filter		<u>0.8267</u>	<u>0.8061</u>	<u>0.0206</u>
FH Wash	<u>0.0009</u>	<u>102.2742</u>	<u>102.2612</u>	<u>0.0121</u>
FILTERABLE TOTAL				<u><u>0.0327</u></u>
Extract	<u>0.0005</u>	<u>68.6648</u>	<u>68.6516</u>	<u>0.0127</u>
Acetone	<u>0.0003</u>	<u>105.4140</u>	<u>105.4053</u>	<u>0.0084</u>
Water	<u>0.0002</u>	<u>109.7721</u>	<u>109.7690 (3.43)</u>	<u>0.0099</u>
CONDENSIBLE TOTAL				<u><u>0.0310</u></u>
PARTICULATE TOTAL				<u><u><u>0.0637</u></u></u>

$$\begin{array}{r} \text{(tot)} \quad 343 \\ \text{(wt. g)} \quad 100 \\ \hline = 3.43 \end{array}$$

Technology & Engineering Corp.

OP-100 (Rev. 1-78)

Name of Company <i>Hillshire Labs</i>		Date <i>9-20-91</i>	
Location <i>New London</i>		PLD Number <i>K512 Smokehouse</i>	
City, State, Zip Code <i>New London</i>		Observer Certification Date <i>4-9-91</i>	
Discharge Location <i>SAFC</i>		Control Device <i>Scrubber</i>	
Height of Discharge Above Ground <i>75'</i>		Steam Plume? ☒ Yes ☐ No Attached ☒ Detached ☐	
Time of Observation	Initial <i>(A)</i> <i>0840-9:10</i>	Final <i>(B)</i> <i>10:30-11:00</i>	
Observer Location			
Distance to Discharge	<i>100'</i>		
Direction from Discharge	<i>SE</i>		
Height of Observation Point in Relation to Discharge	<i>-20'</i>		
Plume Description (Color, Length, etc.)	<i>Steam 50' Steam 25'</i>		
Plume Background Description	<i>BL sky</i>		
Weather Conditions			
Wind Direction	<i>W</i>		
Wind Speed	<i>5-10 0-5</i>		
Ambient Temperature	<i>50</i>		
Sky Conditions (clear, overcast, % clouds, etc.)	<i>CLR</i>		

(A)					(B)				
SEC	0	15	30	45	SEC	0	15	30	45
0	10	10	10	10	30	5	10	10	10
1	10	10	10	10	31	10	5	5	5
2	10	10	10	10	32	5	10	5	5
3	10	10	10	10	33	5	5	5	5
4	5	10	10	5	34	10	10	5	10
5	10	5	10	10	35	10	5	10	10
6	10	10	10	10	36	10	10	10	5
7	10	10	5	10	37	10	10	10	10
8	10	5	10	10	38	5	10	5	5
9	5	10	5	5	39	10	5	10	10
10	5	10	5	10	40	10	10	10	10
11	10	10	10	15	41	5	5	10	5
12	15	10	10	10	42	5	10	10	5
13	10	15	10	10	43	5	5	5	5
14	10	10	5	5	44	10	10	5	10
15	5	5	10	5	45	5	5	5	10
16	10	10	10	10	46	5	5	5	10
17	10	10	10	10	47	10	5	5	10
18	5	10	5	10	48	5	10	10	10
19	10	5	10	10	49	10	5	5	10
20	5	10	5	5	50	10	5	10	10
21	10	10	10	10	51	10	15	10	5
22	10	10	5	10	52	10	10	15	10
23	10	5	10	10	53	10	15	10	10
24	10	15	10	10	54	10	5	10	10
25	10	10	10	10	55	5	10	10	5
26	10	10	10	10	56	10	10	5	10
27	5	10	10	10	57	10	5	5	10
28	10	10	10	5	58	10	10	10	15
29	10	10	10	15	59	10	5	10	15

Describe Point in Plume at Which Opacity was Determined
100 downstream (1st 50' steam)

Remarks:
#2 run steam plume 25' + 25' down read 50' downstream


Summary of Average Opacity (From Computer Program)

Set Number	Time	Opacity	
	Start - End	Sum	Average
		225	9.4
		210	8.7
		225	9.4
		190	7.9
		240	10
		195	7.3
		208	8.3
		165	6.9
		235	9.8
		215	8.9

Allowable Source Opacity

Signature of Observer <i>CHL</i>	Name of Observer (Please print) <i>Chris Huevink</i>
-------------------------------------	---

Sketch of Observer, Discharge, and Sun Location.




Name of Company Hillshire Kohns		Date 9-20-91	
Location		FID Number KSI 2 Smokehouse	
City, State, Zip Code New London		Observer Certification Date 4-9-91	
Discharge Location SAME		Control Device Scrubber	
Height of Discharge Above Ground 75'		Steam Plume? ☒ Attached ☐ Detached	
Time of Observation	Initial 12:00	☒ C	Final
Observer Location			
Distance to Discharge	100		
Direction from Discharge	SE		
Height of Observation Point in Relation to Discharge	-20		
Plume Description (Color, Length, etc.)	Steam		
Plume Background Description	sky		
Weather Conditions	W		
Wind Direction			
Wind Speed	0-5		
Ambient Temperature	60		
Sky Conditions (clear, overcast, & clouds, etc.)	Partly Cloudy 50%		

Describe Point in Plume at Which Opacity was Determined
50' downstream from discharge

- Wind shift at 12:15 to SW at 0-5 mph

Set Number	Time	Opacity	
	Start - End	Sum	Average
		200	8.3
		195	8.1
		205	8.4
		180	7.5
		200	8.3

Signature of Observer 	Name of Observer (Please print) Chris Huanig
Sketch of Observer, Discharge, and Gun Location.	



SEC MIN	0	15	30	45	SEC MIN	0	15	30	45
0	10	10	10	10	30	10	10	10	10
1	10	10	10	10	31	10	10	10	10
2	10	10	10	10	32	10	10	10	10
3	10	10	10	10	33	10	10	10	10
4	10	10	10	10	34	10	10	10	10
5	10	10	10	10	35	10	10	10	10
6	10	10	10	10	36	10	10	10	10
7	10	10	10	10	37	10	10	10	10
8	10	10	10	10	38	10	10	10	10
9	10	10	10	10	39	10	10	10	10
10	10	10	10	10	40	10	10	10	10
11	10	10	10	10	41	10	10	10	10
12	10	10	10	10	42	10	10	10	10
13	10	10	10	10	43	10	10	10	10
14	10	10	10	10	44	10	10	10	10
15	10	10	10	10	45	10	10	10	10
16	10	10	10	10	46	10	10	10	10
17	10	10	10	10	47	10	10	10	10
18	10	10	10	10	48	10	10	10	10
19	10	10	10	10	49	10	10	10	10
20	10	10	10	10	50	10	10	10	10
21	10	10	10	10	51	10	10	10	10
22	10	10	10	10	52	10	10	10	10
23	10	10	10	10	53	10	10	10	10
24	10	10	10	10	54	10	10	10	10
25	10	10	10	10	55	10	10	10	10
26	10	10	10	10	56	10	10	10	10
27	10	10	10	10	57	10	10	10	10
28	10	10	10	10	58	10	10	10	10
29	10	10	10	10	59	10	10	10	10

Allowable Source Opacity

Technology &
Engineering Corp.

SMOKE FORM

Name of Company Hickshire Farm	Date 9-19-91
Location NEW LONDON	FID Number KSEI 3 SHOKETOUSE
City, State, Zip Code NEW LONDON	Observer Certification Date 4-9-91
Discharge Location SAME	Control Device SCRUOPER
Height of Discharge Above Ground 75'	Steam Plume? ☒ Yes ☐ No Attached
Time of Observation 1620	Initial 1620 Final 1650
Observer Location Distance to Discharge ~100'	
Direction from Discharge N	
Height of Observation Point in Relation to Discharge -5'	
Plume Description (Color, Length, etc.) STEAM ~ 40' SLIGHT TAN TAIL DARK TREE	
Plume Background Description N	
Weather Conditions W	
Wind Direction 10-15	
Wind Speed 50	
Ambient Temperature OVERCAST	

SEC MIN	0	15	30	45	SEC MIN	0	15	30	45
0	10	5	10	10	30				
1	10	10	10	10	31				
2	10	10	10	15	32				
3	10	10	5	10	33				
4	15	10	10	10	34				
5	10	15	10	10	35				
6	10	10	10	5	36				
7	5	5	10	10	37				
8	10	10	10	15	38				
9	15	10	5	10	39				
10	10	10	10	10	40				
11	10	5	10	10	41				
12	5	5	10	10	42				
13	10	5	10	10	43				
14	10	10	10	15	44				
15	10	10	10	15	45				
16	10	5	10	10	46				
17	10	15	10	10	47				
18	5	10	10	10	48				
19	10	10	10	10	49				
20	5	10	10	10	50				
21	10	5	10	15	51				
22	5	10	10	10	52				
23	10	5	10	5	53				
24	10	15	10	10	54				
25	10	10	10	10	55				
26	10	5	10	10	56				
27	10	10	15	10	57				
28	10	10	10	10	58				
29	10	10	10	10	59				

Describe Point in Plume at Which Opacity was Determined
AFTER STEAM GONE

Remarks: **GOOD BACKGROUND - DARK TREES WITH PLUME LOCATED FROM ALL OTHERS.**


Summary of Average Opacity
(From Computer Program)

Set Number	Time	Opacity	
	Start - End	Sum	Average
		245	10.1
		225	9.4
		235	9.8
		215	8.9
		245	10.2

Signature of Observer
William J. Dick

Name of Observer (Please print)
WILLIAM J. DICK

Sketch of Observer, Discharge, and Sun Location.



Allowable Source Opacity