Note: This is a reference cited in *AP 42, Compilation of Air Pollutant Emission Factors, Volume I Stationary Point and Area Sources.* AP42 is located on the EPA web site at www.epa.gov/ttn/chief/ap42/

The file name refers to the reference number, the AP42 chapter and section. The file name "ref02_c01s02.pdf" would mean the reference is from AP42 chapter 1 section 2. The reference may be from a previous version of the section and no longer cited. The primary source should always be checked.

AP32 Section:	12.5.1
Background Chapter	3
Reference:	21
Title.	Report on Particulate/PM10 Compliance Testing. Performed for: Nucor Steel, Crawfordsville, IN, RT Mill Baghouse Stack. By: RCP Environmental on March 31, 1998. RCP Project No.: 033198.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT Indianapolis

OFFICE MEMORANDUM

To:

Phil Perry

Date: July 24, 1998

W

From:

Jarrod C. Fisher

Thru: Ed Surla

Subject:

Nucor Steel

Crawfordsville, Indiana Source ID No. 107 00038 Permit No. 107 3702

The subject company has submitted a report concerning particulate and PM-10 testing of the Cold Reversing Mill #2 controlled by mist elimination. EPA Methods 1-5, 9, and 202 were used. The test was conducted on March 31, 1998 by RCP, Inc. The purpose of the testing was to determine compliance status of the facility with regards to an emission limitation under an operating permit condition. I have reviewed this report and found the sampling procedures used and results to be acceptable to this Office. A copy of the test report is filed in the Compliance Data Section. The following is a summary of the test results:

Maximum Permitted Rate:
Average Rate During Test:

102.74 tons per hour 88.30 tons per hour

Filterable PM Testing (Method 5)

Average Measured Emissions:
Allowable Emissions (326 IAC <u>6-3-2</u>):

0.218 lb/hr 7.2 lb/hr

PM-10 Testing (Method 5 + Method 202)

Average Measured Emissions:

Allowable Emissions :

0.218 lb/hr 7.2 lb/hr

Highest 6-min Opacity:

Average Opacity:

Pressure Drops of Mist Eliminator:

Ω¥

0%

East In: 4.0 in. H₂O

East Out: 6.4 in. H_2O West In: 2.8 in. H_2O West Out: 5.0 in. H_2O

STATUS:

In Compliance (at 85.9% of max. permitted rate)

cc:

J. Fisher

WPS/General Files, Montgomery Co.

ESS EJNO LE-10V

RCP

Environmental

5455 West 86th Street Suite 113*Indianapolis, Indiana 46268

Regulatory Compliance Professionals

(317)872-1306

REPORT ON PARTICULATE/PM10 COMPLIANCE TESTING

Performed for:
Nucor Steel
Crawfordsville, Indiana
RT Mill Baghouse Stack
by: RCP Environmental
on March 31, 1998
RCP Project No.: 033198

RECEIVED

MAY 0 6 1998

STATE OF INDIANA
DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT

To the best of our knowledge, the data presented in this report is accurate and complete.

Respectfully Submitted by:

Michael Dicen, Vice-President

RCP Environmental

1-1 PROJECT OVERVIEW

RCP Environmental was contracted by Nucor Steel to perform particulate emissions sampling of the RT Mill Baghouse Stack in Crawfordsville, Indiana on March 31, 1998. The objective of the testing was to determine compliance to air operation permit requirements. The following personnel were involved with the testing program:

Michael Dicen
Paul Fabian
Rick Lyons
Steve Friend

The testing program included particulate (Methods 1-5,202) and visible emissions determination (Method 9). Below is a summary of the results:

Table 1-1 Summary of Test Results

			A COL TIOS ALICE		
Date	Runs	Time	Location	Emissions (lbs/hr)	Permitted Emissions (lbs/hr)
3/31/98	1-3	7:30- 12:33	Baghouse Stack	0.218	5.62

Nucor Steel Crawfordsville, Indiana

2-1 Results

FILTERABLE PARTICULATE BAGHOUSE STACK

Run No	0.	1	2	3	Avg.
Gas Con	ditions				
Ts	Stack Temperature (°F)	89	87	88.8	88.5
Bwo	Moisture (volume %)	1.16	1.01	0.52	0.90
O2	Oxygen (dry volume %)	20.9	20.9	20.9	20.9
CO2	Carbon Dioxide (dry volume %)	0.0	0.0	0.0	0.0
Volumet	ric Flow Rate				
Qa	Actual Conditions (acfm)	74,104	76,203	75,194	75,167
Qstd	Standard Conditions (dscfm)	72,307	72,652	71,870	71,610
<u>Particula</u>	te Results				
C_f	concentration, filterable (gr/dscf) condensable (gr,dscf)	0.002	0.0004	0.0004	0.00035
E _f	Emission Rate, filterable (lb/hr) filterable and condensable (lb/hr)	0.13	0.26	0.26	0.2180

Ď

OFFICE OF AIR MANAGEMENT TEST OBSERVATION REPORT

558
بمعيشين السمر
ستصلي

Agency: IDEM/OAM/CDS	
Date(s) of Test: 3-31-98	
Company Name: Nocor	Plant ID: <u>107 - 200 38</u>
Plant Location:	Title V: No No
City: Crawfordsv. 1/E County: Montgomery	Reported by: 52 F
Pollutants: pm/pmi O Reason(s) for Test: One	ELATING PELMIT
Facility(s) Tested: Temper/Reverse Mill	· · · · · · · · · · · · · · · · · · ·
Person(s) Interviewed: Kuck Lun	·
Test Observer(s): SLF	
Test Methods: 1-4,5, 202	
Process Description: Sheet steel goes Thru A gage	reduction by
compession between Two rolls. An oil spray is	used To lubricaTE
The surface and A mist Eliminator is used To	control the
Emissions	
	·

Company Name: Nucor	Date(s) ofTest: 3-31-98
Test Summary/Comments: Run I did not	
Process problems, Row 1 7130 To	
Process or TESTing problems during	g. This run Each coil went
Thru 5 passes To get To The	cequied gauge. All lank checks
were good A DGM Audit was goe	of M202 was being done w/ M5
TO determine PA/PAIO EMISSIONS.	RUN 2 STATES AT 9:40 and
finished AT 10:55 Am. The process wi	ENT down AT 10:00 pm and did
NOT START back up until 10:15 due	TO A broken MIT LINE. Two couls
WERE 5 pass And one coul was 3	pass during This run. Run
3 STATED AT 11:25 Am. I left	The SITE AFTER OUN 3 STATES
AP's for The MIST Eliminators	were recorded during The
EUNS.	
Runt	
KON WT (165) PASSES.	
46/60 5	
44610 5	
44950 5	
Low Z	
44750 5	
46210 5	
44210 3	