Note: This is a reference cited in *AP 42, Compilation of Air Pollutant Emission Factors, Volume I Stationary Point and Area Sources.* AP42 is located on the EPA web site at www.epa.gov/ttn/chief/ap42/

The file name refers to the reference number, the AP42 chapter and section. The file name "ref02\_c01s02.pdf" would mean the reference is from AP42 chapter 1 section 2. The reference may be from a previous version of the section and no longer cited. The primary source should always be checked.

AP32 Section:	12.5.1
Background Chapter	3
Reference:	46
Title:	Summary of stack test results for Nucor Steel (Darlington SC). Testing conducted on July 17, 1990; February 5-6, February 28, July 23, 1991; September 18, October 27, and December 10, 1992; November 2-3, 1994; February 15-16, 1995; February 25-26, 1997; February 23-24, 1999; January 16 and November 13-15, 2001. Received from Anthony Keeler, South Carolina Department of Health and Environmental Control on September 16, 2002.

Permit No. 0820-0001 ID No. CC

Nucor Steel Corporation Ladle Metallurgical Facility
Darlington, S. C.
Test Date: 7-17-90

#### Particulate Emissions

Test No.	Production	Emis	sions	Limit
	tn/hr	gr/dscf	lbs/hr	lbs/hr
1.	60	0.011	2.84	40.35
2.	60	0.007	1.66	40.35
avg.	60	0.009	2.25	40.35

#### Operation Notes

- The average pressure drop across the baghouse was 7" water. The average ladle process weight is 30 to 35 tons. An average of two ladles were processed during each test. A furnace explosion ended testing after two test runs.

#### Compliance Status

Permit No. 0820-0001-CC, II. Special Conditions A. (PM) - - - Compliance

Joe H. Tallon Asset 8-17-90

Jake Frick W. P. Brantley cc: Robert Brown Don Smith, Pee Dee Dist.



#### August 17, 1990

Nucor Steel Corporation P.O. Box 525 Darlington, South Carolina Attention: Mr. W. E. Dauksch

A summary of the results of the recent source tests at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source(s) tested.

Please review this data and if I can be of further assistance in these matters please call.

Very truly yours,

pult. Julh

Joe H. Tallon Division of Engineering Services Bureau of Air Quality Control

Enclosure

cc: Jake Frick
W. P. Brantley
Robert Brown
Don Smith, Pee Dee Dist.

#### Nucor Steel Corp. #2 Meltshop Baghouse Exhaust Darlington, S.C. RESULTS - TESTS OF Feburary 5-6, 1991

PERMIT NO. 0820-0001

#### 'ARTICULATE:

Test	Production Rate	Emiss	ions	Allow. Emissions
#	tons/hr	lbs/hr	gr/dscf	gr/dscf
1	32.8	3.85	0.0012	0.0052
2	36.8	2.93	0.0009	0.0052
3	34.5	4.95	0.0014	0.0052
Avg.	34.7	3.91	0.0012	0.0052

#### TION NOTES:

- . Unit rated at 40 tons per heat.
- ? . The production rate is given as tons/heat.
- . Flows were taken on the inlet to the baghouse.

#### 'ATUS AS TESTED:

Report Received: 09-26-91
Review Completed: 01-21-1992
Reviewer: Roland O. Shaw

: Jake Frick
W. P. Brantley
Robert Brown
Don Smith, Pee Dee Dist,



Commissioner: Michael D. Jarrett

John B. Pate, MD, Chairman Board: William E. Applegate, III, Vice Chairman

John H. Burriss, Secretary

Promoting Health, Protecting the Environment

Toney Graham, Jr., MD Richard E. Jabbour, DDS Henry S. Jordan, MD Robert J. Stripling, Jr.

January 21, 1992

Nucor Steel Corporation P.O. Box 525 Darlington, South Carolina Attention: Mr. W. E. Dauksch

A summary of the results of the recent source tests at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source(s) tested.

Please review this data and if I can be of further assistance in these matters please call.

,truly,yours,

Roland O. Shaw

Division of Engineering Services Bureau of Air Quality Control

Enclosure

cc: Jake Frick W. P. Brantley Robert Brown Don Smith, Pee Dee Dist. Nucor Steel #1 Melt Shop (EAF #1-3, ID #01-03) Particulate Emissions Tests Darlington, S.C. September 18, 1992-

#### PARTICULATE EMISSIONS:

Run	Production	Emissio	ns	Allowable Emissions
_#_	tons/hr	grs/DSCF	lbs/hr	lbs/tan UL
1.	36.7	0.0052	12.77	55.8
2.	36.7	0.0077	18.83	55.8
<u>3.</u>	<u>36.7</u>	0.0020	<u>4.94</u>	<u>55.8</u>
avg	36.7	0.0050	12.18	55.8

#### OPERATION NOTES:

- 1. During each run six of the eighteen modules were sampled (two traverses, each with four points) so that all modules were tested. The test method should be considered a modified EPA method 5.
- 2. The allowable PM emission rate is based on the total of the three EAF listed allowables.
- 3. The baghouse pressure drop readings are not available.
- 4. The lbs/hr numbers are based on the air flows measured from the compartments. When the measured air flow values for the baghouse inlet duct work are used the average lbs/hr number is 5.23.
- 5. Feed material during testing was .60% #2 scrap, 10% turnings. 10% shredded scrap and 20% #1 scrap with bushings.

#### INDICATED STATUS:

BAQC Permit #0820-0001 ID #01-03 (particulates).....compliance

Robert J. Brown, Jr. RAS

cc: Jake Frick, BAQC
 Phil Brantley, BAQC
 Don Smith, Pee Dee District EQC Office



Interim Commissioner: Thomas E. Brown, Jr.

Board: John H. Burriss, Chairman Richard E. Jabbour, DDS, Vice Chairman Robert J. Stripling, Jr. Secretary

Promoting Health, Protecting the Environment

William E. Applegate, III, Toney Graham, Jr., MD Sandra J. Molander John B. Pate, MD

October 9, 1992

Nucor Steel Corporation Darlington, S.C. 29532 Attn: Mr. Walter Postlethwait

RE: Stack Test of the Nucor Steel #1 Melt Shop (EAFs #1-3)

Dear Mr. Postlethwait:

Enclosed please find our summary of the source tests on the above referenced facility. This summary includes the emission rates, operating parameters and compliance status of the unit tested.

Please review this data and contact me at 734-4528 if you have any question in this matter.

Very truly yours,

Robert J. Brown, Jr.

Engineering Services Division Bureau of Air Quality Control

enclosure

cc: Jake Frick, BAQC
 Phil Brantley, BAQC

Don Smith, Pee Dee District EQC Office

1

Nucor Steel Corporation #1 Melt Shop

Darlington, SC 29532 Permit NO. 0820-0001 RESULTS - TESTS OF October 27, 1992 ID NO. 01-03

#### PARTICULATE:

Test #	Production Rate Tons/hr	Emissi gr/dscf	ons All lbs/hr	ow. Emissions lbs/hr
1	41.0	2.8100	6835.82	55.8
2	41.0	.0039	10.07	55.8
3	41.0	.0866	226.09	55.8
Avg.	41.0	. 9668	2357.33	55.8

#### **VISIBLES**:

Test #	1	2	3	Total
No. of 6 Min. Sets.	6	0	0	6
Sets greater than Std.	0	-	_	-
Average Opacity - %	5	-	-	=
Set max/min opacity - %	20/0	-	-	_

#### **OPERATION NOTES:**

- During each run 6 of the modules were tested so that all eighteen were tested.
- 2. The allowable PM emission rate is based on the total of the three EAF listed allowables.
- 3. Feed material during testing was 20% shredded, 30% plate and structural and #1, 15% #2, 15% bushlings, 20% remelt, Scrap as rolled product.
- 4. The baghouse pressure drop readings were available.

#### STATUS AS TESTED:

> Report Received: 12-14-92 Report Reviewed: 12-21-92

Reviewer: Randall K. Tilford

cc: Jake Frick
W. P. Brantley
D. Fleming
Don Smith, Pee Dee District



Commissioner: Michael D. Jarrett

Board: John B. Pate, MD, Chairman

William E. Applegate, III, Vice Chairman

John H. Burriss, Secretary

Promoting Health, Protecting the Environment

Toney Graham, Jr., MD Richard E. Jabbour, DDS Henry S. Jordan, MD Robert J. Stripling, Jr.

December 21, 1992

Nucor Steel Corporation P.O. Box 525 Darlington, South Carolina 29532 Attention: Mr. W. E. Dauksch

A summary of the results of the recent source tests at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source(s) tested.

Please review this data and if I can be of further assistance in these matters please call.

Very truly yours,

Radall De. Tellet

Randall K. Tilford

Division of Engineering Services Bureau of Air Quality Control

Enclosure

cc: Jake Frick

W. P. Brantley

D. Fleming

Don Smith, Pee Dee District

## Nucor Steel #1 Melt Shop Baghouse Exhaust Darlington, S.C. RESULTS - TESTS OF 12-10-92 Permit No. 0820-0001 ID No. 01-03

#### PARTICULATE:

Test #	Production Rate tons/hr	Emissi gr/dscf	ons lb/hr	Allow. Emissions lb/hr
1	39.3	0.0075	12.10	55.80
2	39.3	0.0054	9.01	55.80
3	39.3	0.0019	3.05	55.80
Avg.	39.3	0.0049	8.05	55.80

#### OPERATION NOTES:

- 1. During each run six of the eighteen modules were sampled. This method should be considered a modified EPA method 5.
- 2. The allowable emission rate is based on the total of the three EAF listed allowables.
- 3. No baghouse pressure readings were taken.
- 4. Feed material during testing was Plate and Structural 47%, #2 35%, Bushling 10%, Shredded 5%, and Turnings 3%.

#### STATUS AS TESTED:

Report Received: 1-5-92
Review Completed: 1-6-92

Reviewer: Randall K. Tilford

بالأراضي الريانية وخيرة والانتهام المتعادية

cc: Jake Frick
W. P. Brantley
Robbie Brown
Don Smith, Pee Dee District

Commissioner: Michael D. Jarrett

Board: John B. Pate, MD, Chairman William E. Applegate, Ill, Vice Chairman

John H. Burriss, Secretary

Promoting Health, Protecting the Environment

Toney Graham, Jr., MD Richard E. Jabbour, DDS Henry S. Jordan, MD Robert J. Stripling, Jr.

January 06, 1992

Nucor Steel Corporation P.O. Box 525 Darlington, South Carolina 29532 Attention: Mr. Wally Postlethwait

A summary of the results of the recent source tests at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source(s) tested.

Please review this data and if I can be of further assistance in these matters please call.

Very truly yours,

Randall Q. Ex

Randall K. Tilford

Division of Engineering Services Bureau of Air Quality Control

Enclosure

cc: Jake Frick
W. P. Brantley

Robbie Brown

Don Smith, Pee Dee District

Nucor Steel
Darlington, SC
No. 2 Reheat Furnance
February 28, 1991

0820-0001 CD

#### NOx Test (Method 7E)

Run #	Flow scfm	Concentration ppm	NOx Emi lbs/hr	ssions tons/yr
1	12573	196	17	77
2	12573	235	21	92
3*	12167 *air recir	59 culated	5	23

#### Notes:

- 1. Air recirculating system not operating during runs 1&2--air recirculating system operating during run # 3. Computer oxygen reading 21% when recirculating system is off, and oxygen reading is approx. 14% when recirculation system is on. Typical operation has gases being recirculated.
- 2. No traverse velocity readings from south stack; all traverse velocity readings taken from the north stack.
- 3. Cold billets being run during the test. Furnace capacity 62 billets.
- 4. All runs were erratic--operator records show approx. 1 hour 50 minutes down time during the test period.
- 5. Steel production during the test period was atypical, according to plant personnel.

#### Status as Tested:

Thomas L. Lathan
Report rec'd 4-18-91
Report completed 4-29-91

cc: Jake Frick
W. P. Brantley
Robert J. Brown
Don Smith, Pee Dee Dist.



Commissioner: Michael D. Jarrett

Board; John B. Pate, MD, Chairman

William E. Applegate, III, Vice Chairman

John H. Burriss, Secretary

Promoting Health, Protecting the Environment

Toney Graham, Jr., MD Richard E. Jabbour, DDS Henry S. Jordan, MD Currie B. Spivey, Jr.

April 29, 1991

Nucor Steel Corporation P.O. Box 525 Darlington, South Carolina 29532 Attention: Mr. W. E. Dauksch

A summary of the results of the recent source tests at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source(s) tested.

Please review this data and if I can be of further assistance in these matters please call.

Very truly yours,

Thomas L. Lathan

Division of Engineering Services Bureau of Air Quality Control

Enclosure

cc: Jake Frick

W. P. Brantley Robert J. Brown

Don Smith, Pee Dee Dist.

#### Nucor Steel No.2 Reheat Furnace Darlington, South Carolina RESULTS OF TEST ON July, 23, 1991

Permit No. 0820-0001 I.D. No. CD

#### NOx Emissions:

Test	ERG	NOx Emissions	Stack Plowrate	HOx E	nissions	Allowable N	Ox Emissions
No.	Status	ppm	cuft/min	lbs/hour	tons/year	lbs/hour	tons/year
1	on	47.4	12932.2 <sup>1</sup>	4.3	18.9	13.7	39,9
2	ON	43.1	12932.2 <sup>l</sup>	3.9	17.2	13.7	39.9
3	OFF	394.6	20458.8 <sup>2</sup>	56.8	248.9	13.7	39.9
4	OFF	437.3	20458.8 <sup>2</sup>	62.9	275.9	13.7	39.9

<sup>1</sup>Based on flow from South stack, no flow in North stack during test.
<sup>2</sup>Based on flow from total of North and South stacks.

#### **OPERATION NOTES:**

- 1. Production averaged 40 tons per hour during testing.
- 2. Flows were conducted during middle of each run. With ERG "ON" no flow was seen in the North stack. With ERG "OFF", flow was seen in both the North and South stacks.

#### STATUS AS TESTED:

> Report Recieved: 08-12-91 Review Completed: 08-26-91 Reviewer: Raymond E. Bishop

cc: Jake Frick
W.P. Brantley
Robert J. Brown, Jr.
Don Smith, Pee Dee District



الأدام بالمعالمة ووراسياني والرا

Commissioner: Michael D. Jarrett

Board: John B. Pate, MD, Chairman

William E. Applegate, III, Vice Chairman

John H. Burriss, Secretary

Promoting Health, Protecting the Environment

Toney Graham, Jr., MD Richard E. Jabbour, DDS Henry S. Jordan, MD Robert J. Stripling, Jr.

August 26, 1991

Nucor Steel
P.O. Box 525
Darlington, South Carolina 29532
Attention: Mr. Walter Postlethwit

A summary of the results of the recent NOx test at your No.2 Reheat furnace facility is enclosed.

This summary includes the emission rates, operating parameters, and compliance status of the source.

Your permit will reflect the amount of time your ERG must be on. Any questions concerning the period of time the ERG must be "ON" should be directed to Robert Brown, Jr. (803) 734-4528.

Please review this data and if I can be of further assistance in these matters please call. (803) 935-6313

Very truly yours,

Raymond E. Bishop
Division of Engineering Services

Bureau of Air Quality Control

Enclosure

cc: Jake Frick

W.P. Brantley

Robert J. Brown, Jr.

Don Smith, Pee Dee District

### Nucor Steel Corp. Melt Shop #3 Baghouse Darlington, South Carolina

RESULTS - TESTS OF November 2 - 3, 1994

PERMIT NO. 0820-0001 ID NO. 0

#### PARTICULATE:

Test #	Production Rate tons/hr	Emission gr/dscf	s lbs/hr	Allow. Emissions lbs/hr
1	90.7	0.00085	3.31	22.29
2	99.5	0.00171	6.72	22.29
3	99.5	0.00114	4.00	22.29
Avg.	96.6	0.00123	4.68	22.29

#### **VISIBLES:**

Test #	1	2	3	TOTAL
No. of 6 Min. Sets	5	5	5	<b>15</b>
Sets greater than stand.	0 -	0	0	0
Average opacity - %	0	0	0	0 (Avg.)
Set max/min opacity - %	0/0	0/0	0/0	_

#### **OPERATION NOTES:**

- 1 . Hot gas fans prone to failure during testing.
- 2 . Melt Shop canopy does not adequately capture EAF emissions.
- 3 . Roof vent opacity limits exceeded during testing.

#### STATUS AS TESTED:

Report Received: 12-21-94
Review Completed: 01-06-1995
Reviewer: Patrick Turner

cc: Jake Frick
W.P. Brantley
Robert J. Brown
Don Smith, Pee Dee Dist.
Main File



Commissioner: Douglas E. Bryant

Board: Richard E. Jabbour, DDS, Chairman Robert J. Stripling, Jr., Vice Chairman Sandra J. Molander, Secretary

Promoting Health, Protecting the Environment

William E. Applegate, III, John H. Burriss Tony Graham, Jr., MD John B. Pate, MD

January 03, 1995

Nucor Steel Corporation P.O. Box 525 Darlington, South Carolina 29532 Attention: Mr. Chad Prior

A summary of the results of the recent source tests at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source(s) tested.

Please review this data and if I can be of further assistance in these matters please call.

Sincerely,

Patrick Turner
Division of Engineering Services
Bureau of Air Quality

Enclosure

cc: Jake Frick
W.P. Brantley
Robert J. Brown
Don Smith, Pee Dee Dist.
Main File

## Nucor Steel Corp. Melt Shop #3 Baghouse Darlington, South Carolina

#### Results - Tests of February 15 and 16, 1995 Permit No. 0820-0001 CV

<u>Method_5D</u> Test	Production	Capacity	Emi	ssions	Allowable
#	tons/hr	%	lbs/hr	gr/dscf	gr/dscf
1	109.2	99.2	1.046	0.00031	0.0052
2	95.5	86.8	1.514	0.00043	0.0052
3	102.8	93.5	0.740	0.00023	0.0052
Avg.	102.5	93.2	1.100	0.00032	0.0052

Capacity is base on 110 lbs/hr.

Ľп	nis:	ion	S
_			

Test	CO	Allowable	NOx	Allowable
#	Lbs/hr	Lbs/hr	Lbs/hr	Lbs/hr
1	162.0		7.2	
2	210.0		14.4	
3	249.5		19.1	
Avg.	207.2	600.0	13.6	22.0

#### Visibles (Method 9)

Test #	ON	E	TW	0	THR	EE
Emission pt.	В	M	В	M	В	M
No. of 6 Min. Sets	10	10	7	**	7	7
Sets greater than std.	0	0	0	**	0	0
Average Opacity %	0	0	0	**	0	0
Set Max/min %	0/0	0/0	0/0	**	0/0	1/0

B=Baghouse M=Melt shop

#### Status as Tested:

Permit # 0820-0001(PM, NOx,CO)	Compliance.
Permit # 0820-0001( Visibles)	Compliance.

Report Received: 3-17-95 Review Complete: 10-11-95

Reviewer: Robert W. Mitchum Pu.,

cc: Jake Frick
Jerry Chalmers
Ken Dulaney
Don Smith, Pee Dee District
Main File



Commissioner: Douglas E. Bryant

Board: John H. Burriss, Chairman William M. Hull, Jr., MD, Vice Chairman Roger Leaks, Jr., Secretary

Promoting Health, Protecting the Environment

Richard E. Jabbour, DDS Cyndi C. Mosteller Brian K. Smith Rodney L. Grandy

October 13, 1995

Nucor Steel Corporation P.O. Box 525 Darlington, South Carolina 29532 Attention: Mr. Chad Prior

A summary of the results of the recent source tests at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source(s) tested.

Please review this data and if I can be of further assistance in these matters please call.

Sincerely,

Robert W. Mitchum

Robert W. rutekus

**Division of Engineering Services** 

**Bureau of Air Quality** 

**Enclosure** 

cc: Jake Frick
Jerry Chalmers
Kenneth A. Dulaney
Don Smith, Pee Dee EQC District
Main File

#### Nucor Steel Corporation

Darlington, South Carolina #3 Melt Shop Baghouse

Results - Tests of February 25 and 26, 1997

Permit No. 0820-0001

Id. No

CV

#### Particulate (Method 5D)

 $\{\phi_{ij}\}$ 

Test	Production	Capacity 1	Emissions		Allov	vable
#	Tons/hr	%	lbs/hr	gr/dscf	lbs/hr	gr/dscf
1	102.3	93.0	10.8	0.0031	22.0	0.0052
2	109.5	99.5	17.4	0.0049	22.0	0.0052
3 -	109.5	99.5	25.6	0.0076	22.0	0.0052
Avg.	107.1	97.4	17.9	0.0052	22.0	0.0052

<sup>1</sup> Based on rated output of 110 tons/hr

Visibles (Method 9)	<del></del>			
Test #	1	2	. 3	Total
No. of 6 Min. Sets	10	5	na	15
Sets greater than std.	0	0	па	0
Average Opacity - %	0	0	na	0
Set Max/min opacity - %	0/0	0/0	na	0/0

#### **Operational Notes**

- 1. Control device is a positive pressure baghouse with 14 individual compartments.
- 2. Allowable for opacity from baghouse is 3%.
- 3. Volumetric flowrate averaged 470,732 ACFM
- 4. Pressure drop at inlet of baghouse averaged 5.7 and ranged from 4.8 to 6.5 inches of H2O.

#### Status as Tested:

> Report Received: 3-26-97 Review Complete: 4-08-97

Reviewer: Robert W. Mitchum

cc: Jake Frick

Jerry Chalmers Beth Boland

Larry Ragsdale

Don Smith, Pee Dee EQC District

Main File



2000 Bull Street Columbia, SC 29201-1708

COMMISSIONER: Douglas E. Bryant

May 26, 1999

BOARD: John H. Burriss Chairman

Vice Chairman

William M. Hull, Jr., MD Nucor Steel Corp.

Attn: Mr. Chad Prior

Roger Leaks, Jr. Secretary

P O Box 525

Darlington, SC 29540

Mark B. Kent

Cyndi C. Mosteller

Brian K. Smith

Rodney L. Grandy

A summary of the results of the recent source tests on Nucor Steel's # 3 Melt Shop Baghouse are enclosed.

This summary includes the emission rates and the operating parameters of the source tested.

Be aware that the Subpart Aaa requires that 160 DSCF be measured and that this should be met on all subsequent tests.

Review this data and if I can be of any assistance do not hesitate to call me at (803) 898-4078.

Sincerely,

Michael G. Verzwyvelt Air Compliance Management Division Bureau of Air Quality

Enclosure

cc: Jerry Chalmers Annie Richardson Joe Eller Don Smith, Pee Dee District Dan McCombs, ATC

Mainfile

# Nucor Steel Corporation Darlington, South Carolina # 3 Melt Shop Baghouse Results-Tests of February 23-24, 1999 Permit No. 0820-0001 Id. No. CP

#### Particulate Method 5D

Test	Production	Capacity1	Emissi	ons	Allo	wable
. #	Tons/hr	%	lbs/hr	gr/dscf	lbs/hr	gr/dscf
1	109.2	99.3	1.083	0.0003	22.0	0.0052
2	124.9	113.5	1.24	0.0004	22.0	0.0052
3	136.7	124.3	1.711	0.0005	22.0	0.0052
Avg.	123.6	112.4	1.345	0.0004	22.0	0.0052

<sup>1.</sup> Based on a rated capacity of 110 tons/hr.

Visibles (Method 9)				
Test #	1	2	3	
No. of 6 Min. Sets	10	20	N/A	
Sets Greater than Std.	0	0	N/A	
Average Opacity-%	0	0	N/A	
Set Max/min Opacity-%	0/0	0/0	N/A	

#### Operational Notes

- 1. Control device is a positive pressure baghouse with 14 compartments.
- 2. Volumetric flow rate averaged 442665 ACFM.
- 3. Pressure drop at the inlet of the baghouse avg. 4.9 and ranged from 3.3 to 6.7 inches WC.
- 4. Visibles were observed by plant personnel.

#### Status as Tested

40 CFR 60, Subpart AAa. 60.272a.(a).(1)Co	mpliance
40 CFR 60, Subpart AAa. 60.272a.(a).(2)	mpliance

Report Received: April 7, 1999 Report Reviewed: May 26, 1999 Reviewer: Michael Verzwyvelt

cc: Jerry Chalmers
Annie Richardson
Joe Eller
Don Smith, Pee Dee District
Mainfile

# Nucor Steel Corporation Darlington South Carolina # 3 Melt Shop Baghouse Exhaust Results - Tests of January 16, 2001 Permit # 0820-0001

ID: CP

#### Particulate: (Method 5D)

Run	Production	Capacity	Emi	ssions	Allo	wable
#	tons/hr	%	lbs/hr	gr/dscf	lbs/hr	gr/dscf
1						
2	110	100.0	10.37	0.003	22.29	.0058
3	104	95.0	11.23	0.003	22.29	.0058
Avg.	107	97.5	10.80	0.003	22.29	.0058

Rated capacity 110 tons/hr

Visibles (Method 9)		·	
Test #	1	2	3
No. of 6 Min. Sets	· <b>x</b>	10	10
Sets greater than std.	x	0	0
Average Opacity - %	X	0	. 0
Set Max/min opacity - %	X	'0/0	0/0

#### Operational Notes:

- 1. Run # 1 was excluded, results were atypical.
- 2. Volumetric flow rate averaged 500340 ACFM.
- 3. Control device is a positive pressure baghouse with 14 compartments.
- 4. Pressure drop at the inlet of the baghouse avg. 8.9 and ranged from 8.8 to 9.1 inches WC.
- 5. Visibles were observed by plant personnel.

#### Status as tested

cc: Jake Frick

Annie Richardson

Joe Eller

Don Smith, Pee Dee District

Main File

Received: February 20, 2001 Report Completed: March 08, 2001

Reviewer: Roderick A. Moore



00 Bull Street Columbia, SC 29201-1708

March 08, 2001

COMMISSIONER: Douglas E. Bryant

BOARD: Bradford W. Wyche Chairman

William M. Hull, Jr., MD Vice Chairman

Mark B. Kent Secretary

Howard L. Brilliant, MD

Brian K. Smith

Rodney L. Grandy

Larry R. Chewning, Jr., DMD

Nucor Steel Corporation

P.O. Box 525

Darlington South Carolina 29540

Attn: Matt Kanes

A summary of the results of the recent test at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source (s) tested.

Although this facility is operating within allowable particulate emission limits, we have noted a significant increase in the actual particulate emissions from 1.345 lbs/hr in 1999 to 10.8 lbs/hr in 2001. The average volumetric flow rate (ACFM) in 1999 was 442665 compared to 500340 in 2001. Particulate emission increases of this magnitude may warrant maintenance and/or operational investigative work.

Please review this data and if I can be of further assistance in these matters do not hesitate to call me at (803) 898-3276 or e-mail me at moorera@columb31.dhec.state.sc.us.

Sincerely,

Roderick A. Moore

Lobust a. Moore

Air Compliance Management Division

Bureau of Air Quality

Enclosure

CC: Jake Frick

Annie Richardson

Joe Eller

Don Smith, Pee Dee District

Main File

## Nucor Steel Corporation Darlington South Carolina # 3 Melt Shop Baghouse Exhaust Results - Tests of November 13-15, 2001

Permit # TV-0820-0001 ID: 01

#### Particulate: (Method 5D)

Run	Production	Capacity	Emissions	Allowable
#	tons/hr	%	gr/dscf	gr/dscf
1	109	72.0	0.0006	0.0052
2	121	81.0	0.0005	0.0052
3	132	88.0	0.0004	0.0052
Avg.	120	80.3	0.0005	0.0052

Rated capacity 150 tons/hr

Visibles (Method 9)			
Test #	<u> </u>	2	3
No. of 6 Min. Sets	10	10	10
Sets greater than std.	0	0	0
Average Opacity - %	0	0	0
Set Max/min opacity - %	0/0	0/0	0/0

#### Operational Notes:

- 1. Volumetric flow rate averaged 500340 ACFM.
- 2. Control device is a positive pressure baghouse with 14 compartments.
- 3. Pressure drop at the inlet of the baghouse avg. 7.2 and ranged from 7.0 to 7.7 inches WC.
- 4. Visibles were observed by plant personnel.

#### Status as tested

ce: Jake Frick
Annie Richardson
Joe Eller
Don Smith, Pee Dee District
Carol Boney
Main File

Received: December 20, 2001
Report Completed: January 18, 2002
Reviewer: Roderick A. Moore



0 Bull Street Columbia, SC 29201-1708

COMMISSIONER: Douglas E. Bryant

BOARD: Bradford W. Wyche Chairman

January 18, 2002

William M. Hull, Jr., MD Vice Chairman

Mark B. Kent Secretary

Howard L. Brilliant, MD

Brian K. Smith

Louisiana W. Wright

Larry R. Chewning, Jr., DMD

**Nucor Steel Corporation** 

P.O. Box 525

Darlington, South Carolina 29540

Attention: Matt Kanes

A summary of the results of the recent source tests at the indicated facility is enclosed.

This summary includes the emission rates, operating parameters and compliance status of the source(s) tested.

Please review this data and if I can be of further assistance in these matters please call.

Sincerely,

Roderick A. Moore

leik a. Moore

Air Compliance Management Division

Bureau of Air Quality

**Enclosure** 

cc: Jake Frick

Annie Richardson

Joe Eller

Carol Boney

Don Smith, Pee Dee District

Main File

NOTE: Draft determinations are marked with a " • " beside the RBLC ID.

Report Date: 09/17/2002

Control Technology Determinations (Freeform)

#### FACILITY INFORMATION: NUCOR STEEL-DARLINGTON COUNTY

RBLC Id:

\*SC-0075

\*Company Name:

NUCOR STEEL CORPORATION

\*Plant Name:

NUCOR STEEL- DARLINGTON COUNTY

Plant County:

DARLINGTON

Plant Contact Name: Plant Contact Address:

JOSEPH A. RUTKOWSKI **POST OFFICE BOX 525** 

Plant Contact City

DARLINGTON

Plant Contact State:

SC

Plant Contact Zip Code: 29532 Plant Contact Phone:

Plant Contact Email:

EPA Region:

4

Agency Code:

SC001

Agency Name:

SOUTH CAROLINA DEPT OF HEALTH & ENV CTRL

Agency Contact:

LARRY RAGSDALE

Agency Phone:

(803) 734-4750

Agency Email:

\*Permit/File No.:

0820-0001-CW

\*SIC:

3312

NAICS: Airs Id: EPA Id: UTM Zone: X Coordinate: Y coordinate:

Application Received

05/08/1996 ACT

Date:

Permit Issuance Date:

01/08/1998 ACT

Start Up Date:

Compliance Validation

Date:

Entry Date:

05/15/2002

Last Update:

09/12/2002 M

New or Modified:

Public Hearing: Fuel:

YES

**Emission Sources:** 

NATURAL GAS, PROPANE BACK-UP FUEL

MELT SHOP #3, ELECTRIC ARC FURNACE WITH A SHELL

CAPACITY OF 160 TONS, LADLE METALLURGICAL FURNACE. FOUR STRAND CONTINUOUS CASTING MACHINE, REHEAT FURNACE #1 AND #2, 9 PIECES OF ANCILLARY EQUIPMENT;

LADLE PRE-HEATERS #1-3, LADLE DRY OUT, VERTICAL HOLDING STATION, TUNDISH PRE-HEATERS #1-2, TUNDISH DRY OUTS #1-2.

Abatement:

MAIN BAGHOUSE, CASTER CANOPY, SIDE DRAFT HOOD, ROOF MONITORS, DIRECT SHELL EVACUATION SYSTEM, LOW NOX

BURNERS

Narrative:

STEEL MILL

Notes:

PERMIT FOR INCREASE PRODUCTION FROM 110 BILLET TONS OF STEEL PER HOUR (BTPH) TO 150 BTPH. SUBJECT TO CONDITIONS

AND EMISSIONS LIMITATIONS

#### PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process:

ELECTRIC ARC FURNACE (EAF)

\*Process Type:

81,006

\*SCC Code:

3-04-007-01

Primary Fuel:

DC POWERED

Throughput: Throughput Unit:

160 **TONS** 

Compliance Verified:

No

Stack Testing: Inspections:

No No

Calculations: Other Testing: No No

Other Testing Method:

Process/Compliance

Notes:

EMISSIONS FROM EAF ARE CAPTURED BY THE DIRECT SHELL EVACUATION SYSTEM (DSE) VIA THE CONSTEEL PROCESS AND AN OVERHEAD CANOPY. EACH OF THESE ARE DUCTED TO THE MAIN BAGHOUSE. CONSTEEL/WATER COOLED DUCT PROCESS CONSISTING OF SHAKER/CONVEYOR SYSTEM CONNECTED TO EAF THAT FEEDS SCRAP METAL TO THE FURNACE. PROCESS IS DUCTED TO THE MAIN BAGHOUSE. CONTINUOUS MONITORING REQUIRED FOR OPACITY ONCE PER DAY DURING REFINING AND MELTING PERIOD. MUST CHECK AND RECORD FAN MOTOR AMPS AND DAMPER POSITION OR INSTALL, CALIBRATE AND MAINTAIN A MONITORING DEVICE FOR VOLUMETRIC FLOW THROUGH SEPARATELY DUCTED HOODS ONCE PER SHIFT. MONTHLY OPERATIONAL STATUS INSPECTIONS OF EQUIPMENT IMPORTANT

TO PERFORMANCE OF THE TOTAL CAPTURE SYSTEM. MONITOR 4TH HOLE DUCT DIFFERENTIAL PRESSURE OR EAF ONCE PER SHIFT. SHALL NOT BE OPERATED WITH A DEFECTIVE DELTA SECTION OR OTHER DISREPAIR THAT WILL SIGNIFICANTLY REDUCE THE EFFICIENCY OF THE DIRECT EVACUATION

THROUGHT THE SCRAP PREHEATING SYSTEM.

#### POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - ELECTRIC ARC FURNACE (EAF)

\*Pollutant

VE

\*CAS Number:

VE

\*Control Method Code: A

\*Control Method

DIRECT SHELL EVACUATION SYSTEM, OVERHEAD CANOPY,

Description:

DUCTED TO MAIN BAGHOUSE.

#### Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1:

Emission Limit 1 Unit: %

**Emission Limit 1** 

Condition:

\*Basis: BACT-PSD

\*Percent Efficiency:

Emission Limit 2:

Emission Limit 2 Unit: % OPACITY

**Emission Limit 2** 

Condition:

Standard Emission:

Standard Emission Unit:

Standard Emission

Condition:

\*Emission Type:

**CAP Cost of Control** 

\$0

6

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

#### PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process:

LADLE METALLURGICAL FURNACE (LMF)

\*Process Type:

81.006

\*SCC Code:

3-04-007-99

Primary Fuel:

**AC POWERED** 

Throughput:

Throughput Unit:

Compliance Verified:

No

Stack Testing:

No

Inspections:

No

Calculations:

No

Other Testing:

No

Other Testing Method:

Process/Compliance

EMISSIONS ARE CAPTURED BY A SIDE DRAFT HOOD AND

Notes:

DUCTED TO THE MAIN BAGHOUSE. ALLOYS ARE ADDED TO THE MOLTEN STEEL AT THE LMF AND MIXING TAKES PLACE VIA

INERT GAS STIRRING. SUBJECT TO PSD.

POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - LADLE METALLURGICAL FURNACE (LMF)

\*Pollutant

VE.

\*CAS Number:

VE.

\*Control Method Code:

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

20

Emission Limit 1 Unit:

%

**Emission Limit 1** 

Condition:

**BACT-PSD** 

\*Basis: \*Percent Efficiency:

**Emission Limit 2:** 

**Emission Limit 2 Unit:** 

**Emission Limit 2** 

Condition:

Standard Emission:

20

Standard Emission Unit: % OPACITY

Standard Emission

Condition:

\*Emission Type:

P

CAP Cost of Control

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates: Pollutant Notes:

#### PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process:

FOUR STRAND CONTINUOUS CASTING MACHINE

\*Process Type:

81.006

\*SCC Code:

3-03-009-22

Primary Fuel:

Throughput:

150

Throughput Unit:

BTPH STEEL -No

Compliance Verified:

No

Stack Testing:

Inspections:

No No

Calculations: Other Testing:

No

Other Testing Method:

Process/Compliance

Notes:

EMISSIONS FROM THE CASTER ARE CAPTURED BY A 30' BY 30' CANOPY WITH AIR CAPACITY OF 60,000 ACFM, AND DUCTED TO

THE MAIN BAGHOUSE. SUBJECT TO PSD.

### POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - FOUR STRAND CONTINUOUS CASTING MACHINE

\*Pollutant

VE

\*CAS Number:

VE

\*Control Method Code:

e: A

\*Control Method

CANOPY DUCTED TO BAGHOUSE

Description:

Number of Options

Considered:

Rank of Option Selected:
Emission Limit 1: 20
Emission Limit 1 Unit: %

**Emission Limit 1** 

Condition:

\*Basis: BACT-PSD

\*Percent Efficiency: Emission Limit 2: Emission Limit 2 Unit: Emission Limit 2

Condition:

Standard Emission: 20

Standard Emission Unit: % OPACITY

Standard Emission

Condition:

\*Emission Type: P
CAP Cost of Control \$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

#### PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process: REHEAT FURNACE #1

\*Process Type: 12.310

\*SCC Code: 3-03-009-33 Primary Fuel: NATURAL GAS

Throughput: 140000000

Throughput Unit: BTU/H HEAT INPUT CAP

Compliance Verified: No Stack Testing: No Inspections: No Calculations: No

Other Testing:

No

Other Testing Method:

Process/Compliance

Notes:

MAIN FUEL IS NATURAL GAS, PROPANE AS A BACK-UP. UTILIZES' LOW NOX BURNERS. NATURAL GAS AND PROPANE USAGE IS RESTRICTED TO AN EQUIVALENT OF 1150 X 10^6 SCF PER YEAR AT ESTABLISHED BTU CONTENTS OF 1000 BTU/CF AND 90500

BTU/GALLON RESPECTIVELY. SUBJECT TO PSD.

POLLUTANT INFORMATION: NUCOR STEEL-DARLINGTON COUNTY - REHEAT FURNACE #1

\*Pollutant

CO

\*CAS Number:

630-08-0

\*Control Method Code:

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

27.6

Emission Limit 1 Unit:

LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

Emission Limit 2 Unit:

**Emission Limit 2** 

Condition:

Standard Emission:

.197

120.9

T/YR

Standard Emission Unit: LB/MMBTU

Standard Emission

Condition:

\*Emission Type:

**CAP Cost of Control** 

P \$0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

NOX

\*CAS Number:

10102

\*Control Method Code:

Р

\*Control Method

Description:

LOW NOX BURNERS AND RECUPERATORS, FUEL RESTRICTIONS.

Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1: Emission Limit 1 Unit:

13.7 LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

Emission Limit 2: Emission Limit 2 Unit: 60 T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.098

Standard Emission Unit: LB/MMBTU

Standard Emission

Condition:

\*Emission Type:

P

CAP Cost of Control

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant OPACITY

\*CAS Number:

VE

\*Control Method Code:

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1: 20

Emission Limit 1 Unit: %

**Emission Limit 1** 

Condition:

\*Basis: BACT-PSD

\*Percent Efficiency:

**Emission Limit 2:** 

Emission Limit 2 Unit:

Emission Limit 2

Condition:

Standard Emission:

20

Standard Emission Unit: % OPACITY

Standard Emission

Condition:

\*Emission Type:

P

CAP Cost of Control

Equipment:

\$0

**Annualized Cost:** 

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates: Pollutant Notes:

\*Pollutant

SO<sub>2</sub>

\*CAS Number:

7446-09-5

\*Control Method Code: A

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

.12

Emission Limit 1 Unit:

LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

.53

**Emission Limit 2 Unit:** 

T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.0009

Standard Emission Unit: LB/MMBTU

Standard Emission

Condition:

\*Emission Type:

P

CAP Cost of Control

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

PM

\*CAS Number:

PM

\*Control Method Code: A

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

2

**Emission Limit 1 Unit:** 

LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

8.8

**Emission Limit 2 Unit:** 

T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.01

Standard Emission Unit: LB/MMBTU

Standard Emission

Condition:

\*Emission Type:

P

**CAP Cost of Control** 

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

#### PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process:

**MELTSHOP #3** 

\*Process Type:

81.006

\*SCC Code:

3-04-007-99

Primary Fuel:

NATURAL GAS

Throughput:

150

Throughput Unit:

BILLET TONS STEEL/H

Compliance Verified: Stack Testing:

No No

No

Inspections:

No

Calculations: Other Testing:

No

Other Testing Method:

Process/Compliance

Notes:

MAX TOTAL YEARLY OUTPUT OF 1,314,000 BILLET TONS OF STEEL USING ROLLING AVG METHOD. SOURCE TESTS FOR PM, SO2, NOX, CO, VOCS, LEAD AND OPACITY SHALL BE CONDUCTED WITHIN 90 DAYS OF ACHIEVING THE FOLLOWING MONTHLY AVG RATES: 120 BTPH, 130 BTPH, 140 BTPH AND 150 BTPH. MAIN BAGHOUSE IS A POSITIVE PRESSURE, REVERSE AIR CLEANING TYPE WITH 3 MAIN FANS, 2 REVERSE AIR FANS. MAIN BAGHOUSE CONTROLS THE ELECTRIC ARC FURNACE DIRECT SHELL EVACUATION SYSTEM, LADLE METALLURGICAL FURNACE, AND THE CASTER CANOPY: NO MORE THAN 3 MAIN BAGHOUSE COMPARTMENTS WILL BE OFF LINE WITHOUT CURTAILMENT OF MELT SHOP OPERATIONS. TWO FANS WILL BE ON-LINE DURING NORMAL

PLANT OPERATIONS. DUST COLLECTED WILL BE KEPT ENCLOSED UNTIL REMOVED FROM PLANT SITE, FUGITIVE EMISSIONS FROM SLAG HANDLING SHALL BE MINIMIZED BY IMPLEMENTING PROPER HANDLING PROCEDURES.

#### POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - MELTSHOP #3

\*Pollutant

CO

\*CAS Number:

630-08-0

\*Control Method Code: A

\*Control Method Description:

POSITIVE PRESSURE, REVERSE AIR CLEANING BAGHOUSE WITH 3 FANS, 2 REVERSE AIR FANS, DSE SYSTEM, CASTER CANOPY, RAFT

HOOD ON LMF, AND ROOF MONITORS.

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 2.76

Emission Limit 1 Unit: LB/T OF STEEL

Emission Limit 1

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

414

Emission Limit 2 Unit:

LB/H, 1813.32 T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

Standard Emission Unit: PPM @ 15% O2

Standard Emission

Condition:

\*Emission Type:

F

CAP Cost of Control

0 2

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

NOX

\*CAS Number:

10102

\*Control Method Code: A

\*Control Method

POSITIVE PRESSURE, REVERSE AIR CLEANING BAGHOUSE WITH 3 FANS, 2 REVERSE AIR FANS, DSE SYSTEM, SIDE DRAFT HOOD ON

LMF, CASTER CANOPY, AND ROOF MONITORS.

Number of Options

Considered:

Description:

Rank of Option Selected:

Emission Limit 1:

.35

Emission Limit 1 Unit:

LB/T STEEL

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

52.5

Emission Limit 2 Unit:

LB/H, 229.95 T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

Standard Emission Unit: PPM @ 15% O2

Standard Emission

Condition:

\*Emission Type:

F

**CAP Cost of Control** 

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

PB

\*CAS Number:

7439-92-1

\*Control Method Code:

\*Control Method

POSITIVE PRESSURE, REVERSE AIR CLEANING BAGHOUSE WITH 3

FANS, 2 REVERSE AIR FANS, DSE, SIDE DRAFT HOOD ON LMF,

ROOF MONITORS.

Number of Options

Considered:

Description:

Rank of Option Selected:

**Emission Limit 1:** 

1.9

Emission Limit 1 Unit:

LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** Emission Limit 2 Unit:

**Emission Limit 2** 

Condition:

Standard Emission:

Standard Emission Unit:

Standard Emission

Condition:

\*Emission Type:

F

CAP Cost of Control

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates: Pollutant Notes:

\*Pollutant

SO2

\*CAS Number:

7446-09-5

\*Control Method Code: A

\*Control Method

POSITIVE PRESSURE REVERSE AIR CLEANING BAGHOUSE WITH 3 MAIN FANS AND 2 REVERSE AIR FANS. DSE SYSTEM, SIDE DRAFT

HOOD ON LMF, CASTER CANOPY, AND ROOF MONITORS.

Number of Options

Considered:

Description:

Rank of Option Selected: **Emission Limit 1:** 

Emission Limit 1 Unit:

LB/T OF STEEL

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

30

Emission Limit 2 Unit:

LB/H & 131.40 T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

Standard Emission Unit: PPM @ 15% O2

Standard Emission

Condition:

\*Emission Type:

F

**CAP** Cost of Control

\$0

Equipment:

**Annualized Cost:** 

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

VE.

\*CAS Number:

**VE** 

\*Control Method

\*Control Method Code: A

Description:

POSITIVE PRESSURE, REVERSE AIR CLEANING MAIN BAGHOUSE WITH 3 FANS AND 2 REVERSE AIR FANS, CASTER CANOPY, DSE,

SIDE DRAFT HOOD OF LMF AND ROOF MONITORS.

Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1:

3

Emission Limit 1 Unit:

%

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

Emission Limit 2 Unit:

% FROM EAF OPERATION

**Emission Limit 2** 

Condition:

Standard Emission:

Standard Emission Unit: % OPACITY

Standard Emission

Condition:

\*Emission Type:

F

CAP Cost of Control

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

VOC

\*CAS Number:

VOC

\*Control Method Code:

Α

\*Control Method

POSITIVE PRESSURE, REVERSE AIR CLEANING MAIN BAGHOUSE, WITH 3 FANS, 2 REVERSE AIR FANS, DSE SYSTEM, SIDE DRAFT

Description:

HOOD ON LMF, DSE, AND ROOF MONITORS.

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

35

Emission Limit 1 Unit:

LB/T STEEL

**Emission Limit 1** 

Condition:

\*Basis:

BACT-PSD

\*Percent Efficiency:

Emission Limit 2:

52.5

Emission Limit 2 Unit:

LB/H, 229.95 T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.35

Standard Emission Unit: LB/TON OF STEEL

Standard Emission

Condition:

\*Emission Type:

**CAP Cost of Control** 

F

Equipment:

\$ 0

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates: Pollutant Notes:

\*Pollutant

PM

\*CAS Number:

PM

\*Control Method Code:

Α

\*Control Method

POSITIVE PRESSURE REVERSE AIR CLEANING BAGHOUSE- 3 MAIN

Description:

FANS. 2 REVERSE AIR FANS. UNCAPTURED FUGITIVES VENTED

THRU ROOF MONITORS

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

.0052

Emission Limit 1 Unit:

GR/DSCF

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

51

Emission Limit 2 Unit:

LB/H, 223.4 T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.0052

Standard Emission Unit: GR/DSCF

Standard Emission

Condition:

\*Emission Type:

F

**CAP Cost of Control** 

\$0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

#### PROCESS INFORMATION: NUCOR STEEL-DARLINGTON COUNTY

\*Process:

REHEAT FURNACE #2

\*Process Type:

12.310

\*SCC Code:

3-03-009-33

Primary Fuel:

NATURAL GAS

Throughput:

140000000

Throughput Unit:

BTU/H HEAT INPT CAP

Compliance Verified:

No

Stack Testing:

No

Inspections:

No No

Calculations: Other Testing:

No

Other Testing Method:

Process/Compliance

Notes:

NATURAL GAS IS MAIN FUEL, PROPANE AS BACK UP. UTILIZES LOW NOX BURNERS AND EXTERNAL FLUE GAS RECIRCULATION.

NATURAL GAS AND PROPANE USAGE IS RESTRICTED TO AN

EQUIVALENT OF 1095 X 10^6 SCF PER YEAR AS ESTABLISHED BTU CONTENTS OF 1000 BTU/CF AND 90500 BTU/GAL RESPECTIVELY.

SUBJECT TO PSD.

## POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - REHEAT FURNACE #2

\*Pollutant

CO

\*CAS Number:

630-08-0

\*Control Method Code:

\*Control Method

Description: Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

26.2

Emission Limit 1 Unit:

LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

114.8

Emission Limit 2 Unit:

T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.187

Standard Emission Unit: LB/MMBTU

Standard Emission

Condition:

\*Emission Type:

P

CAP Cost of Control

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

NOX

\*CAS Number:

10102

\*Control Method Code:

\*Control Method

LOW NOX BURNERS AND EXTERNAL FLUE GAS RECIRCULATION,

Description:

FUEL RESTRICTIONS.

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

17.5

**Emission Limit 1 Unit:** 

LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

76.6

Emission Limit 2 Unit:

T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.125

Standard Emission Unit: LB/MMBTU

Standard Emission

Condition:

\*Emission Type:

P

**CAP Cost of Control** 

\$0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

**OPACITY** 

\*CAS Number:

**VE** 

\*Control Method Code:

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

20

Emission Limit 1 Unit:

%

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

**Emission Limit 2 Unit:** 

**Emission Limit 2** 

Condition:

Standard Emission:

20

Standard Emission Unit: % OPACITY

Standard Emission

Condition:

\*Emission Type: P
CAP Cost of Control

Control \$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

SO2

\*CAS Number:

7446-09-5

\*Control Method Code: A

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1:

.08

Emission Limit 1 Unit:

LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

Emission Limit 2: .4

Emission Limit 2 Unit: T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.0006

Standard Emission Unit: LB/MMBTU

Standard Emission

Condition:

\*Emission Type:

P

**CAP Cost of Control** 

\$ 0

Equipment:

**Annualized Cost:** 

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

PM

\*CAS Number:

PM

\*Control Method Code:

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1:

1.9

Emission Limit 1 Unit: LB/H

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

8.3

Emission Limit 2 Unit:

T/YR

**Emission Limit 2** 

Condition:

Standard Emission:

.01

Standard Emission Unit: LB/MMBTU

Standard Emission

Condition:

\*Emission Type:

P

CAP Cost of Control

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

## PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process:

ANCILLARY EQUIPMENT

\*Process Type:

81.006

\*SCC Code:

3-03-009-98

Primary Fuel:

NATURAL GAS

Throughput: Throughput Unit: 11000000

Compliance Verified:

BTU/H No

Stack Testing:

No

Inspections:

No

Calculations:

No

Other Testing:

No

Other Testing Method:

Process/Compliance

Notes:

ANCILLARY EQUIPMENT INCLUDES 9 PIECES: LADLE PRE-

HEATERS #1, #2, & #3; LADLE DRY OUT, VERTICAL HOLDING STATION, TUNDISH PRE-HEATERS #1 & #2, AND TUNDISH DRY OUTS #1 & 32. EACH PIECE HAS RATED HEAT INPUT CAPACITY OF 11.0 X 10^6 BTU/H. ALL ANCILLARY EQUIPMENT USES NATURAL GAS AS MAIN FUEL AND PROPANE AS BACK UP AND LOW NOX BURNERS. NATURAL GAS AND PROPANE USAGE FOR ALL OF THE 9 PIECES OF EQUIPMENT IS RESTRICTED TO AN EQUIVALENT OF 831.6 X 10^6 SCF PER YEAR AT ESTABLISHED BTU CONTENTS OF 1000 BTU/CF AND 90500 BTU/GAL RESPECTIVELY. THESE UNITS ARE SUBJECT TO PSD.

# POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - ANCILLARY EQUIPMENT

\*Pollutant

**OPACITY** 

\*CAS Number:

VE

\*Control Method Code:

\*Control Method

Description:

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

20

Emission Limit 1 Unit:

%

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

Emission Limit 2:

Emission Limit 2 Unit:

**Emission Limit 2** 

Condition:

Standard Emission:

Standard Emission Unit:

Standard Emission

Condition:

\*Emission Type:

**CAP Cost of Control** 

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

#### PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process:

MAIN BAGHOUSE DUST HANDLING SYSTEM

\*Process Type:

81.006

\*SCC Code:

3-03-009-98

Primary Fuel: Throughput:

Throughput Unit:

Compliance Verified:

No

Stack Testing:

No

Inspections:

No

Calculations: Other Testing: No No

Other Testing Method:

Process/Compliance

INCLUDES HOPPERS, SCREW CONVEYORS, PNEUMATIC

Notes:

CONVEYING SYSTEM, STORAGE SILO, AND LOADING OPERATION.

SUBJECT TO PSD.

## POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - MAIN BAGHOUSE **DUST HANDLING SYSTEM**

\*Pollutant

**OPACITY** 

\*CAS Number:

**VE** 

\*Control Method Code:

Α

\*Control Method

**BAGHOUSE** 

Description:

Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1: 10 Emission Limit 1 Unit: %

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency:

**Emission Limit 2:** 

**Emission Limit 2 Unit:** 

**Emission Limit 2** 

Condition:

Standard Emission:

10

Standard Emission Unit: OPACITY

Standard Emission

Condition:

\*Emission Type:

CAP Cost of Control

\$ 0

F

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

#### PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process:

EAF FLUX/ALLOY SYSTEM

\*Process Type:

81.006

\*SCC Code:

3-03-009-04

Primary Fuel: Throughput:

Throughput Unit:

Compliance Verified:

No

Stack Testing: Inspections:

No No

Calculations:

No

Other Testing:

No

Other Testing Method:

Process/Compliance Notes:

CONSISTS OF FIVE STORAGE SILOS, CONTROLLED BY TWO BIN VENT FILTERS EACH RATED AT 1200 ACFM, AND ASSOCIATED FEED SYSTEMS. FLUX/ALLOY IS FED TO THE EAF. THERE IS A

VALVE IN THE DUCTWORK THAT WHEN ENGAGED ALLOWS THE EAF FLUX/ALLOY SYSTEM TO BE VENTED THROUGH THE MAIN

BAGHOUSE, SUBJECT TO PSD.

## POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - EAF FLUX/ALLOY SYSTEM

\*Pollutant

**OPACITY** 

\*CAS Number:

VE

\*Control Method Code:

Α

\*Control Method

BAGHOUSE, BIN VENT FILTER

Description:

Number of Options

Considered:

Rank of Option Selected:

**Emission Limit 1:** 

20

Emission Limit 1 Unit:

%

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency: **Emission Limit 2:** 

Emission Limit 2 Unit:

**Emission Limit 2** 

Condition:

Standard Emission:

20

Standard Emission Unit: % OPACITY

Standard Emission

Condition:

\*Emission Type:

P

**CAP Cost of Control** 

\$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

PM

\*CAS Number:

PM

\*Control Method Code:

1 141

\*Control Method

ue.

Description:

BIN VENT FILTERS, VENT TO BAGHOUSE.

Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1:

.5

P

\$ 0

Emission Limit 1 Unit:

LB/H

**Emission Limit 1** 

Condition:

\*Basis:

BACT-PSD

\*Percent Efficiency:

**Emission Limit 2:** 

Emission Limit 2 Unit:

Emission Limit 2

Condition:

Standard Emission:

Standard Emission Unit: GR/DSCF

Standard Emission

Condition:

\*Emission Type:

CAP Cost of Control

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No

Dollar Year Used In Cost

Estimates:

Pollutant Notes:

## PROCESS INFORMATION: NUCOR STEEL- DARLINGTON COUNTY

\*Process:

LMF FLUX/ALLOY SYSTEM

\*Process Type:

81.006

\*SCC Code:

3-03-009-04

Primary Fuel: Throughput:

Throughput Unit:

Compliance Verified:

No

Stack Testing:

No

Inspections: Calculations:

No No

Other Testing:

No

Other Testing Method:

Process/Compliance

Notes:

CONSISTS OF FOUR STORAGE SILOS CONTROLLED BY TWO BIN VENT FILTERS, EACH REATED AT 1200 ACFM, AND ASSOCIATED FEED SYSTEMS. FLUX/ALLOY IS FED TO THE LMF. SUBJECT TO

PSD.

POLLUTANT INFORMATION: NUCOR STEEL- DARLINGTON COUNTY - LMF FLUX/ALLOY SYSTEM

\*Pollutant

**OPACITY** 

\*CAS Number:

VE.

\*Control Method Code: Α

\*Control Method

**BIN VENT FILTERS** 

Description:

Number of Options

Considered:

Rank of Option Selected: **Emission Limit 1:** 20 **Emission Limit 1 Unit:** 

**Emission Limit 1** 

Condition:

\*Basis:

**BACT-PSD** 

\*Percent Efficiency: **Emission Limit 2:** Emission Limit 2 Unit:

**Emission Limit 2** 

Condition:

Standard Emission:

20

Standard Emission Unit: % OPACITY

Standard Emission

Condition:

\*Emission Type: **CAP Cost of Control**  P

\$0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes:

\*Pollutant

**PM** 

\*CAS Number:

PM

\*Control Method Code:

Α

\*Control Method

BIN VENT FILTERS

Description:

Number of Options

Considered:

Rank of Option Selected:

Emission Limit 1: .5
Emission Limit 1 Unit: LB/H

Emission Limit 1 Condition:

\*Basis: BACT-PSD

\*Percent Efficiency:

Emission Limit 2:

Emission Limit 2 Unit: GR/DSCF

Emission Limit 2

Condition:

Standard Emission: Standard Emission Unit: Standard Emission

Condition:

\*Emission Type: P
CAP Cost of Control
Favinment: \$ 0

Equipment:

Annualized Cost:

O&M Cost:

Cost Effectiveness:

Cost Verified by Agency: No Dollar Year Used In Cost

Estimates:

Pollutant Notes: