

Note: This is a reference cited in *AP 42, Compilation of Air Pollutant Emission Factors, Volume I Stationary Point and Area Sources*. AP42 is located on the EPA web site at www.epa.gov/ttn/chief/ap42/

The file name refers to the reference number, the AP42 chapter and section. The file name "ref02_c01s02.pdf" would mean the reference is from AP42 chapter 1 section 2. The reference may be from a previous version of the section and no longer cited. The primary source should always be checked.

Background Report Reference

AP-42 Section Number: 12.20

Background Chapter: 4

Reference Number: 76


Title: Gravo, Inc., Scrubber Efficiency
Evaluation project

November 1989

AP-42 Section 12.20
Reference
Report Sect. 4
Reference 76

DER - RECEIVED
HARRISTOWN

NOV 29 1989



AirNova, Inc.

AIR QUALITY SAMPLING AND ANALYSIS

~~674023, INC.~~
~~PATENTED TECHNOLOGY~~

Scrubber Efficiency Evaluation
Project

(609) 858-2100
931 Haddon Avenue
P.O. Box 97
Collingswood, NJ 08108

Commonwealth of Pennsylvania
 Environmental Resources
 December 21, 1989

Subject: Stack Test Review

To: Data File
 Grayco, Inc.
 Chalfont, Bucks County

From: Scott M. Darling *Scott*
 Air Pollution Control Engineer
 Continuous Emission Monitoring Unit
 Division of Technical Services & Monitoring
 Bureau of Air Quality Control

Through: Chief, Continuous Emission Monitoring Unit
 Chief, Source Testing & Monitoring Section *WJ*

The stack tests conducted by Air Nova, Inc. on the scrubber operated by Grayco, Inc. were not compliance tests and were not performed using the Department's reference methods for particulate and chromium. The procedures used should give results indicative of the source's emissions, but could be biased low.

Errors in the calculation of the emission rates were discovered in the test report. The following are the Department calculated results:

Run	1		2	
Pollutant	Particulate	Chromium	Particulate	Chromium
Inlet Concentration (ppm/DSCF)	0.0432	0.0019	0.0392	0.00117
Outlet Concentration (ppm/DSCF)	0.0046	0.00015	0.0041	0.00012
Inlet Emission Rate (lbs./hr.)	0.2352	0.0103	0.2170	0.0065
Outlet Emission Rate (lbs./hr.)	0.0245	0.0003	0.0214	0.00065
Removal Efficiency (%)	89.2	92.2	90.1	90.0

From Amy

Brown


4/16/96

Can you check to see
 if this is their entire
 report.

Thanks Rick

Rick, Heres the rest. Brown 4/16

Not
 enough
 data



November 22, 1989

DER - RECEIVED
NORRISTOWN

NOV 29 1989

Mr. N. Rao Kona
Regional Air Pollution Control Engineer
PA Dept. of Environmental Resources
1875 New Hope Street
Norrstown, PA 19401

Re: Plan Approval No. 09-313-069

Dear Mr. Kona:

You were notified on July 25, 1989, that the construction of the double-packed scrubber was completed.

The plan approval does not officially require the outside testing for scrubber efficiency. Gravco had such a test program completed on September 1, 1989, by Air Nova, Inc. The results of these tests for particulate and chromium concentrations emission rates are incorporated in the attached copy of Air Nova's report.

Gravco is volunteering this data to expedite the issuance of a permanent operating permit for the scrubber.

Sincerely yours,

A handwritten signature in cursive script, appearing to read 'Bob Isen'.

Robert Rand Isen
General Counsel

Bill Cosden

RI/sc


Enclosure

cc: Mr. Edward Brown, D.E.R.
Jackie Hyton
William Cosden

12/24

DER - RECEIVED
WARRINGTON

NOV 29 1989



AirNew, Inc.

AIR QUALITY SAMPLING AND ANALYSIS

~~SP-4-122, NYC,~~
~~RECEIVED WARRINGTON~~

Scrubber Efficiency Evaluation
Project

(609) 858-2100
931 Haddon Avenue
P.O. Box 97
Collingswood, NJ 08108

Project No. 1267

~~GRANCO, INC.~~
~~Portland, Oregon~~

Scrubber Efficiency Evaluation
Project

Prepared for:

Bill Conden
WDC Consultants
P. O. Box 372
Beverly, NJ 08010

November 1989

Table of Contents

	Page
1.0 Introduction	1
2.0 Site Description	2
3.0 Results	3
Appendix A - Laboratory Data	
Appendix B - Field Data Sheets	
Appendix C - Lotus 1-2-3 Calculation Printouts	

1.0 Introduction

AirNova, Inc. conducted a scrubber efficiency evaluation project at the ~~GRAVCO~~
~~Particulate Production~~ facility in Chalfont, Pennsylvania. The on-site testing was conducted on September 1, 1989.

The scrubber was utilized to remove chromium and particulate emissions from the exhaust stream of a chrome plating process. Two (2) simultaneous sampling runs were conducted on the inlet and outlet of the scrubber. Testing was conducted for the following parameters:

Sampling Location	Parameter
Inlet	Particulates Total Chromium
Outlet	Particulates Total Chromium

The removal efficiency of total chromium and particulates was determined from the testing. This report is a summary of the testing project.

2.0 Site Description

The scrubber which was evaluated was designed by Corro-Flow Engineering of Louisville, Kentucky. The counter-current flow scrubber utilized deionized water as the scrubbing solution.

2.1 Process Data

No. of Rollers	4
Length of Rollers	46 inches
Circumference of Rollers	23.5 inches
Application Rate	0.5 micron/min.
Current	2800 amps

Run 1

103.5	G198
103.5	G203

Run 2

103.5	G197
103.5	G200

} ?

3.0 Results

3.1 Air Flows, Temperatures, Moisture Levels

Run	Location	ACFM	Temp. °F	Moisture Level %	DSCFM
1	Inlet	705	89	7.0	634
2	Inlet	719	90	6.7	647
Average		712	90	6.9	641
1	Outlet	672	101	1.1	628
2	Outlet	654	103	0.9	611
Average		663	102	1.0	620

3.2 Particulate Concentrations and Emission Rates

Run	Location	Front Half Concentration grains/dscf	Total Conc. grains/dscf	Front Half Emission Rate lbs/hr	Total Emission lbs/hr
1	Inlet	.046	.047	.019	.019
2	Inlet	.039	.039	.019	.019
Average		.043	.043	.019	.019
1	Outlet	.004	.005	.002	.002
2	Outlet	.001	.002	.001	.001
Average		.003	.004	.002	.002

Standard Conditions: 68°F, 29.92 in. Hg.

3.3 Chromium Concentrations and Emission Rates

Run	Location	Concentration g/dscf	Concentration mg/dscm	Emission Rate lbs/hr
1	Inlet	1.2×10^{-4}	2.0×10^{-6}	0.01
2	Inlet	0.7×10^{-4}	1.1×10^{-6}	0.01
Average		1.0×10^{-4}	1.6×10^{-6}	0.01
1	Outlet	1.0×10^{-5}	1.6×10^{-7}	0.0008
2	Outlet	0.9×10^{-5}	1.4×10^{-7}	0.0007
Average		1.0×10^{-5}	1.5×10^{-7}	0.0008

3.4 Particulate Removal Efficiency (% PER)

Run	Front Half % PER	Total % PER
1	92.1	91.4
2	97.3	96.6
Average		94.0

3.5 Chromium Removal Efficiency (% CRE)

Run	% CRE
1	92.1
2	98.7
Average	90.4

Standard Conditions: 68°F, 29.92 in. Hg.

Appendix A
Laboratory Data

~~GRAYCO~~
 Emission Evaluation Test
 Particulate Laboratory Data

A. Glass Microfibre Filters

Sample I.D.	Final mass (g.)	Initial mass (g.)	Net mass (g.)
1-in	0.3377	0.3328	0.0049
2-in	0.3465	0.3435	0.0030
1-out	0.3410	0.3394	0.0016
2-out	0.3569	0.3470	0.0099
Blank	0.3328	0.3332	-0.0004

B. Acetone Front half wash / Back Catch

Sample I.D.	Final m. (g.)	Initial m. (g.)	Net m. (g.)	Volume (ml)	Aliquot Vol. (ml)
1-in/Ft.	96.458	96.3283	0.1297	110	110
2-in/Ft.	70.8000	70.66	0.1400	127	127
1-in/Bk.	100.8296	100.8283	0.0013	240	100
2-in/Bk.	100.3519	100.3501	0.0018	250	100
1-out/Ft.	92.5391	92.5301	0.0090	110	110
2-out/Ft.	100.8312	100.8283	0.0029	100	100
1-out/Bk.	97.8270	97.8255	0.0011	166	100
2-out/Bk.	95.9984	95.9973	0.0011	182	100
blank	97.8259	97.8259	0	50	50

C. Back half Filtration (.22u)

Sample I.D.	Final m. (g)	Initial (g)	Net m. (g)	Volume (ml)	Aliquot Vol. (ml)
1-in	0.0703	0.0701	0.0002	240	240
2-in	0.0710	0.0707	0.0003	350	350
1-out	0.0717	0.0712	0.0005	154	154
2-out	0.0708	0.0705	0.0003	175	175

Gravco
~~Fluorimetric~~ Emission Evaluation Test
 Chromium Laboratory Data

A. Aqueous Samples

Sample I.D.	Matrix	Aliquot Vol (ml)	Sample Vol. (ml)	Conc. mg/l
1-in	Ft-1/2 acetone	1	113	42.6
1-in	Bk-1/2 DI wash	20	260	< 0.05
2-in	Ft-1/2 acetone	1	188	14.3
2-in	Bk-1/2 DI wash	20	270	< 0.05
1-out	Ft-1/2 acetone	1	131	1.1
1-out	Bk-1/2 DI wash	20	174	< 0.05
2-out	Ft-1/2 acetone	1	122	1.65
2-out	Bk-1/2 DI wash	20	122	< 0.05
blank	DI	20	100	< 0.05
Spike (2-out)	Bk-1/2 DI wash	20 + 5 ml 20 ppm Cr ⁺		11.7 117 % Rec
Control (blank)	DI	20 + 5 ml 20 ppm Cr ⁺		10.8 108 % Rec


B. Glass Microfibre Filters

Sample I.D.	Total ug
1-in	1130
1-out	261
2-in	1630
2-out	229

Appendix B
Field Data Sheets

Airnova, Inc.

Job 1000000
 Date 7/1/78
 Sampling Location 1000000
 Sample for 1000000
 Air Sample 1000000
 Sample Size 1000000
 Sample Pressure 1000000
 Filter Number 1000000
 Filter Size 1000000
 Filter Material 1000000
 Filter Weight 1000000
 Filter Volume 1000000
 Filter Area 1000000
 Filter Thickness 1000000
 Filter Porosity 1000000
 Filter Efficiency 1000000
 Filter Flow Rate 1000000
 Filter Operating Time 1000000
 Filter Maintenance 1000000
 Filter Notes 1000000



PROJECT NUMBER 1000000
 SAMPLE NUMBER 1000000
 DATE 7/1/78
 TIME 1000000
 LOCATION 1000000
 OPERATOR 1000000
 ASSIGNED TO 1000000
 APPROVED BY 1000000
 SIGNATURE 1000000
 DATE 1000000

READ AND RECORD ALL DATA EVERY MINUTE

TRAVEL TIME PUMP NUMBER	CLOCK TIME HH:MM:SS	GAS WATER RATIO G/L	VELOCITY M/S	ORANGE PRESSURE PSI	STACK TEMPERATURE °F	ORANGE WATER TEMPERATURE °F	PUMP VACUUM IN. HG	SAMPLE BOX TEMPERATURE °F	WIND DIRECTION °
1	06 11:00	757.165	.14	1.2	103	96	3.75	239	1
2	06 11:01	761.1	.11	1.01	103	98	3.5	234	1
3	06 11:02	766.7	.12	1.15	103	102	3.75	247	1
4	06 11:03	769.7	.13	1.2	101	107	3.75	246	115
5	06 11:04	773.2	.13	1.2	101	107	3.75	251	101
6	06 11:05	776.2	.12	1.1	101	107	3.75	254	100
7	06 11:06	779.2	.14	1.3	101	103	3.75	258	102
8	06 11:07	783.8	.13	1.2	101	110	3.75	261	177
9	06 11:08	787.7	.12	1.15	103	111	3.7	259	91
10	06 11:09	791.2	.11	1.05	103	111	3.0	261	95
11	06 11:10	794.7	.11	1.05	101	106	2.5	261	85
12	06 11:11	798.2	.11	1.05	101	109	2.5	262	11
13	06 11:12	801.7	.11	1.05	101	109	2.5	262	11
14	06 11:13	805.2	.11	1.05	101	109	2.5	262	11
15	06 11:14	808.7	.11	1.05	101	109	2.5	262	11
16	06 11:15	812.2	.11	1.05	101	109	2.5	262	11
17	06 11:16	815.7	.11	1.05	101	109	2.5	262	11
18	06 11:17	819.2	.11	1.05	101	109	2.5	262	11
19	06 11:18	822.7	.11	1.05	101	109	2.5	262	11
20	06 11:19	826.2	.11	1.05	101	109	2.5	262	11
21	06 11:20	829.7	.11	1.05	101	109	2.5	262	11
22	06 11:21	833.2	.11	1.05	101	109	2.5	262	11
23	06 11:22	836.7	.11	1.05	101	109	2.5	262	11
24	06 11:23	840.2	.11	1.05	101	109	2.5	262	11
25	06 11:24	843.7	.11	1.05	101	109	2.5	262	11
26	06 11:25	847.2	.11	1.05	101	109	2.5	262	11
27	06 11:26	850.7	.11	1.05	101	109	2.5	262	11
28	06 11:27	854.2	.11	1.05	101	109	2.5	262	11
29	06 11:28	857.7	.11	1.05	101	109	2.5	262	11
30	06 11:29	861.2	.11	1.05	101	109	2.5	262	11
31	06 11:30	864.7	.11	1.05	101	109	2.5	262	11
32	06 11:31	868.2	.11	1.05	101	109	2.5	262	11
33	06 11:32	871.7	.11	1.05	101	109	2.5	262	11
34	06 11:33	875.2	.11	1.05	101	109	2.5	262	11
35	06 11:34	878.7	.11	1.05	101	109	2.5	262	11
36	06 11:35	882.2	.11	1.05	101	109	2.5	262	11
37	06 11:36	885.7	.11	1.05	101	109	2.5	262	11
38	06 11:37	889.2	.11	1.05	101	109	2.5	262	11
39	06 11:38	892.7	.11	1.05	101	109	2.5	262	11
40	06 11:39	896.2	.11	1.05	101	109	2.5	262	11
41	06 11:40	899.7	.11	1.05	101	109	2.5	262	11
42	06 11:41	903.2	.11	1.05	101	109	2.5	262	11
43	06 11:42	906.7	.11	1.05	101	109	2.5	262	11
44	06 11:43	910.2	.11	1.05	101	109	2.5	262	11
45	06 11:44	913.7	.11	1.05	101	109	2.5	262	11
46	06 11:45	917.2	.11	1.05	101	109	2.5	262	11
47	06 11:46	920.7	.11	1.05	101	109	2.5	262	11
48	06 11:47	924.2	.11	1.05	101	109	2.5	262	11
49	06 11:48	927.7	.11	1.05	101	109	2.5	262	11
50	06 11:49	931.2	.11	1.05	101	109	2.5	262	11
51	06 11:50	934.7	.11	1.05	101	109	2.5	262	11
52	06 11:51	938.2	.11	1.05	101	109	2.5	262	11
53	06 11:52	941.7	.11	1.05	101	109	2.5	262	11
54	06 11:53	945.2	.11	1.05	101	109	2.5	262	11
55	06 11:54	948.7	.11	1.05	101	109	2.5	262	11
56	06 11:55	952.2	.11	1.05	101	109	2.5	262	11
57	06 11:56	955.7	.11	1.05	101	109	2.5	262	11
58	06 11:57	959.2	.11	1.05	101	109	2.5	262	11
59	06 11:58	962.7	.11	1.05	101	109	2.5	262	11
60	06 11:59	966.2	.11	1.05	101	109	2.5	262	11

Stick 20

PLANT Parameter DATE 9/1/89 RUN NUMBER 2 1 PA Porticulate

TRAVEL POINT NUMBER	CLOCK TIME SAMPLING TIME MIN	CLOCK TIME END	GAS WATER READING IN LBS	VELOCITY HEAD W.G. IN H ₂ O	DIFFERENTIAL PRESS. IN H ₂ O		SLATE TEMPERATURE °F	DRY GAS WET TEMPERATURE °F		PUMP VACUUM IN HG	SAMPLE BOX TEMPERATURE °F	WET BULB TEMPERATURE °F
					DESIGN	ACTUAL		INLET	OUTLET			
1	07	13:45	801.712	11	1.15	1.15	100	103	103	1.5	27	71
2	07	13:51	805.4	11	1.15	1.15	101	103	103	1.5	27	71
3	07	13:57	804.8	11	1.15	1.15	101	103	103	1.5	27	71
4	07	14:03	811.8	11	1.15	1.15	102	103	103	1.5	27	71
5	07	14:13	813.8	11	1.15	1.15	103	103	103	1.5	27	71
6	07	14:20	822.1	11	1.15	1.15	103	103	103	1.5	27	71
7	07	14:30	827.1	11	1.15	1.15	103	103	103	1.5	27	71
8	07	14:37	838.672	11	1.15	1.15	102	103	103	1.5	27	71
9	07	14:46	842.825	11	1.15	1.15	102	103	103	1.5	27	71
10	07	14:53	846.8	11	1.15	1.15	102	103	103	1.5	27	71
11	07	15:00	846.8	11	1.15	1.15	102	103	103	1.5	27	71
12	07	15:07	854.545	11	1.15	1.15	103	103	103	1.5	27	71
13	07	15:14	854.545	11	1.15	1.15	103	103	103	1.5	27	71

27.5

IMPURITIES _____
 FINAL VOLUME 171 _____
 INITIAL VOLUME 200 _____
 NET VOLUME -29 _____
 TOTAL MOISTURE _____
 SILICA GEL _____
 FINAL WEIGHT _____
 INITIAL WEIGHT _____
 NET WEIGHT _____
 TOTAL MOISTURE _____

ANALYTICAL DATA BY _____
 ACETONE FRONT WASH
 FINAL _____ mg
 TARE _____ mg
 NET _____ mg
 FILTER NUMBER 1
 FINAL _____ mg
 TARE _____ mg
 NET _____ mg
 FILTER NUMBER 2
 FINAL _____ mg
 TARE _____ mg
 NET _____ mg
 FILTER NUMBER 3
 FINAL _____ mg
 TARE _____ mg
 NET _____ mg
 TOTAL FRONT _____ mg

ACETONE BACK WASH
 FINAL _____ mg
 TARE _____ mg
 NET _____ mg
 ETHER-CHLOROFORM EXTRACT
 FINAL _____ mg
 TARE _____ mg
 NET _____ mg
 WATER EVAPORATION
 FINAL _____ mg
 TARE _____ mg
 NET _____ mg
 TOTAL BACK _____ mg

I CERTIFY THAT THE SAMPLES RECEIVED BY THIS DATA SHEET WERE COLLECTED IN ACCORDANCE WITH METHODS OUTLINED BY _____
 I FURTHER CERTIFY THAT THE SAMPLES WERE IN THE POSSESSION OF, OR STORED FOR, SHIPMENT BY COMMON CARRIER BY RAIL OR BY AIR, AND THAT THE SAMPLES WERE DELIVERED TO A LABORATORY FOR ANALYSIS.
 SIGNED _____ DATE _____
 WITNESS _____ DATE _____
 I CERTIFY THAT I RECEIVED THE SAMPLES DESCRIBED BY THIS DATA SHEET FROM THE ABOVE NAMED INDIVIDUAL AND ANALYZED THEM IN ACCORDANCE WITH THE ABOVE NAMED PROCEDURE.
 SIGNED _____ DATE _____

CALCULATED PRESSURE DIFFERENTIAL ACROSS ORIFICE, IN H₂O _____
 AVERAGE WATER TEMPERATURE (AMBIENT + 20°F), °F _____
 PRESSURE HEAD IN GAS STREAM BY VOLUME _____
 PRESSURE HEAD AT WATER, IN H₂O _____
 STATES PRESSURE IN STACK, IN H₂O _____
 P₁ - P₂ - STACK GAUGE PRESSURE IN H₂O _____
 RATIO OF STATES PRESSURE TO WATER PRESSURE _____
 AVERAGE STACK TEMPERATURE, °F _____
 AVERAGE VELOCITY HEAD, IN H₂O _____
 MAXIMUM VELOCITY HEAD, IN H₂O _____
 C FACTOR _____
 CALCULATED NOZZLE DIAMETER, IN _____
 ACTUAL NOZZLE DIAMETER, IN _____
 REFERENCE IN H₂O _____
 DRY MOLECULAR WEIGHT DETERMINATION BY _____

SAMPLING TIME (24 HOURS) _____
 SAMPLING LOCATION _____
 SAMPLE TYPE (BAG, INTEGRATED, CONTINUOUS) _____
 ANALYTICAL METHOD _____
 AMBIENT TEMPERATURE _____

RUN	1		2		3	
	ACTUAL READING	NET	ACTUAL READING	NET	ACTUAL READING	NET
GAS						
CO ₂						
O ₂ IN ACTUAL OF READING MINUS ACTUAL CO ₂ READING						
CO ₂ IN ACTUAL CO READING MINUS ACTUAL O ₂ READING						
W ₂ IN ACTUAL OF						

RUN	1		2		3	
	ACTUAL READING	NET	ACTUAL READING	NET	ACTUAL READING	NET
GAS						
CO ₂						
O ₂ IN ACTUAL OF READING MINUS ACTUAL CO ₂ READING						
CO ₂ IN ACTUAL CO READING MINUS ACTUAL O ₂ READING						
W ₂ IN ACTUAL OF						

111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539
 540
 541
 542
 543
 544
 545
 546
 547
 548
 549
 550
 551
 552
 553
 554
 555
 556
 557
 558
 559
 560
 561
 562
 563
 564
 565
 566
 567
 568
 569
 570
 571
 572
 573
 574
 575
 576
 577
 578
 579
 580
 581
 582
 583
 584
 585
 586
 587
 588
 589
 590
 591
 592
 593
 594
 595
 596
 597
 598
 599
 600
 601
 602
 603
 604
 605
 606
 607
 608
 609
 610
 611
 612
 613
 614
 615
 616
 617
 618
 619
 620
 621
 622

11-11-11

THE

三、

3

100

10-10-68

SECRET

412 96 196 426 636

SECRET

6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
84

[illegible][illegible]

PLANT *Phosphate* DATE *9-1-90* RUN NUMBER *100*

TRAVEL POINT NUMBER	CLOCK TIME HH:MM:SS	GAS METER READING W.L.F.	VELOCITY HEAD W.L.F.	ORIFICE PRESSURE DIFFERENTIAL W.L.F.		STACK TEMPERATURE °F	GAS METER TEMPERATURE °F		PUMP VACUUM W.L.F.	SAMPLE GAS TEMPERATURE °F	OUTLET TEMPERATURE °F
				DESIGNED	ACTUAL		INLET	OUTLET			
100	1009	69	119	117	117	96	97	96	7	291	301
101		695.999	115	114	114	97	104	98	6	296	306
102		700.533	114	115	115	97	106	99	4	258	30
103		705.579	115	116	116	97	107	100	7	253	38
104		710.922	115	116	116	97	109	101	1	252	37
105		716.068	119	115	115	90	110	102	10	235	41
106		721.909	111	112	112	92	110	103	6	250	42
107		725.914	113	114	114	93	110	103	6	250	42
108		731.004	115	116	116	93	111	104	7	255	45
109		736.051	115	116	116	91	112	104	7	255	43
110		741.304	119	115	115	91	113	104	6	257	40
111		746.449	119	115	115	82	113	105	1	257	41
112		751.596									
113											
114											
115											
116											
117											
118											
119											
120											
121											
122											
123											
124											
125											
126											
127											
128											
129											
130											
131											
132											
133											
134											
135											
136											
137											
138											
139											
140											
141											
142											
143											
144											
145											
146											
147											
148											
149											
150											
151											
152											
153											
154											
155											
156											
157											
158											
159											
160											
161											
162											
163											
164											
165											
166											
167											
168											
169											
170											
171											
172											
173											
174											
175											
176											
177											
178											
179											
180											
181											
182											
183											
184											
185											
186											
187											
188											
189											
190											
191											
192											
193											
194											
195											
196											
197											
198											
199											
200											

699X OK 111.004 87 M"

Appendix C
Lotus 1-2-3
Calculation Printouts

Air Nova Inc.

EPA Method 5 Calculations

Plant Paramount/Gravco project

Project # 1267

Operation Platen Press No. 2

Run 1

Location Chalfont, Pa

Date 9/01/89

Scrubber Inlet Test Data

Vlc =	77.6 cc	Vol. of H2O collected (impingers)
Vm =	50.737 cf	Dry gas meter reading
Pb =	30.1 in. Hg	Barometric pressure
Pst =	30.1 in. Hg	Stack pressure
dP =	0.368	Average sq. rt delta P
dH =	1.458 in. H2O	Average draft gauge reading
Tm =	554.25 R	Average meter temperature
Ts =	549.25 R	Average stack temperature
Ar =	0.001 ft ²	Area of nozzle orifice
Y =	0.99	Meter calibration factor
t =	72 min.	Duration of sampling time
A =	0.5450 sq. ft.	Cross sectional area of stack
Cp =	0.85	Pitot tube coefficient
Kp =	85.49	Pitot tube constant
K1 =	17.64 R/in. Hg	constant
K2 =	0.04707 cu. ft./ml	constant
K3 =	0.002569 in. Hg-cf/ml-R	constant

1) Volume of gas sampled at standard conditions, Vmstd

$$Vmstd = K1 * Y * Vm * (Pb + dH/13.6) / Tm$$

$$Vmstd = 48.29 \text{ cu. ft.}$$

2) Volume of water vapor collected at standard conditions.

$$Vw(std) = K2 * Vlc$$

$$Vw(std) = 3.55 \text{ scf}$$

3) Decimal fraction of moisture by volume in stack gas

$$Bws = Vwstd / (Vmstd + Vwstd)$$

$$Bws = 0.070$$

4) Molecular weight of the stack gas on a dry basis M_d .

$$M_d = (1-Q) * ((.44 * \%CO_2) + (.28 * \%CO) + (.32 * \%O_2) + (.28 * \%N_2)) + (18 * Q)$$

$$M_d = 28.05$$

Orsat analysis

% CO ₂	0
% CO	0
% O ₂	20.3
% N ₂	79.7

5) Average stack gas velocity.

$$v_s = K_p * C_p * (dP^{0.5}) * (T_s / P_s * M_d)^{.5}$$

$$v_s = 21.56 \text{ ft/sec}$$

6) Average actual stack gas volumetric flowrate.

$$Q = 60 * v_s * A_s$$

$$Q = 705.08 \text{ cfm}$$

7) Average stack gas dry volumetric flowrate.

$$Q_{std} = Q * (T_{std} / T_s) * (P_s / P_{std})$$

$$Q_{std} = 633.93 \text{ cfm}$$

8) Analytical data

a) Front half water wash - insoluble

0 g .22u filter net weight

b) Front half water wash - soluble

0 g filtrate net wt
0 g water blank net wt
0 ml Final wash volume
0 ml aliquot

ERR. 0 g soluble net wt

c) Front half acetone wash

0.1397 g wash net wt
0 g acetone blank net wt
110 ml Final wash volume
110 ml aliquot

0.1397 g soluble particulate

d) Front half glass microfibre filter

0.0053 g filter net wt

e) Back half water wash -insoluble

0.0002 g .22u filter net weight

f) Back half water wash - soluble

0.0013 g filtrate net wt
0 g water blank net wt
240 ml Final wash volume
100 ml aliquot

0.0013 g soluble net wt

g) Back half acetone rinse

0 g wash net wt
0 g acetone blank net wt
0 ml Final wash volume
0 ml aliquot

ERR

0 g soluble particulate

9) Total particulate concentrations
mass/dscf

0.0464 grains/dscf Front 1/2 (inc. bk 1/2 insoluble)
0.0468 grains/dscf Total

10) Total particulate emission rate

Conc. * (1 lb/7000 gr) * Qstd * 60 min/hr

W = 0.0192 lbs/hr Front 1/2 (inc. bk 1/2 insoluble)
W = 0.0194 lbs/hr Total Particulate

11) Total Chromium concentration

Total Cr = 0.006 g

Conc. = Cr/dscf

Conc. = 0.00012 g/dscf

12) Total Chromium Emission Rate

$$\text{Conc.} = (1/453.6) * Q_{\text{std}} * 60$$

$$W_{\text{Cr}} = 0.01 \text{ lbs/hr}$$

13) Isokineticity

$$\% I = 100 * T_s * ((K_3 * V)_{\text{sc}} + (V_m * Y / T_m) (P_b + dH / 13.6)) / (60 * t * P_s + V_m * T_m)$$

$$\% I = 110.06$$

Scrubber Outlet Test Data

V_{lc}	=	10 cc	Vol. of H ₂ O collected (impingers)
V_m	=	44.107 cf	Dry gas meter reading
P_b	=	30.1 in. Hg	Barometric pressure
P_s	=	30.1 in. Hg	Stack pressure
dP	=	0.351	Average sq. rt delta P
dH	=	1.158 in. H ₂ O	Average draft gauge reading
T_m	=	564.29 R	Average meter temperature
T_s	=	561.83 R	Average stack temperature
A_n	=	0.001 ft ²	Area of nozzle orifice
Y	=	0.99	Meter calibration factor
t	=	72 min.	Duration of sampling time
A	=	0.5450 sq. ft.	Cross sectional area of stack
C_p	=	0.85	Pitot tube coefficient
K_p	=	85.49	Pitot tube constant
K_1	=	17.64 R/in. Hg	constant
K_2	=	0.04707 cu. ft/ml	constant
K_3	=	0.002669 in. Hg-cf/ml-R	constant

14) Volume of gas sampled at standard conditions, V_{mstd}

$$V_{\text{mstd}} = K_1 * Y * V_m * ((P_b + dH / 13.6) / T_m)$$

$$V_{\text{mstd}} = 41.20 \text{ cu. ft}$$

15) Volume of water vapor collected at standard conditions.

$$V_{\text{w(std)}} = K_2 * V_{\text{lc}}$$

$$V_{\text{w(std)}} = 0.4707 \text{ scf}$$

16) Decimal fraction of moisture by volume in stack gas

$$B_{\text{ws}} = V_{\text{mstd}} / (V_{\text{mstd}} + V_{\text{wstd}})$$

$$B_{\text{ws}} = 0.011$$

17) Molecular weight of the stack gas on a dry basis M_d .

$$M_s = (1 - B) * ((44 * \%CO_2) + (28 * \%CO) + (32 * \%O_2) + (28 * \%N_2)) + (18 * B)$$

$$M_s = 28.69$$

Oxnat analysis

% CO2	0
% CO	0
% O2	20.3
% N2	79.7

18) Average stack gas velocity.

$$v_s = K_p \cdot C_p \cdot (d^2 \cdot 0.5) \cdot (T_s / P_s \cdot H_d) \cdot 0.5$$

$$v_s = 20.55 \text{ ft/sec}$$

19) Average actual stack gas volumetric flowrate.

$$Q = 60 \cdot v_s \cdot A_s$$

$$Q = 672.13 \text{ cfm}$$

20) Average stack gas dry volumetric flowrate.

$$Q_{std} = Q \cdot (T_{std} / T_s) \cdot (P_s / P_{std})$$

$$Q_{std} = 628.28 \text{ cfm}$$

21) Analytical data

a) Front half water wash - insoluble

0 g .22u filter net weight

b) Front half water wash - soluble

0 g filtrate net wt

0 g water blank net wt

0 ml Final wash volume

0 ml aliquot

ERR 0 g soluble net wt

c) Front half acetone wash

0.009 g wash net wt

0 g acetone blank net wt

110 ml Final wash volume

110 ml aliquot

0.009 g soluble particulate

d) Front half glass microfibre filter

0.002 g filter net wt

e) Back half water wash -insoluble

0.0005 g .22u filter net weight

f) Back half water wash - soluble

0.0011 g filtrate net wt

0 g water blank net wt

166 ml Final wash volume

100 ml aliquot

0.0011 g soluble net wt

g) Back half acetone rinse

0 g wash net wt

0 g acetone blank net wt

0 ml Final wash volume

0 ml aliquot

ERR

0 g soluble particulate

22) Total particulate concentrations
mass/dscf

0.00431 grains/dscf Front 1/2 (inc. bk 1/2 insoluble)

0.00472 grains/dscf Total

23) Total particulate emission rate

Conc. * (1 lb/7000 gr) * Qstd * 60 min/hr

W = 0.00152 lbs/hr Front 1/2 (inc. bk 1/2 insoluble)

W = 0.00157 lbs/hr Total Particulate

24) Total Chromium concentration

Total Cr = 0.00041 g

Conc. = Cr/dscf

Conc. = 0.0000100 g/dscf

25) Total Chromium Emission Rate

Conc. * (1/453.6) * Qstd * 60

Wcr = 0.00083 lbs/hr

26) Isokineticity

0.10967

38.19

$$\% I = 100 \times T_s \div (0.3 \times V_{le} + (V_m \times V / T_m) (P_b + dH / 13.6)) \div (60 \times t \times P_s + V_m \times A_n)$$

$$\% I = 94.75$$

2.672.16

27) Scrubber Particulate Removal Efficiency

$$\% RE = 100 \times (W_{in} - W_{out}) / W_{in}$$

$$\% RE = 92.08 \text{ Front } 1/2$$

$$\% RE = 91.40 \text{ Total}$$

28) Scrubber Chromium Removal Efficiency

$$\% RE = 100 \times (W_{in} - W_{out}) / W_{in}$$

$$\% RE = 92.06$$

Air Nova Inc.

EPA Method 5 Calculations

Plant Paramount/Gravco project
 Project # 1267
 Operation Platen Press No. 2
 Run 2
 Location Chalfont, Pa
 Date 9/01/89

Scrubber Inlet Test Data

Vlc =	88.2 cc	Vol. of H2O collected (impingers)
Vm =	61.467 cf	Dry gas meter reading
Pb =	30.1 in. Hg	Barometric pressure
Ps =	30.1 in. Hg	Stack pressure
dP =	0.375	Average sq. rt delta P
dH =	1.508 in. H2O	Average draft gauge reading
Tm =	564.5 R	Average meter temperature
Ts =	550.50 R	Average stack temperature
An =	0.001 ft ²	Area of nozzle orifice
Y =	0.99	Meter calibration factor
t =	84 min.	Duration of sampling time
A =	0.5450 sq. ft.	Cross sectional area of stack
Cp =	0.85	Pitot tube coefficient
Kp =	85.49	Pitot tube constant
K1 =	17.64 R/in. Hg	constant
K2 =	0.04707 cu. ft/ml	constant
K3 =	0.002669 in. Hg-cf/ml-R	constant

1) Volume of gas sampled at standard conditions, Vmstd
 $Vmstd = K1 * Y * Vm * (Pb + dH/13.6) / Tm$

Vmstd = 57.45 cu. ft

2) Volume of water vapor collected at standard conditions.

Vw(std) = K2 * Vlc

Vw(std) = 4.15 scf

3) Decimal fraction of moisture by volume in stack gas

Bws = Vwstd / (Vmstd + Vwstd)

Bws = 0.067

4) Molecular weight of the stack gas on a dry basis M_d

$$M_d = (1-Q) + (44 \times \%CO_2) + (28 \times \%CO) + (32 \times \%O_2) + (28 \times \%N_2) + (18 \times Q)$$

$$M_d = 28.08$$

Orsat analysis

% CO_2 0

% CO 0

% O_2 20.3

% N_2 79.7

5) Average stack gas velocity.

$$v_s = K_p C_p (dP^{0.5}) (T_s/P_s M_d)^{0.5}$$

$$v_s = 21.98 \text{ ft/sec}$$

6) Average actual stack gas volumetric flowrate.

$$Q = 60 \times v_s \times A_s$$

$$Q = 715.87 \text{ cfm}$$

7) Average stack gas dry volumetric flowrate.

$$Q_{std} = Q \times (T_{std}/T_s) \times (P_s/P_{std})$$

$$Q_{std} = 645.89 \text{ cfm}$$

8) Analytical data

a) Front half water wash - insoluble

0 g .220 filter net weight

b) Front half water wash - soluble

0 g filtrate net wt

0 g water blank net wt

0 ml Final wash volume

0 ml aliquot

ERR

0 g soluble net wt

c) Front half acetone wash

0.14 g wash net wt
0 g acetone blank net wt
187 ml Final wash volume
187 ml aliquot

0.14 g soluble particulate

d) Front half glass microfibre filter

0.0034 g filter net wt

e) Back half water wash - insoluble

0.0003 g .22u filter net weight

f) Back half water wash - soluble

0.0018 g filtrate net wt
0 g water blank net wt
250 ml Final wash volume
100 ml aliquot

0.0018 g soluble net wt

g) Back half acetone rinse

0 g wash net wt
0 g acetone blank net wt
0 ml Final wash volume
0 ml aliquot

ERR

0 g soluble particulate

9) Total particulate concentrations
mass/dscf

0.0386 grains/dscf Front 1/2 (inc. bk 1/2 insoluble)
0.0391 grains/dscf Total

10) Total particulate emission rate

Conc. * (1 lb/7000 gr) * 60 min/hr

W = 0.0190 lbs/hr Front 1/2 (inc. bk 1/2 insoluble)
W = 0.0192 lbs/hr Total Particulate

11) Total Chromium concentration

Total Cr = 0.0043 g

Conc. = Cr/dscf

Conc. = 0.00007 g/dscf

1) Total Chromium Emission Rate

Conc. = $(1/453.5) * Q_{std} * 60$

Wcr = 0.01 lbs/hr

13) Isokineticity

$\% I = 100 * T_s * ((K3 * V_{lc} + (V_m * Y / T_m) (P_b + dH / 13.6)) / (60 * t * P_s * v_s * A_n))$

$\% I = 109.98$

Scrubber Outlet Test Data

$V_{lc} =$	10 cc	Vol. of H ₂ O collected (impingers)
$V_m =$	52.83 cf	Dry gas meter reading
$P_b =$	30.1 in. Hg	Barometric pressure
$P_s =$	30.1 in. Hg	Stack pressure
$dP =$	0.341	Average sq. rt delta P
$dH =$	1.104 in. H ₂ O	Average draft gauge reading
$T_m =$	565.46 R	Average meter temperature
$T_s =$	563.25 R	Average stack temperature
$A_n =$	0.001 ft ²	Area of nozzle orifice
$Y =$	0.99	Meter calibration factor
$t =$	84 min.	Duration of sampling time
$A =$	0.5450 sq. ft.	Cross sectional area of stack
$C_p =$	0.85	Pitot tube coefficient
$K_p =$	85.49	Pitot tube constant
$K_1 =$	17.64 R/in. Hg	constant
$K_2 =$	0.04707 cu. ft/ml	constant
$K_3 =$	0.002669 in. Hg-cf/ml-R	constant

14) Volume of gas sampled at standard conditions, V_{mstd}

$V_{mstd} = K_1 * Y * V_m * (P_b + dH / 13.6) / T_m$

$V_{mstd} = 49.24$ cu. ft

15) Volume of water vapor collected at standard conditions.

$V_w(std) = K_2 * V_{lc}$

$V_w(std) = 0.4707$ scf

16) Decimal fraction of moisture by volume in stack gas

$B_{ws} = V_{wstd} / (V_{mstd} + V_{wstd})$

$B_{ws} = 0.009$

17) Molecular weight of the stack gas on a dry basis M_d .

$M_g = (1 - Q) * ((44 * \%CO_2) + (28 * \%CO) + (32 * \%O_2) + (28 * \%N_2)) + (18 * Q)$

$M_g = 28.71$

Oresat analysis

% CO ₂	0
% CO	0
% O ₂	20.3
% N ₂	79.7

18) Average stack gas velocity.

$$v_s = K_p \cdot C_p \cdot (dp^{0.5}) \cdot (T_s / P_{std})^{0.5}$$

$$v_s = 20.01 \text{ ft/sec}$$

19) Average actual stack gas volumetric flowrate.

$$Q = 60 \cdot v_s \cdot A_s$$

$$Q = 654.32 \text{ cfm}$$

20) Average stack gas dry volumetric flowrate.

$$Q_{std} = Q \cdot (T_{std} / T_s) \cdot (P_s / P_{std})$$

$$Q_{std} = 611.22 \text{ cfm}$$

21) Analytical data

a) Front half water wash - insoluble

0 g .22u filter net weight

b) Front half water wash - soluble

0 g filtrate net wt

0 g water blank net wt

0 ml Final wash volume

0 ml aliquot

ERR 0 g soluble net wt

c) Front half acetone wash

0.0029 g wash net wt

0 g acetone blank net wt

100 ml Final wash volume

100 ml aliquot

0.0029 g soluble particulate

d) Front half glass microfibre filter

0.0007 g filter net wt

e) Back half water wash - insoluble

0.0003 g 1220 filter net weight

f) Back half water wash - soluble

0.0011 g filtrate net wt

0 g water blank net wt

182 ml Final wash volume

100 ml aliquot

0.0011 g soluble net wt

g) Back half acetone rinse

0 g wash net wt

0 g acetone blank net wt

0 ml Final wash volume

0 ml aliquot

ERR

0 g soluble particulate

22) Total particulate concentrations
mass/dscf

0.00122 grains/dscf Front 1/2 (inc. bk 1/2 insoluble)

0.00157 grains/dscf Total

23) Total particulate emission rate

Conc. * (1 lb/7000 gr) * Qstd * 60 min/hr

W = 0.00052 lbs/hr

Front 1/2 (inc. bk 1/2 insoluble)

W = 0.00066 lbs/hr

Total Particulate

24) Total Chromium concentration

Total Cr = 0.00044 g

Conc. = Cr/dscf

Conc. = 0.0000089 g/dscf

25) Total Chromium Emission Rate

Conc. * (1/453.6) * Qstd * 60

Wcr = 0.00072 lbs/hr

26) Isokineticity

$$\% I = 100 * T_s * ((K3 * V_{1c} + (V_m * V / T_m) * (P_b + dH / 13.6)) / (60 * (P_{g1} * V_{s1} + P_n)))$$

$$\% I = 99.77$$

27) Scrubber Particulate Removal Efficiency

$$\% RE = 100 * (W_{in} - W_{out}) / W_{in}$$

$$\% RE = 97.29 \text{ Front } 1/2$$

$$\% RE = 96.56 \text{ Total}$$

28) Scrubber Chromium Removal Efficiency

$$\% RE = 100 * (W_{in} - W_{out}) / W_{in}$$

$$\% RE = 88.72$$

100

1351
1352
1353
1354
1355
1356

50455-114
50455-114

3

1. The first part of the document is a header section containing the following information:

2. The second part of the document is a list of items, numbered 1 through 10, which are:

3. The third part of the document is a list of items, numbered 1 through 10, which are:

4. The fourth part of the document is a list of items, numbered 1 through 10, which are:

5. The fifth part of the document is a list of items, numbered 1 through 10, which are:

6. The sixth part of the document is a list of items, numbered 1 through 10, which are:

7. The seventh part of the document is a list of items, numbered 1 through 10, which are:

8. The eighth part of the document is a list of items, numbered 1 through 10, which are:

9. The ninth part of the document is a list of items, numbered 1 through 10, which are:

10. The tenth part of the document is a list of items, numbered 1 through 10, which are:

[illegible]

2000

1954-55

[illegible]

RE: *Phonograph* 9-1-39 3-1-39 *Ph. Ph. Ph.*

DATE	TIME	NO. OF RECORDS	REMARKS	NO. OF RECORDS	REMARKS	NO. OF RECORDS	REMARKS	NO. OF RECORDS	REMARKS	
100	1339	690.122	116	117.117	86	97	92	7	244	54
101		695.999	113	119.119	88	101	98	6	257	55
102		700.533	114	115.115	91	106	94	6	253	56
103		705.579	115	11.11	99	107	100	7	253	58
104		710.322	115	11.11	90	109	101	7	252	60
105		716.068	119	115.115	90	109	108	6	253	61
106		721.308	111	112.112	92	110	105	6	253	63
107		725.719	113	114.114	93	110	103	6	254	64
108		731.009	113	111.111	93	111	103	7	255	65
109		736.051	115	116.116	91	112	101	7	255	68
110		741.384	119	113.113	91	113	104	6	254	69
111		746.999	119	113.113	92	113	105		257	71
112	1503	751.076								

UPPER CH. 11. 004 27.11

2025-11-25 14:25:25

1900

Sl. No.	Name	Age	Sex	Religion	Marital Status	Education	Occupation	Income	Assets	Liabilities	Net Worth
1	Mr. A. B. C.	45	Male	Hindu	Married	High School	Teacher	10000	50000	10000	40000
2	Mr. D. E. F.	35	Male	Muslim	Single	College	Engineer	15000	60000	15000	45000
3	Mr. G. H. I.	55	Male	Hindu	Married	High School	Retired	8000	40000	8000	32000
4	Mr. J. K. L.	25	Male	Buddhist	Single	College	Student	5000	20000	5000	15000
5	Mr. M. N. O.	65	Male	Hindu	Married	High School	Retired	12000	50000	12000	38000
6	Mr. P. Q. R.	40	Male	Muslim	Married	College	Engineer	18000	70000	18000	52000
7	Mr. S. T. U.	30	Male	Hindu	Single	College	Engineer	20000	80000	20000	60000
8	Mr. V. W. X.	50	Male	Buddhist	Married	High School	Teacher	9000	45000	9000	36000
9	Mr. Y. Z. A.	20	Male	Hindu	Single	College	Student	4000	15000	4000	11000
10	Mr. B. C. D.	60	Male	Muslim	Married	High School	Retired	11000	48000	11000	37000
11	Mr. E. F. G.	42	Male	Hindu	Married	College	Engineer	16000	65000	16000	49000
12	Mr. H. I. J.	38	Male	Buddhist	Single	College	Engineer	19000	75000	19000	56000
13	Mr. K. L. M.	52	Male	Hindu	Married	High School	Teacher	10500	52000	10500	41500
14	Mr. N. O. P.	28	Male	Muslim	Single	College	Student	6000	25000	6000	19000
15	Mr. Q. R. S.	68	Male	Hindu	Married	High School	Retired	13000	55000	13000	42000
16	Mr. T. U. V.	48	Male	Buddhist	Married	College	Engineer	17000	68000	17000	51000
17	Mr. W. X. Y.	32	Male	Hindu	Single	College	Engineer	21000	85000	21000	64000
18	Mr. Z. A. B.	58	Male	Muslim	Married	High School	Teacher	11500	50000	11500	38500
19	Mr. C. D. E.	44	Male	Hindu	Married	College	Engineer	16500	66000	16500	49500
20	Mr. F. G. H.	36	Male	Buddhist	Single	College	Engineer	18500	72000	18500	53500

Run #2 Outlet

Source Testing Review Sheet

Particulate Test

BTU/lb Coal =

lb Coal/hr =

Heat Input =

 $V_{H_2O} (ml) = 10$ V_m (sample volume) [cc] = 57.030 $T_m (^{\circ}R)$ (Temp. of Dig. Gr. Matter) = 565 $^{\circ}R$ $P_{tot} = P_{bar} + P_{static}/13.1 (in Hg) = 29.88$ $\Delta H = 1.104$ $C_p = 0.85$ $K_p = 85.49$ $T_{static} (^{\circ}R) = 563^{\circ}R$ $A_N = (Area of Nozzle) (F + 1) 0.00052$ $V_{H_2O, sat} = (0.0474) (V_{H_2O}) = [cc] 0.474$ $V_{m, sat} = V_m \left(\frac{T_{sat}}{T_m} \right) \left(\frac{P_{tot}}{P_{sat}} \right) = [cc] 53.633$ $B_{H_2O} = \frac{V_{H_2O, sat}}{V_{m, sat} + V_{H_2O, sat}} = [\%] 0.87\%$ $M_d = .44 (\% CO_2) + .32 (\% O_2) + .24 (\% CO + \% N_2) = 26.81$ $M_s = M_d (1 - B_{H_2O}) + 18 (B_{H_2O}) = 28.72$ $V_s = (K_p)(C_p)(VAP)_{tot} \sqrt{\frac{T_{static}}{(P_s)(M_s)}} = [ft/sec] 20.08$ $Q_s = (A_s)(V_s)(CO) = [cfm] 656.5$ $Q_{s, sat} = Q_s \left(\frac{T_{sat}}{T_s} \right) \left(\frac{P_{tot}}{P_{sat}} \right) (1 - B_{H_2O}) = [DSCF] 611.8$ $V_{s, sat} = \frac{Q_{s, sat}}{A_s} = [ft/min] 1122.7$ $C_s (conc) = (W_{part})(5.43)/(V_{m, sat}) = (g/dscf) 0.00401 Part$ $P_{part} (Partic. Pct./hr) = (W_{part})(Q_{s, sat})(CO)/(V_{m, sat})(454) = 0.00012 Chrm.
0.00065 Chrm.$ $\% I_{skKinetic} = \frac{V_{m, sat}}{(A_N)(\Theta)(V_{s, sat})} \times 100\% = 109\%$ $lb Part/MM BTU = \frac{P_{part}}{Heat Input} =$

ALLOWABLE = 16/MM BTU

 $P_{bar} = 29.8$ P_{static} $(VAP)_{tot} = 0.3411$ $A_s = \frac{\pi d^2}{4} (ft) = 0.595$ Θ (Test Time) = .84 $V_{part} [grains] 0.0142 Part
6,000431 Chrm.$ $\% CO_2 O_2$ $\% O_2 20.3$ $\% (CO + N_2) = 1 - (\% CO_2 + \% O_2) = 79.7$

BTU/lb Coal =

lb Coal/hr =

Heat Input =

 $V_{H_2O} (ml) = 88.2$ $V_m (\text{sample volume}) [L/F] = 61.467$ $T_m (^{\circ}R) (T_{avg} \text{ of Dry Gas Meter}) = 565^{\circ}R$ $P_g = P_{bar} + P_{static}/13.6 (P_{H_2O}) = 29.91$ $\Delta H = 1.508$ $C_p = 0.89$ $K_p = 85.49$ $T_{stack} (^{\circ}R) = 551^{\circ}R$ $A_N = (Area \text{ of Nozzle}) [ft^2] 0.00052$ $V_{H_2O, std} = (0.0474) (V_{H_2O}) [scf] 4.1807$ $V_{m, std} = V_m \left(\frac{T_{std}}{T_m} \right) \left(\frac{P_g}{P_{std}} \right) [scf] 57.064$ $B_{H_2O} = \frac{V_{H_2O, std}}{V_{m, std} + V_{H_2O, std}} = [\%] 6.83\%$ $M_d = .44 (\% CO_2) + .32 (\% O_2) + .24 (\% CO + \% N_2) = 28.81$ $M_s = M_d (1 - B_{H_2O}) + 16 (B_{H_2O}) = 28.07$ $V_s = (K_p)(C_p)(\Delta T)_{avg} \sqrt{\frac{T_{stack}}{(P_g)(M_s)}} = [ft^3/scf] 22.07$ $Q_s = (A_s)(V_s)(60) [cfm] 721.7$ $Q_{s, std} = Q_s \left(\frac{T_{std}}{T_g} \right) \left(\frac{P_g}{P_{std}} \right) (1 - B_{H_2O}) [Dscf] 646.5$ $V_{s, std} = \frac{Q_{s, std}}{A_s} [ft^3/min] 1086.3$ $C_s (conc) = (W_{part})(15.43)/(V_{m, std}) = (g/scf) 0.0342$ $P_{part} (Pound Part./hr) = (W_{part})(Q_{s, std})(60)/(V_{m, std})(454) = 0.217$
Part Chromdown
0.0065 Gr $\% \text{ Isokinetic} = \frac{V_{m, std}}{(A_N)(\Theta)(V_{s, std})} \times 100\% = 110\%$ $\text{lb Part/MM BTU} = \frac{P_{part}}{\text{heat input}} =$

ALLOWABLE =

lb/MMBTU

Run #1 Inlet Source Testing Review Sheet Particulate Test

BTU/lb Coal =

lb Coal/hr =

Heat Input =

$V_{H_2O} (ml) = 77.6$

V_m (sample volume) [L] = 50.737

$T_m (^{\circ}R)$ (Temp. of Dry Gas Meter) = 554 $^{\circ}R$

$P_g = P_{atm} + P_{static}/13.1 (in Hg) = 29.91$

$\Delta H = 1458$

$C_p = .83$

$K_p = 85.49$

$T_{stack} (^{\circ}R) = 549$

$A_N = (Area of Nozzle) [ft^2] = 0.00092$

$V_{H_2O} (ml) = (0.0474) (V_{imp}) [scf] = 3.678$

$V_m (scf) = V_m \left(\frac{T_{std}}{T_m} \right) \left(\frac{P_m}{P_{std}} \right) [scf] = 49.523$

$B_{wet} = \frac{V_{H_2O} (ml)}{V_m (scf) + V_{H_2O} (ml)} [\%] = 7.04$

$M_d = .44 (\% CO_2) + .32 (\% O_2) + .24 (\% CO + \% N_2) = 28.81$

$M_s = M_d (1 - B_{wet}) + 18 (B_{wet}) = 28.03$

$V_s = (K_p)(C_p)(VAP)_{wet} \sqrt{\frac{T_{stack}}{(P_s)(M_s)}} [ft/sec] = 21.62$

$Q_s = (A_s)(V_s)(60) [cfm] = 707.2$

$Q_{s, std} = Q_s \left(\frac{T_{std}}{T_s} \right) \left(\frac{P_s}{P_{std}} \right) (1 - B_{wet}) [Dscf] = 634.4$

$V_{s, std} = \frac{Q_{s, std}}{A_s} [ft^3/min] = 1169.06$

$C_s (conc) = (W_{part})(15.43)/(V_{m, std}) (g/scf) = 0.04323 g/scf Part$

$P_{part} (Pound Part/hr) = (W_{part})(Q_{s, std})(60)/(V_{m, std})(454) = 0.2352 lb/hr$

$\% Isokinetic = \frac{V_{m, std}}{(A_N)(\Theta)(V_{s, std})} \times 100\% = 52.4\%$

0.01034 lb/hr
Chromatogram

11.3%

lb Part/MM BTU = $\frac{P_{part}}{\text{Heat Input}} =$

ALLOWABLE = lb/MM BTU

$P_{atm} = 29.8$ $P_{static} =$

$(VAP)_{wet} = 0.3679$

$A_s = \frac{\pi d^2}{4} (ft) = .045$

Θ (Test Time) = 72

$W_{part} [grams] = 0.1361 gm Part.$
 $0.00514 gm Chromatogram$

$\% CO_2 = 0$

$\% O_2 = 20.3$

$\% (CO + N_2) = 1 - (\% CO_2 + \% O_2) = 79.7$

Run #1 Oil-Water Source Testing Review Sheet

Particulate Test

$$\text{BTU/lb Coal} =$$

$$\text{lb Coal/hr} =$$

$$\text{Heat Input} =$$

$$V_{\text{std}} (\text{ml}) = 10$$

$$V_m (\text{sample volume}) [CF] = 44.107$$

$$T_m (^{\circ}\text{R}) (\text{Temp. of Dry Gas Meas.}) = 564^{\circ}\text{R}$$

$$P_{\text{std}} = P_{\text{bar}} + P_{\text{static}}/13.6 (P_{\text{in}} H_2\text{O}) = 29.89$$

$$\Delta H = 1.158$$

$$C_p = .85$$

$$K_p = 85.49$$

$$T_{\text{stack}} (^{\circ}\text{R}) = 562^{\circ}\text{R}$$

$$A_N = (A_{\text{area of Nozzle}}) (F) = 0.00032$$

$$V_{\text{std}} = (0.0474) (V_{\text{std}}) = [SCF] 0.474$$

$$V_m = V_m \left(\frac{T_{\text{std}}}{T_m} \right) \left(\frac{P_m}{P_{\text{std}}} \right) = [SCF] 41.296$$

$$B_{\text{std}} = \frac{V_{\text{std}}}{V_m + V_{\text{std}}} = [\%] 1.1\%$$

$$M_d = .44 (\% \text{CO}_2) + .32 (\% \text{O}_2) + .28 (\% \text{CO} + \% \text{N}_2) = 29.81$$

$$M_s = M_d (1 - B_{\text{std}}) + 18 (B_{\text{std}}) = 28.69$$

$$V_s = (K_p)(C_p)(\Delta P)_{\text{std}} \sqrt{\frac{T_{\text{stack}}}{(P_s)(M_s)}} = [ft^3/sec] 20.66$$

$$Q_s = (A_s)(V_s)(60) = [CFM] 675.49$$

$$Q_{s, \text{std}} = Q_s \left(\frac{T_{\text{std}}}{T_m} \right) \left(\frac{P_m}{P_{\text{std}}} \right) (1 - B_{\text{std}}) = [DSCF] 627.7$$

$$V_{s, \text{std}} = \frac{Q_{s, \text{std}}}{A_s} = [ft^3/min]$$

$$C_s (\text{conc}) = (W_{\text{part}})(15.43)/(V_{s, \text{std}}) = (g/dscf) 0.0096 \text{ g/dscf} \rightarrow \text{Part.}$$

$$P_{\text{part}} (\text{Part. Part. / hr}) = (W_{\text{part}})(Q_{s, \text{std}})(60)/(V_{s, \text{std}})(454) = 0.0245 \%$$

$$W_{\text{part}} (2.00 \text{ lb}) = \#/\text{hr}$$

$$0.0008 \text{ \#}/\text{hr}$$

$$\% \text{Isokinetic} = \frac{V_{s, \text{std}}}{(A_N)(\Theta)(V_{s, \text{std}})} \times 100\% = 95.6\%$$

Chromatogram

$$\text{lb Part/MMBTU} = \frac{P_{\text{part}}}{\text{heat input}} =$$

$$\text{ALLOWABLE} = \text{lb/MMBTU}$$

$$P_{\text{bar}} = 29.8 \quad P_{\text{static}} = .19$$

$$(\Delta P)_{\text{std}} = .3507$$

$$A_s = \frac{\pi d^2}{4} (\mu) = 0.545$$

$$\Theta (\text{Test Time})$$

$$W_{\text{part}} [\text{g/min}] \quad 0.0022 \rightarrow \text{Part.}$$

$$\% \text{CO}_2 = 0$$

$$\% \text{O}_2 = 20.3$$

$$\% (\text{CO} + \text{N}_2) = 1 - (\% \text{CO}_2 + \% \text{O}_2) = 71.7$$

$$0.000406 \rightarrow \text{Chromatogram}$$